

SAC-4P- 5,0-28R/FS SCO RAIL - Sensor/actuator cable



1407318

<https://www.phoenixcontact.com/us/products/1407318>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 4-position, PE-X halogen-free, black RAL 9005, shielded (Tinned copper braided shield), free cable end, on Socket straight M12 SPEEDCON, coding: A, cable length: 5 m, For railway applications

Your advantages

- Easy and safe: 100 % electrically tested plug-in components
- Securely locked by special vibration brake
- Resistant to temperature influences – tested for an extended temperature range and for resistance to temperature shocks
- Reliable signal transmission – 360° shielding in environments with electromagnetic interference

Commercial data

Item number	1407318
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF03
Product key	BF1CCA
Catalog page	Page 131 (C-4-2013)
GTIN	4046356774345
Weight per piece (including packing)	281.3 g
Weight per piece (excluding packing)	287.4 g
Customs tariff number	85444290
Country of origin	PL

SAC-4P- 5,0-28R/FS SCO RAIL - Sensor/actuator cable



1407318

<https://www.phoenixcontact.com/us/products/1407318>

Technical data

Notes

General	Further products with variable cable type and variable cable length can be found in the accessories section
---------	---

Product properties

Product type	Sensor/actuator cable
Application	Railway applications
Number of positions	4
No. of cable outlets	1
Shielded	yes
Coding	A

Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Material specifications

Flammability rating according to UL 94	V0
Seal material	NBR
Material of grip body	PA 6.6
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	PA 6.6
Material for screw connection	Zinc die-cast, nickel-plated

Electrical properties

Insulation resistance	$\geq 100 \text{ M}\Omega$
Nominal voltage U_N	48 V AC
	60 V DC
Nominal current I_N	4 A

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 100
-----------------------------	------------

Signaling

Status display	No
Status display present	No

Connection data

Conductor connection

Tightening torque	0.4 Nm (M12 connector)
-------------------	------------------------

SAC-4P- 5,0-28R/FS SCO RAIL - Sensor/actuator cable



1407318

<https://www.phoenixcontact.com/us/products/1407318>

Connector

Connection 1

Type	free cable end
------	----------------

Connection 2

Type	Socket straight M12 SPEEDCON
Number of positions	4
Locking type	SPEEDCON
Coding type	A

Cable/line

Cable length	5 m
--------------	-----

Shielded black RADOX® [28R]

Dimensional drawing			
Cable weight	56 kg/km		
Number of positions	4		
Shielded	yes		
Cable type	Shielded black RADOX® [28R]		
Conductor structure signal line	19x 0.18 mm		
AWG signal line	20		
Conductor cross section	4x 0.5 mm²		
Wire diameter incl. insulation	1.43 mm		
External cable diameter	5.40 mm ±0.3 mm		
Outer sheath, material	PE-X		
External sheath, color	black RAL 9005		
Conductor material	Tin-plated Cu litz wires		
Material wire insulation	PE-X		
Single wire, color	white 1, white 2, white 3, white 4		
Overall twist	4 wires, twisted		
Optical shield covering	85 %		
Max. conductor resistance	≤ 40.1 Ω/km		
Nominal voltage, cable	600 V AC (Core-ground, U ₀)		
	1000 V AC (Core-ground, U)		
	≤ 720 V AC (core-ground)		
	≤ 1200 V AC (Core-ground, U _m)		

SAC-4P- 5,0-28R/FS SCO RAIL - Sensor/actuator cable



1407318

<https://www.phoenixcontact.com/us/products/1407318>

Test voltage	≤ 900 V DC (Core-ground, V ₀)
	≤ 1500 V DC (Line-line)
	3500 V AC (50 Hz, 5 min.)
	8400 V DC (50 Hz, 5 min.)
Minimum bending radius, fixed installation	3 x D
Minimum bending radius, flexible installation	4 x D
Smallest bending radius, fixed installation	17 mm
Smallest bending radius, movable installation	22 mm
Halogen-free	in accordance with EN 50267-2-1
Flame resistance	EN 60332-1-2
	EN 50266
	EN 50305, 9.1.2
	NF C32-070, 2.1
	NF C32-070, 2.2
	UL 1685, 12 (FT4)
	in accordance with ISO 6722-1 5.22 (UN ECE-R 118.01)
Fume corrosiveness	EN 50267-2-2
Fume toxicity	BS 6853 B.1
	EN 50305, 9.2
Concentration of fumes	BS 6853 D.8.7
	EN 61034-2
	UL 1685, 12 (FT4)
Resistance to oil	according to IRM 902, 72 h at 100 °C
Fire protection in rail vehicles	BS 6853 (Category Ia, Ib, II)
	GM/RT 2130 (Category Ia, Ib, II)
	EN 45545 (Risk level HL1 - HL3)
	DIN 5510 (Fire protection level 1, 2, 3, 4)
	NF F16-101 (Category A1, A2, B)
	NF F16-101 (Class C/F0)
	NFPA 130
Other resistance	Resistance to fuels (according to IRM 903, 168 h at 70 °C)
Ambient temperature (operation)	-50 °C ... 120 °C (cable, fixed installation)
	-25 °C ... 90 °C (Cable, flexible installation)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65
Ambient temperature (operation)	-40 °C ... 85 °C (Plug / socket)

Standards and regulations

M12

Standard designation	M12 connector
----------------------	---------------

SAC-4P- 5,0-28R/FS SCO RAIL - Sensor/actuator cable



1407318
<https://www.phoenixcontact.com/us/products/1407318>

Standards/specifications	IEC 61076-2-101
Standard designation	Shock, vibration
Standards/specifications	EN 50155

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com