

# SAC-4P-10,0-28R/FR SCO RAIL - Sensor/actuator cable



1407322

<https://www.phoenixcontact.com/us/products/1407322>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 4-position, PE-X halogen-free, black RAL 9005, shielded, free cable end, on Socket angled M12 SPEEDCON, coding: A, cable length: 10 m, For railway applications

## Your advantages

- Easy and safe: 100 % electrically tested plug-in components
- Securely locked by special vibration brake
- Resistant to temperature influences – tested for an extended temperature range and for resistance to temperature shocks
- Reliable signal transmission – 360° shielding in environments with electromagnetic interference

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 1407322             |
| Packing unit                         | 1 pc                |
| Minimum order quantity               | 1 pc                |
| Sales key                            | BF03                |
| Product key                          | BF1CCA              |
| Catalog page                         | Page 131 (C-4-2013) |
| GTIN                                 | 4046356774383       |
| Weight per piece (including packing) | 538 g               |
| Weight per piece (excluding packing) | 560.3 g             |
| Customs tariff number                | 85444290            |
| Country of origin                    | PL                  |

# SAC-4P-10,0-28R/FR SCO RAIL - Sensor/actuator cable



1407322

<https://www.phoenixcontact.com/us/products/1407322>

## Technical data

### Notes

|         |                                                                                                             |
|---------|-------------------------------------------------------------------------------------------------------------|
| General | Further products with variable cable type and variable cable length can be found in the accessories section |
|---------|-------------------------------------------------------------------------------------------------------------|

### Product properties

|                      |                       |
|----------------------|-----------------------|
| Product type         | Sensor/actuator cable |
| Application          | Railway applications  |
| Number of positions  | 4                     |
| No. of cable outlets | 1                     |
| Shielded             | yes                   |
| Coding               | A                     |

### Insulation characteristics

|                      |    |
|----------------------|----|
| Overvoltage category | II |
| Degree of pollution  | 3  |

### Material specifications

|                                        |                              |
|----------------------------------------|------------------------------|
| Flammability rating according to UL 94 | V0                           |
| Seal material                          | NBR                          |
| Material of grip body                  | PA 6.6                       |
| Contact material                       | CuSn                         |
| Contact surface material               | Ni/Au                        |
| Contact carrier material               | PA 6.6                       |
| Material for screw connection          | Zinc die-cast, nickel-plated |

### Electrical properties

|                       |                            |
|-----------------------|----------------------------|
| Insulation resistance | $\geq 100 \text{ M}\Omega$ |
| Nominal voltage $U_N$ | 48 V AC                    |
|                       | 60 V DC                    |
| Nominal current $I_N$ | 4 A                        |

### Mechanical properties

#### Mechanical data

|                             |            |
|-----------------------------|------------|
| Insertion/withdrawal cycles | $\geq 100$ |
|-----------------------------|------------|

### Signaling

|                        |    |
|------------------------|----|
| Status display         | no |
| Status display present | No |

### Connection data

#### Conductor connection

|                   |                        |
|-------------------|------------------------|
| Tightening torque | 0.4 Nm (M12 connector) |
|-------------------|------------------------|

# SAC-4P-10,0-28R/FR SCO RAIL - Sensor/actuator cable



1407322

<https://www.phoenixcontact.com/us/products/1407322>

## Connector

### Connection 1

|      |                |
|------|----------------|
| Type | free cable end |
|------|----------------|

### Connection 2

|                     |                            |
|---------------------|----------------------------|
| Type                | Socket angled M12 SPEEDCON |
| Number of positions | 4                          |
| Locking type        | SPEEDCON                   |
| Coding type         | A                          |

## Cable/line

|              |      |
|--------------|------|
| Cable length | 10 m |
|--------------|------|

### Shielded black RADOX® [28R]

|                                 |                                                                                                                                                 |
|---------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| Dimensional drawing             |                                                              |
| Cable weight                    | 56 kg/km                                                                                                                                        |
| Number of positions             | 4                                                                                                                                               |
| Shielded                        | yes                                                                                                                                             |
| Cable type                      | Shielded black RADOX® [28R]                                                                                                                     |
| Conductor structure signal line | 19x 0.18 mm                                                                                                                                     |
| AWG signal line                 | 20                                                                                                                                              |
| Conductor cross section         | 4x 0.5 mm²                                                                                                                                      |
| Wire diameter incl. insulation  | 1.43 mm                                                                                                                                         |
| External cable diameter         | 5.40 mm ±0.3 mm                                                                                                                                 |
| Outer sheath, material          | PE-X                                                                                                                                            |
| External sheath, color          | black RAL 9005                                                                                                                                  |
| Conductor material              | Tin-plated Cu litz wires                                                                                                                        |
| Material wire insulation        | PE-X                                                                                                                                            |
| Single wire, color              | white 1, white 2, white 3, white 4                                                                                                              |
| Overall twist                   | 4 wires, twisted                                                                                                                                |
| Optical shield covering         | 85 %                                                                                                                                            |
| Max. conductor resistance       | ≤ 40.1 Ω/km                                                                                                                                     |
| Nominal voltage, cable          | 600 V AC (Core-ground, U <sub>0</sub> )<br>1000 V AC (Core-ground, U)<br>≤ 720 V AC (core-ground)<br>≤ 1200 V AC (Core-ground, U <sub>m</sub> ) |

# SAC-4P-10,0-28R/FR SCO RAIL - Sensor/actuator cable



1407322

<https://www.phoenixcontact.com/us/products/1407322>

|                                               |                                                            |
|-----------------------------------------------|------------------------------------------------------------|
| Test voltage                                  | ≤ 900 V DC (Core-ground, V <sub>0</sub> )                  |
|                                               | ≤ 1500 V DC (Line-line)                                    |
|                                               | 3500 V AC (50 Hz, 5 min.)                                  |
|                                               | 8400 V DC (50 Hz, 5 min.)                                  |
| Minimum bending radius, fixed installation    | 3 x D                                                      |
| Minimum bending radius, flexible installation | 4 x D                                                      |
| Smallest bending radius, fixed installation   | 17 mm                                                      |
| Smallest bending radius, movable installation | 22 mm                                                      |
| Halogen-free                                  | in accordance with EN 50267-2-1                            |
| Flame resistance                              | EN 60332-1-2                                               |
|                                               | EN 50266                                                   |
|                                               | EN 50305, 9.1.2                                            |
|                                               | NF C32-070, 2.1                                            |
|                                               | NF C32-070, 2.2                                            |
|                                               | UL 1685, 12 (FT4)                                          |
|                                               | in accordance with ISO 6722-1 5.22 (UN ECE-R 118.01)       |
| Fume corrosiveness                            | EN 50267-2-2                                               |
| Fume toxicity                                 | BS 6853 B.1                                                |
|                                               | EN 50305, 9.2                                              |
| Concentration of fumes                        | BS 6853 D.8.7                                              |
|                                               | EN 61034-2                                                 |
|                                               | UL 1685, 12 (FT4)                                          |
| Resistance to oil                             | according to IRM 902, 72 h at 100 °C                       |
| Fire protection in rail vehicles              | BS 6853 (Category Ia, Ib, II)                              |
|                                               | GM/RT 2130 (Category Ia, Ib, II)                           |
|                                               | EN 45545 (Risk level HL1 - HL3)                            |
|                                               | DIN 5510 (Fire protection level 1, 2, 3, 4)                |
|                                               | NF F16-101 (Category A1, A2, B)                            |
|                                               | NF F16-101 (Class C/F0)                                    |
|                                               | NFPA 130                                                   |
| Other resistance                              | UNI CEI 11170 (Risk level LR1 - LR4)                       |
|                                               | Resistance to fuels (according to IRM 903, 168 h at 70 °C) |
| Ambient temperature (operation)               | -50 °C ... 120 °C (cable, fixed installation)              |
|                                               | -25 °C ... 90 °C (Cable, flexible installation)            |

## Environmental and real-life conditions

### Ambient conditions

|                                 |                                  |
|---------------------------------|----------------------------------|
| Degree of protection            | IP65                             |
| Ambient temperature (operation) | -40 °C ... 85 °C (Plug / socket) |

## Standards and regulations

### M12

|                      |               |
|----------------------|---------------|
| Standard designation | M12 connector |
|----------------------|---------------|

# SAC-4P-10,0-28R/FR SCO RAIL - Sensor/actuator cable



1407322  
<https://www.phoenixcontact.com/us/products/1407322>

|                          |                  |
|--------------------------|------------------|
| Standards/specifications | IEC 61076-2-101  |
| Standard designation     | Shock, vibration |
| Standards/specifications | EN 50155         |

# SAC-4P-10,0-28R/FR SCO RAIL - Sensor/actuator cable




1407322

<https://www.phoenixcontact.com/us/products/1407322>


## Drawings

Schematic diagram



Pin assignment M12 socket, 4-pos., A-coded, view female side

Circuit diagram




# SAC-4P-10,0-28R/FR SCO RAIL - Sensor/actuator cable

1407322

<https://www.phoenixcontact.com/us/products/1407322>

Dimensional drawing



Socket M12-SPEEDCON, angled, shielded

# SAC-4P-10,0-28R/FR SCO RAIL - Sensor/actuator cable



1407322

<https://www.phoenixcontact.com/us/products/1407322>

## Approvals

📄 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1407322>



**EAC-RoHS**

Approval ID: RU D-DE.HB35.B.00387

# SAC-4P-10,0-28R/FR SCO RAIL - Sensor/actuator cable



1407322  
<https://www.phoenixcontact.com/us/products/1407322>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27060311 |
| ECLASS-12.0 | 27060311 |
| ECLASS-13.0 | 27060311 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC001855 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 26121600 |
|-------------|----------|

1407322  
<https://www.phoenixcontact.com/us/products/1407322>

Environmental product compliance

|                                         |                                                             |
|-----------------------------------------|-------------------------------------------------------------|
| EU RoHS                                 |                                                             |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                                          |
| China RoHS                              |                                                             |
| Environment friendly use period (EFUP)  | EFUP-E                                                      |
|                                         | No hazardous substances above the limits                    |
| EU REACH SVHC                           |                                                             |
| REACH candidate substance (CAS No.)     | 6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol(CAS: 119-47-1) |
| SCIP                                    | 35b8302f-44e1-497c-aa61-0671363fed8c                        |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)