

HC-EVO-B10-HLFS-PLBK - Housing



1407626

<https://www.phoenixcontact.com/ca/products/1407626>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



HEAVYCON EVO sleeve housing, plastic, with bayonet flange for EVO screw connection, B10, for single locking latch, height: 60.5 mm, without EVO screw connection

Your advantages

- Flexible cable outlet direction, lateral or straight
- Lower costs than metal version
- Low weight
- Lower risk of condensation

Commercial data

Item number	1407626
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF27
Product key	BF7APL
Catalog page	Page 604 (C-2-2019)
GTIN	4046356776882
Weight per piece (including packing)	70.2 g
Weight per piece (excluding packing)	70 g
Customs tariff number	85389099
Country of origin	PL

HC-EVO-B10-HLFS-PLBK - Housing

1407626

<https://www.phoenixcontact.com/ca/products/1407626>



Technical data


Notes

General	For contact inserts HC-B10, BB18, DD42, M, K8/24, HV03-I-PT, HC- 3-E...C
---------	--

Product properties

Product type	Housing with locking latch
Housing type	Sleeve housing
Product family	HC-EVO-B
Application	Standard
Type	B10
No. of cable outlets	1
Cable outlet	straight
Pg screw connection	none

Dimensions

Dimensional drawing	
Width	44 mm
Height	60.5 mm
Length	73 mm

Material specifications

Flammability rating according to UL 94	V0 (Housing)
Housing material	PA
Impact strength	IK08

Mechanical properties

Mechanical data

Locking type	Pin
--------------	-----

Mounting

Assembly instructions	The sleeve base housing must be supplemented with the EVO screw connection. The EVO screw connection is available in four sizes. It facilitates the creation of a straight or a side cable outlet. The EVO screw connection is mounted with the aid of, for example, a pipe wrench
-----------------------	--

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP66
----------------------	------

HC-EVO-B10-HLFS-PLBK - Housing



1407626

<https://www.phoenixcontact.com/ca/products/1407626>

Enclosure rating (NEMA)	12 (UL 50e)
Impact strength	IK08
Ambient temperature (operation)	-40 °C ... 125 °C

HC-EVO-B10-HLFS-PLBK - Housing


1407626

<https://www.phoenixcontact.com/ca/products/1407626>



Drawings

Dimensional drawing



Dimensional drawing

HC-EVO-B10-HLFS-PLBK - Housing




1407626


<https://www.phoenixcontact.com/ca/products/1407626>

Approvals


To download certificates, visit the product detail page: <https://www.phoenixcontact.com/ca/products/1407626>




DNV
Approval ID: TAE000037S




cUL Recognized
Approval ID: E255026



UL Recognized
Approval ID: E255026



EAC
Approval ID: RU C-DE.AI30.B.01102



EAC
Approval ID: RU C-DE.BL08.B.00511

cULus Recognized

HC-EVO-B10-HLFS-PLBK - Housing

1407626

<https://www.phoenixcontact.com/ca/products/1407626>



Classifications

ECLASS

ECLASS-11.0	27440202
ECLASS-12.0	27440202
ECLASS-13.0	27440202

ETIM

ETIM 9.0	EC000437
----------	----------

UNSPSC

UNSPSC 21.0	31261500
-------------	----------

HC-EVO-B10-HLFS-PLBK - Housing



1407626

<https://www.phoenixcontact.com/ca/products/1407626>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd
8240 Parkhill Drive
Milton, Ontario L9T 5V7
1-800-890-2820
cdinfo@phoenixcontact.ca