

1408737

https://www.phoenixcontact.com/us/products/1408737

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



HEAVYCON ADVANCE B10 box mounting base, for M6 screw locking, salt-water-resistant aluminum, with 2 x M20 thread, without surface coating

## Commercial data

Item number	1408737
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	BF58
Product key	BF7AAA
Catalog page	Page 235 (NTK-2012)
GTIN	4046356583343
Weight per piece (including packing)	446.2 g
Weight per piece (excluding packing)	446.2 g
Customs tariff number	85389099
Country of origin	CN



1408737

https://www.phoenixcontact.com/us/products/1408737

# Technical data

#### Notes

General For contact inserts HC-B10, BB18, DD42, M, K8/24	
----------------------------------------------------------	--

## Product properties

Product type	Housing with screw locking
Housing type	Box mounting bases
Application	Offshore
Туре	B10
No. of cable outlets	2
Type of the screw connection	2x M20
Shielded	yes
Cable outlet	lateral
Pg screw connection	none

## Dimensions

Dimensional drawing	8 9.5 95.5 - 64.5 - 45 - 57 - 57
Width	45 mm
Height	68 mm
Length	105 mm

# Material specifications

Housing material	Die-cast aluminum, corrosion resistant
Housing surface material	uncoated

### Environmental and real-life conditions

#### Ambient conditions

Degree of protection	IP66
	IP68 (0.2 bar/24 h)
	IP69K
Enclosure rating (NEMA)	4 (NEMA 250)
	4X (NEMA 250)
	6P (NEMA 250)
	12 (NEMA 250)
Ambient temperature (operation)	-40 °C 125 °C

## Mechanical properties

Med	chanic	al da	ta



1408737

https://www.phoenixcontact.com/us/products/1408737

Type of the screw connection	2x M20
Locking type	Nut
Mounting	
Assembly note	To ensure optimum shielding, any insulating powder coating must be removed from the housing support area on the control cabinet panel





1408737

https://www.phoenixcontact.com/us/products/1408737

# Drawings

## Dimensional drawing





Dimensional drawing



1408737

https://www.phoenixcontact.com/us/products/1408737

# Classifications

### **ECLASS**

ECLASS-11.0	27440202
ECLASS-13.0	27440202



1408737

https://www.phoenixcontact.com/us/products/1408737

# Environmental product compliance

EU REACH SVHC

REACH candidate substance (CAS No.)

No substance above 0.1 wt%



1408737

https://www.phoenixcontact.com/us/products/1408737

#### Accessories

### HC-B 10-TMS-SD-IP50 - Protective cover

1690749

https://www.phoenixcontact.com/us/products/1690749



Protective cover B10, with clip locking, protective cover material: PA, height: 31.2 mm, seal: no, with lanyard

### HC-B 10-TMS-SD-IP65 - Protective cover

1690781

https://www.phoenixcontact.com/us/products/1690781



HEAVYCON ADVANCE IP65 protective cover B10, for panel mounting side, with screw locking, with retaining cord, diameter of retaining cord eyelet 3 mm



1408737

https://www.phoenixcontact.com/us/products/1408737

#### G-INS-M20-S68N-PNES-GY - Cable gland

1411125

https://www.phoenixcontact.com/us/products/1411125



Cable gland, material for screw connection: PA, application: Standard, external cable diameter 6 mm  $\dots$  12 mm, shielding: no, connecting thread: M20 x 1.5, color: silver-grey RAL 7001

#### G-INS-M20-S68N-PNES-BK - Cable gland

1411133

https://www.phoenixcontact.com/us/products/1411133



Cable gland, material for screw connection: PA, application: Standard, external cable diameter 6 mm  $\dots$  12 mm, shielding: no, connecting thread: M20 x 1.5, color: jet black RAL 9005



1408737

https://www.phoenixcontact.com/us/products/1408737

### G-INS-M20-S68N-NNES-S - Cable gland

1411163

https://www.phoenixcontact.com/us/products/1411163



Cable gland, material for screw connection: Brass, nickel-plated, application: Standard, external cable diameter 6 mm  $\dots$  12 mm, shielding: no, connecting thread: M20 x 1.5, color: silver, with O-ring

### HC-M-KV-M20(11-16) - Cable gland

1645998

https://www.phoenixcontact.com/us/products/1645998



Metal screw connection up to 5 bar, thread length: 6 mm, cable diameter: 11 - 16 mm, WAF 27, screw connection: M20



1408737

https://www.phoenixcontact.com/us/products/1408737

### G-INSEC-M20-S68N-NCRS-S - Cable gland

1411189

https://www.phoenixcontact.com/us/products/1411189



Cable gland, material for screw connection: Brass, nickel-plated, application: EMC, external cable diameter 9 mm  $\dots$  13 mm, shielding: yes, connecting thread: M20 x 1.5, color: silver, with O-ring

#### HC-M-KV-Z-M20 - Cable gland

1646146

https://www.phoenixcontact.com/us/products/1646146



Metal screw connection with strain relief clamp, thread length: 6 mm, cable sealing area: 7.5 - 15 mm, clamping area: 11 - 17 mm, SW 24, screw connection: M20



1408737

https://www.phoenixcontact.com/us/products/1408737

### HC-M-KV-T-M20 - Cable gland

1646188

https://www.phoenixcontact.com/us/products/1646188



Metal screw connection with cable bend protection and strain relief, thread length: 6 mm, cable sealing area: 7.5 - 15 mm, clamping area: 10 - 16 mm, SW 24, screw connection: M20

### REDUC-M-KV-M20/M16 - Reducing adapter

1647611

https://www.phoenixcontact.com/us/products/1647611

Reducing adapter, connecting thread: M20 x 1.5, color: silver, with O-ring







1408737

https://www.phoenixcontact.com/us/products/1408737

#### ENLAR-M-KV-M20/M25 - Extension adapter

1647666

https://www.phoenixcontact.com/us/products/1647666

Extension adapter, connecting thread: M20 x 1.5, color: silver, with O-ring





#### HC-M-BS-M20 - Screw plug

1645846

https://www.phoenixcontact.com/us/products/1645846

Screw plug, material for screw connection: Brass, nickel-plated, connecting thread: M20 x 1.5, color: silver



Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com