1408850

https://www.phoenixcontact.com/us/products/1408850

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



HEAVYCON ADVANCE B16 box mounting base, for M6 screw locking, salt-water-resistant aluminum, with 2 x M32 thread, without surface coating

Commercial data

Item number	1408850
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	BF58
Product key	BF7AAA
Catalog page	Page 506 (C-4-2013)
GTIN	4046356583459
Weight per piece (including packing)	450.8 g
Weight per piece (excluding packing)	450.8 g
Customs tariff number	85389099
Country of origin	PL

PHŒNIX

1408850

https://www.phoenixcontact.com/us/products/1408850

Technical data

Notes

General	For contact inserts HC-B16, BB32, D40, DD72, HS6, M, K
Product properties	
Product type	Housing with screw locking
Housing type	Box mounting bases
Application	Offshore
Туре	B16
No. of cable outlets	2
Type of the screw connection	2x M32
Shielded	yes
Cable outlet	lateral
Pg screw connection	none

Dimensions

Dimensional drawing	
Width	45 mm
Height	72 mm
Length	125.5 mm

Material specifications

Housing material	Die-cast aluminum, corrosion resistant
Housing surface material	uncoated

Environmental and real-life conditions

Ambient conditions	
Degree of protection	IP66
	IP68 (0.2 bar/24 h)
	IP69K
Enclosure rating (NEMA)	4 (NEMA 250)
	4X (NEMA 250)
	6P (NEMA 250)
	12 (NEMA 250)
Impact strength	IK09
Ambient temperature (operation)	-40 °C 125 °C

Mechanical properties

1408850

https://www.phoenixcontact.com/us/products/1408850

لكا	PHŒN CONT/	IX
Ľ	CONTA	

Mechanical data Type of the screw connection 2x M32 Locking type Nut

Mounting


Assembly note	To ensure optimum shielding, any insulating powder coating
	must be removed from the housing support area on the control
	cabinet panel




1408850

https://www.phoenixcontact.com/us/products/1408850

Drawings





Dimensional drawing

1408850

https://www.phoenixcontact.com/us/products/1408850



Classifications

ECLASS

ECLASS-11.0	27440202
ECLASS-13.0	27440202

1408850

https://www.phoenixcontact.com/us/products/1408850

DPHŒNIX CONTACT

Environmental product compliance

EU REACH SVHC

REACH candidate substance (CAS No.)

No substance above 0.1 wt%

1408850

https://www.phoenixcontact.com/us/products/1408850



Accessories

HC-B 16-TMS-SD-IP65 - Protective cover

1690794

https://www.phoenixcontact.com/us/products/1690794



HEAVYCON ADVANCE IP65 protective cover B16, for panel mounting side, with screw locking, with retaining cord, diameter of retaining cord eyelet 3 mm

HC-B 16-TMS-SD-IP50 - Protective cover

1690752

https://www.phoenixcontact.com/us/products/1690752



Protective cover B16, with clip locking, protective cover material: PA, height: 31.2 mm, seal: no, with lanyard

1408850

https://www.phoenixcontact.com/us/products/1408850



G-INS-M32-M68N-PNES-GY - Cable gland

1411127

https://www.phoenixcontact.com/us/products/1411127



Cable gland, material for screw connection: PA, application: Standard, external cable diameter 15 mm ... 21 mm, shielding: no, connecting thread: M32 x 1.5, color: silver-grey RAL 7001

G-INS-M32-M68N-PNES-BK - Cable gland

1411136 https://www.phoenixcontact.com/us/products/1411136



Cable gland, material for screw connection: PA, application: Standard, external cable diameter 15 mm ... 21 mm, shielding: no, connecting thread: M32 x 1.5, color: jet black RAL 9005

1408850

https://www.phoenixcontact.com/us/products/1408850



G-INS-M32-M68N-NNES-S - Cable gland

1411166

https://www.phoenixcontact.com/us/products/1411166



Cable gland, material for screw connection: Brass, nickel-plated, application: Standard, external cable diameter 15 mm ... 21 mm, shielding: no, connecting thread: M32 x 1.5, color: silver, with O-ring

HC-M-KV-M32(19-27) - Cable gland

1646010 https://www.phoenixcontact.com/us/products/1646010



Metal screw connection up to 5 bar, thread length: 8 mm, cable diameter: 19 - 27 mm, WAF 43, screw connection: M32

1408850

https://www.phoenixcontact.com/us/products/1408850



G-INSEC-M32-M68N-NCRS-S - Cable gland

1411191

https://www.phoenixcontact.com/us/products/1411191



Cable gland, material for screw connection: Brass, nickel-plated, application: EMC, external cable diameter 14 mm ... 21 mm, shielding: yes, connecting thread: M32 x 1.5, color: silver, with O-ring

HC-M-KV-Z-M32 - Cable gland

1646162 https://www.phoenixcontact.com/us/products/1646162



Metal screw connection with strain relief clamp, thread length: 8 mm, cable sealing area: 18 - 27 mm, clamping area: 19 - 30 mm, SW 40, screw connection: M32

1408850

https://www.phoenixcontact.com/us/products/1408850



HC-M-KV-T-M32 - Cable gland

1646201

https://www.phoenixcontact.com/us/products/1646201

Metal screw connection with cable bend protection and strain relief, thread length: 8 mm, cable sealing area: 18 - 27 mm, clamping area: 20 - 30 mm, SW 40, screw connection: M32



REDUC-M-KV-M32/M25 - Reducing adapter

1647637 https://www.phoenixcontact.com/us/products/1647637

Reducing adapter, connecting thread: M32 x 1.5, color: silver, with O-ring



1408850

https://www.phoenixcontact.com/us/products/1408850

ENLAR-M-KV-M32/M40 - Extension adapter

1647682

https://www.phoenixcontact.com/us/products/1647682

Extension adapter, connecting thread: M32 x 1.5, color: silver, with O-ring



HC-M-BS-M32 - Screw plug

1645862 https://www.phoenixcontact.com/us/products/1645862



Screw plug, material for screw connection: Brass, nickel-plated, connecting thread: M32 x 1.5, color: silver

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com