

1408931

https://www.phoenixcontact.com/us/products/1408931

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



HEAVYCON ADVANCE B24 box mounting base, for M6 screw locking, salt-water-resistant aluminum, with 2 x M25 thread, without surface coating

### Commercial data

Item number	1408931
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	BF58
Product key	BF7AAA
Catalog page	Page 235 (NTK-2012)
GTIN	4046356583589
Weight per piece (including packing)	535 g
Weight per piece (excluding packing)	535 g
Customs tariff number	85389099
Country of origin	CN



1408931

https://www.phoenixcontact.com/us/products/1408931

### Technical data

### Notes

General	For contact inserts HC-B24, BB46, D64, DD104, M, K
Product properties	

Product type	Housing with screw locking
Housing type	Box mounting bases
Application	Offshore
Туре	B24
No. of cable outlets	2
Type of the screw connection	2x M25
Shielded	yes
Cable outlet	lateral
Pg screw connection	none

### Dimensions

Dimensional drawing	2 9 05.5 05.5 152 05.5 57
Width	45 mm
Height	72 mm
Length	152 mm

### Material specifications

Housing material	Die-cast aluminum, corrosion resistant
Housing surface material	uncoated

### Environmental and real-life conditions

#### Ambient conditions

Degree of protection	IP66
	IP68 (0.2 bar/24 h)
	IP69K
Enclosure rating (NEMA)	4 (NEMA 250)
	4X (NEMA 250)
	6P (NEMA 250)
	12 (NEMA 250)
Impact strength	IK09
Ambient temperature (operation)	-40 °C 125 °C

### Mechanical properties



1408931

https://www.phoenixcontact.com/us/products/1408931

#### Mechanical data

Type of the screw connection	2x M25
Locking type	Nut

### Mounting

Assembly note	To ensure optimum shielding, any insulating powder coating must be removed from the housing support area on the control cabinet panel




1408931

https://www.phoenixcontact.com/us/products/1408931

### Drawings

### Dimensional drawing



Dimensional drawing



1408931

https://www.phoenixcontact.com/us/products/1408931

### Classifications

### **ECLASS**

ECLASS-11.0	27440202
ECLASS-13.0	27440202



1408931

https://www.phoenixcontact.com/us/products/1408931

### Environmental product compliance

EU REACH SVHC

REACH candidate substance (CAS No.)

No substance above 0.1 wt%



1408931

https://www.phoenixcontact.com/us/products/1408931

#### Accessories

#### HC-B 24-TMS-SD-IP65 - Protective cover

1690804

https://www.phoenixcontact.com/us/products/1690804



HEAVYCON ADVANCE B24 IP65 protective cover, for panel mounting side, with screw locking, with retaining cord, diameter of retaining cord eyelet: 3 mm

#### HC-B 24-TMS-SD-IP50 - Protective cover

1690765

https://www.phoenixcontact.com/us/products/1690765



Protective cover B24, with clip locking, protective cover material: PA, height: 31.2 mm, seal: no, with lanyard



1408931

https://www.phoenixcontact.com/us/products/1408931

### G-INS-M25-M68N-PNES-GY - Cable gland

1411126

https://www.phoenixcontact.com/us/products/1411126



Cable gland, material for screw connection: PA, application: Standard, external cable diameter 11 mm  $\dots$  17 mm, shielding: no, connecting thread: M25 x 1.5, color: silver-grey RAL 7001

#### G-INS-M25-M68N-PNES-BK - Cable gland

1411134

https://www.phoenixcontact.com/us/products/1411134



Cable gland, material for screw connection: PA, application: Standard, external cable diameter 11 mm  $\dots$  17 mm, shielding: no, connecting thread: M25 x 1.5, color: jet black RAL 9005



1408931

https://www.phoenixcontact.com/us/products/1408931

### G-INS-M25-M68N-NNES-S - Cable gland

1411165

https://www.phoenixcontact.com/us/products/1411165



Cable gland, material for screw connection: Brass, nickel-plated, application: Standard, external cable diameter 11 mm  $\dots$  17 mm, shielding: no, connecting thread: M25 x 1.5, color: silver, with O-ring

#### HC-M-KV-M25(14-21) - Cable gland

1646007

https://www.phoenixcontact.com/us/products/1646007



Metal screw connection up to 5 bar, thread length: 7 mm, cable diameter: 14 - 21 mm, WAF 34, screw connection: M25



1408931

https://www.phoenixcontact.com/us/products/1408931

### G-INSEC-M25-S68N-NCRS-S - Cable gland

1411190

https://www.phoenixcontact.com/us/products/1411190



Cable gland, material for screw connection: Brass, nickel-plated, application: EMC, external cable diameter 11 mm  $\dots$  16 mm, shielding: yes, connecting thread: M25 x 1.5, color: silver, with O-ring

#### G-INESR-M25-M68N-NEPDS-S - Cable gland

1415193

https://www.phoenixcontact.com/us/products/1415193



Cable gland, material for screw connection: Brass, nickel-plated, application: Standard, external cable diameter 9 mm ... 17 mm, shielding: no, connecting thread: M25 x 1.5, color: silver, with external strain relief, with O-ring




1408931

https://www.phoenixcontact.com/us/products/1408931

#### HC-M-KV-T-M25 - Cable gland

1646191

https://www.phoenixcontact.com/us/products/1646191





### REDUC-M-KV-M25/M20 - Reducing adapter

1647624

https://www.phoenixcontact.com/us/products/1647624

Reducing adapter, connecting thread: M25 x 1.5, color: silver, with O-ring







1408931

https://www.phoenixcontact.com/us/products/1408931

#### ENLAR-M-KV-M25/M32 - Extension adapter

1647679

https://www.phoenixcontact.com/us/products/1647679

Extension adapter, connecting thread: M25 x 1.5, color: silver, with O-ring





#### HC-M-BS-M25 - Screw plug

1645859

https://www.phoenixcontact.com/us/products/1645859

Screw plug, material for screw connection: Brass, nickel-plated, connecting thread: M25 x 1.5, color: silver



Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com