

1408999

https://www.phoenixcontact.com/us/products/1408999

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



HEAVYCON ADVANCE B24 coupling housing, for M6 screw locking, salt-water-resistant aluminum, with 1 \times M32 thread, straight cable outlet, without surface coating

Commercial data

Item number	1408999
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	BF58
Product key	BF7AAA
Catalog page	Page 235 (NTK-2012)
GTIN	4046356583640
Weight per piece (including packing)	546.9 g
Weight per piece (excluding packing)	546.9 g
Customs tariff number	85389099
Country of origin	CN



1408999

https://www.phoenixcontact.com/us/products/1408999

Technical data

Notes

General For contact inserts HC-B24, BB46, D64, DD104, M, K
--

Product properties

Product type	Housing with screw locking
Housing type	Coupling housings
Application	Offshore
Туре	B24
No. of cable outlets	1
Type of the screw connection	1x M32
Fixing screws	M6
Shielded	yes
Cable outlet	straight
Pg screw connection	none

Dimensions

Dimensional drawing	2 9 05.5 05.5 05.5 05.5 05.5 05.5 05.5 05
Width	45 mm
Height	72 mm
Length	152 mm

Material specifications

Housing material	Die-cast aluminum, corrosion resistant
Housing surface material	uncoated

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP66
	IP68 (0.2 bar/24 h)
	IP69K
Enclosure rating (NEMA)	4 (NEMA 250)
	4X (NEMA 250)
	6P (NEMA 250)
	12 (NEMA 250)
Impact strength	IK09
Ambient temperature (operation)	-40 °C 125 °C



1408999

https://www.phoenixcontact.com/us/products/1408999

Mechanical properties

Mechanical data

Type of the screw connection	1x M32
Locking type	Nut

Mounting

Fixing screws	M6




1408999

https://www.phoenixcontact.com/us/products/1408999

Drawings

Dimensional drawing



Dimensional drawing



1408999

https://www.phoenixcontact.com/us/products/1408999

Classifications

ECLASS

ECLASS-11.0	27440202
ECLASS-13.0	27440202



1408999

https://www.phoenixcontact.com/us/products/1408999

Environmental product compliance

EU REACH SVHC

REACH candidate substance (CAS No.)

No substance above 0.1 wt%



1408999

https://www.phoenixcontact.com/us/products/1408999

Accessories

HC-B 24-TMS-SD-IP65 - Protective cover

1690804

https://www.phoenixcontact.com/us/products/1690804



HEAVYCON ADVANCE B24 IP65 protective cover, for panel mounting side, with screw locking, with retaining cord, diameter of retaining cord eyelet: 3 mm

HC-B 24-TMS-SD-IP50 - Protective cover

1690765

https://www.phoenixcontact.com/us/products/1690765



Protective cover B24, with clip locking, protective cover material: PA, height: 31.2 mm, seal: no, with lanyard



1408999

https://www.phoenixcontact.com/us/products/1408999

G-INS-M32-M68N-PNES-GY - Cable gland

1411127

https://www.phoenixcontact.com/us/products/1411127



Cable gland, material for screw connection: PA, application: Standard, external cable diameter 15 mm \dots 21 mm, shielding: no, connecting thread: M32 x 1.5, color: silver-grey RAL 7001

G-INS-M32-M68N-PNES-BK - Cable gland

1411136

https://www.phoenixcontact.com/us/products/1411136



Cable gland, material for screw connection: PA, application: Standard, external cable diameter 15 mm \dots 21 mm, shielding: no, connecting thread: M32 x 1.5, color: jet black RAL 9005



1408999

https://www.phoenixcontact.com/us/products/1408999

G-INS-M32-M68N-NNES-S - Cable gland

1411166

https://www.phoenixcontact.com/us/products/1411166



Cable gland, material for screw connection: Brass, nickel-plated, application: Standard, external cable diameter 15 mm ... 21 mm, shielding: no, connecting thread: M32 x 1.5, color: silver, with O-ring

HC-M-KV-M32(19-27) - Cable gland

1646010

https://www.phoenixcontact.com/us/products/1646010



Metal screw connection up to 5 bar, thread length: 8 mm, cable diameter: 19 - 27 mm, WAF 43, screw connection: M32



1408999

https://www.phoenixcontact.com/us/products/1408999

G-INSEC-M32-M68N-NCRS-S - Cable gland

1411191

https://www.phoenixcontact.com/us/products/1411191



Cable gland, material for screw connection: Brass, nickel-plated, application: EMC, external cable diameter 14 mm ... 21 mm, shielding: yes, connecting thread: M32 x 1.5, color: silver, with O-ring

HC-M-KV-Z-M32 - Cable gland

1646162

https://www.phoenixcontact.com/us/products/1646162

Metal screw connection with strain relief clamp, thread length: 8 mm, cable sealing area: 18 - 27 mm, clamping area: 19 - 30 mm, SW 40, screw connection: M32






1408999

https://www.phoenixcontact.com/us/products/1408999

HC-M-KV-T-M32 - Cable gland

1646201

https://www.phoenixcontact.com/us/products/1646201





REDUC-M-KV-M32/M25 - Reducing adapter

1647637

https://www.phoenixcontact.com/us/products/1647637

Reducing adapter, connecting thread: M32 x 1.5, color: silver, with O-ring





Jun 6, 2024, 9:25 AM Page 11 (12)



1408999

https://www.phoenixcontact.com/us/products/1408999

ENLAR-M-KV-M32/M40 - Extension adapter

1647682

https://www.phoenixcontact.com/us/products/1647682

Extension adapter, connecting thread: M32 x 1.5, color: silver, with O-ring





HC-M-BS-M32 - Screw plug

1645862

https://www.phoenixcontact.com/us/products/1645862

Screw plug, material for screw connection: Brass, nickel-plated, connecting thread: M32 x 1.5, color: silver



Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com