


SAC-HZ-4P-2,0-542/FR SCO BK - Sensor/actuator cable

1409577
<https://www.phoenixcontact.com/us/products/1409577>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Commercial data

Item number	1409577
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	BF13
Product key	BF1IGB
GTIN	4055626018331
Weight per piece (including packing)	106.2 g
Weight per piece (excluding packing)	22.22 g
Customs tariff number	85444290
Country of origin	US

SAC-HZ-4P-2,0-542/FR SCO BK - Sensor/actuator cable



1409577

<https://www.phoenixcontact.com/us/products/1409577>

Technical data

Notes

General	These cable assemblies are UL/cUL listed for use in Class I, Division 2 (CID2) hazardous locations.
---------	---

Product properties

Product type	Sensor/actuator cable
Number of positions	4
Application	U.S. cables for hazardous locations
No. of cable outlets	1
Shielded	no
Coding	A

Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Material specifications

Flammability rating according to UL 94	HB
Seal material	NBR
Material of grip body	TPU, hardly inflammable, self-extinguishing
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Material for screw connection	Zinc die-cast, nickel-plated
Outer sheath, material	PVC

Electrical properties

Insulation resistance	$\geq 100 \text{ M}\Omega$
Nominal voltage U_N	250 V AC
	250 V DC
Nominal current I_N	4 A
Protective circuit	unwired

Signaling

Status display	No
Status display present	No

Connection data

Conductor connection	
Tightening torque	0.4 Nm (M12 connector)

Connector

SAC-HZ-4P-2,0-542/FR SCO BK - Sensor/actuator cable



1409577

<https://www.phoenixcontact.com/us/products/1409577>

Connection 1

Type	free cable end
------	----------------


Connection 2

Type	Socket angled M12 SPEEDCON
Number of positions	4
Locking type	SPEEDCON
Coding type	A

Cable/line

Cable length	2 m
--------------	-----

PVC yellow 105 °C [542]

Dimensional drawing	
Cable weight	36 kg/km
UL AWM Style	2517 (105 °C / 300 V)
Number of positions	4
Shielded	no
Cable type	PVC yellow 105 °C [542]
Conductor structure signal line	30x 1.30 mm
AWG signal line	22
Wire diameter incl. insulation	1.27 mm ±0.03 mm
External cable diameter	5.00 mm ±0.2 mm
Outer sheath, material	PVC
External sheath, color	yellow
Conductor material	Tin-plated Cu litz wires
Material wire insulation	PVC
Single wire, color	brown, blue, black, white
Overall twist	4 wires, twisted
Max. conductor resistance	max. 50.5 Ω/km (20 °C)
Insulation resistance	≥ (550 M Ohms/m @ 500V)
Nominal voltage, cable	300 V
Minimum bending radius, flexible installation	8 x D
Smallest bending radius, movable installation	40 mm
Flame resistance	FT4
Other resistance	UV resistant
Special properties	UL standards PLTC and ITC

SAC-HZ-4P-2,0-542/FR SCO BK - Sensor/actuator cable



1409577

<https://www.phoenixcontact.com/us/products/1409577>

Ambient temperature (operation)	-30 °C ... 105 °C (cable, fixed installation)
	-5 °C ... 105 °C (Cable, flexible installation)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65
	IP67
	IP68
Ambient temperature (operation)	-25 °C ... 90 °C (Plug / socket)

Approvals

Conformity/Approvals

UL, USA / Canada	Class I, Div. 2, Groups A, B, C, D
------------------	------------------------------------

Standards and regulations

Standard designation	M12 connector
Standards/specifications	IEC 61076-2-101

SAC-HZ-4P-2,0-542/FR SCO BK - Sensor/actuator cable




1409577

<https://www.phoenixcontact.com/us/products/1409577>

Drawings

Dimensional drawing




M12 x 1 socket, straight

SAC-HZ-4P-2,0-542/FR SCO BK - Sensor/actuator cable

1409577

<https://www.phoenixcontact.com/us/products/1409577>

Schematic diagram



Pin assignment M12 plug, 4-pos., A-coded, view plug side


SAC-HZ-4P-2,0-542/FR SCO BK - Sensor/actuator cable



1409577

<https://www.phoenixcontact.com/us/products/1409577>

Schematic diagram



Pin assignment M12 socket, 4-pos., A-coded, view female side


SAC-HZ-4P-2,0-542/FR SCO BK - Sensor/actuator cable



1409577


<https://www.phoenixcontact.com/us/products/1409577>

Dimensional drawing



EXCLIP mounted plug

Circuit diagram




SAC-HZ-4P-2,0-542/FR SCO BK - Sensor/actuator cable

1409577


<https://www.phoenixcontact.com/us/products/1409577>

Dimensional drawing



Plug, M12 x 1, straight, shielded

Dimensional drawing



EXCLIP socket

SAC-HZ-4P-2,0-542/FR SCO BK - Sensor/actuator cable



1409577
<https://www.phoenixcontact.com/us/products/1409577>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1409577>

**EAC-RoHS**
Approval ID: RU D-DE.HB35.B.00387

	cUL Listed Approval ID: FILE E 359524			
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	150 V	4 A	-	-

	UL Listed Approval ID: FILE E 359524			
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	150 V	4 A	-	-

cULus Listed

SAC-HZ-4P-2,0-542/FR SCO BK - Sensor/actuator cable



1409577
<https://www.phoenixcontact.com/us/products/1409577>

Classifications

ECLASS

ECLASS-11.0	27060311
ECLASS-12.0	27060311
ECLASS-13.0	27060311

ETIM

ETIM 9.0	EC001855
----------	----------

UNSPSC

UNSPSC 21.0	26121600
-------------	----------

SAC-HZ-4P-2,0-542/FR SCO BK - Sensor/actuator cable



1409577
<https://www.phoenixcontact.com/us/products/1409577>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com