



	Description	For Use With	Cat. No.
	Feeder Block for Compact Busbar • Supply of compact busbars Increases terminal capacity	140M-C	140M-C-WBE
		140M-F	140M-F-WBE
	Feeder Terminal for Compact Busbar • For supply of compact busbars • Top feed — overlaps compact busbar • Meets IEC spacing requirements	140M-C, -D	140M-C-WTN
	Feeder Terminal for Compact Busbar • For supply of compact busbars • Top feed — overlaps compact busbar • Meets UL Type E spacing requirements	140M-C, -D	140M-C-WTEN
		140M-F	140M-F-WTE
	Three-phase Compact Busbar for 32 A Motor Protection Circuit Breakers — 64 A Max. Continuous Current • 45 mm spacing • For use with front-mounted auxiliary contact	2 connections	140M-C-W452N
		3 connections	140M-C-W453N
		4 connections	140M-C-W454N
		5 connections	140M-C-W455N
	Three-phase Compact Busbar for 32 A Motor Protection Circuit Breakers — 64 A Max. Continuous Current • 54 mm spacing • For use with side-mounted auxiliary contact	2 connections	140M-C-W542N
		3 connections	140M-C-W543N
		4 connections	140M-C-W544N
		5 connections	140M-C-W545N
	Three-phase Compact Busbar for 45 A Motor Protection Circuit Breakers — 115 A Max. Continuous Current • 54 mm spacing • For use with front-mounted auxiliary contact	2 connections	140M-F-W542
		3 connections	140M-F-W543
		4 connections	140M-F-W544
	Three-phase Compact Busbar for 45 A Motor Protection Circuit Breakers — 115 A Max. Continuous Current • 63 mm spacing • For use with side-mounted auxiliary contact	2 connections	140M-F-W632
		3 connections	140M-F-W633
		4 connections	140M-F-W634
	Terminal Cover • For covering of unused compact bus bar terminals IP2X finger protection • Must be ordered in multiples of 10 • (10 pcs/pkg)	140M-C, -D	140M-C-WSN
		140M-F	140M-F-WS
	Top Hat Rail Adapter — 10 mm • Adjusts the depth of the 140M-C to the 140M-D • Allows the use of compact busbars across both frame sizes • Must be ordered in multiples of 10 • (10 pcs/pkg)	140M-C	140-KBH2
	DIN (#3) symmetrical hat rail • 35 x 7.5 x 1 m • (10 pcs/pkg)	140M-D, -F	199-DR1
	DIN (#3) Symmetrical Rail • 35 mm x 15 mm x 1 m long • Top Hat Rail (DIN #3 Symmetrical Rail) • (5 pcs/pkg)	140M-C, -D, -F	1492-DR9