


Table 37 - Shunt Trip Units

Description	Connection Diagram ⁽¹⁾	Trip Rating	For Use With	Cat. No.
 Shunt Trip - Left-side mounted - Adds 18 mm to the width of the device - Provides remote tripping of the MPCB/MCP - Maximum on time for DC operated devices: 5 sec.		24V, 50 Hz/24...28V, 60 Hz	140MT (all) 140UT-D	140MT-C-SNK
		110V, 50 Hz/120V, 60 Hz		140MT-C-SND
		220...230V, 50 Hz		140MT-C-SNF
		240...260V, 60 Hz		140MT-C-SNA
		277V, 60 Hz		140MT-C-SNT
		380...400V, 50 Hz		140MT-C-SNN
		480V, 60 Hz/415V, 50 Hz		140MT-C-SNB
		24V DC		140MT-C-SNZJ

(1) Connection Diagram Reference:





Table 38 - Additional Accessories

	Description		For Use With	Cat. No.
	Anti-Tamper Shield		140MT (all)	140MT-C-CA
	Lockable Twist Knob - For one padlock 4...6 mm (3/16 in.) diameter shackle - Can be locked in OFF position	Blue	140MT (all) 140UT-D	140MT-C-KB
		Black		140MT-C-KN
		Red/Yellow		140MT-C-KRY
	Locking Tag - Padlock attachment to the lockable handles - Up to three padlocks 4...8 mm (5/16 in.) diameter shackle		140MT-C-KB 140MT-C-KN 140MT-C-KRY	140MT-C-M3
	Door Coupling Handle - For 3 padlocks 4...8 mm (5/16 in.) in diameter - IPX4 Protection/Type 1, 3R Interlock override capability - Can be modified for locking in ON position - Ships with coupling — order extension shaft and legend plate separately	Black	140MT-C, -D 140UT-D	140MT-C-DN66
		Red/Yellow	140MT-C, -D 140UT-D	140MT-C-DRY66