





Table 40 - Other Accessories (Continued)

|                                                                                     | Description                                                                                                                                                                                                                                                                                                            |                   | For Use With                              | Cat. No.     |
|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|-------------------------------------------|--------------|
|    | Three-phase Compact Busbar for MPCBs — 64 A Max Continuous Current <ul style="list-style-type: none"> <li>• 45 mm (1.77 in.) spacing</li> <li>• For use with front-mounted auxiliary contact</li> </ul>                                                                                                                | 2 connections     | 140MT-C, -D                               | 140MT-C-W452 |
|                                                                                     |                                                                                                                                                                                                                                                                                                                        | 3 connections     |                                           | 140MT-C-W453 |
|                                                                                     |                                                                                                                                                                                                                                                                                                                        | 4 connections     |                                           | 140MT-C-W454 |
|                                                                                     |                                                                                                                                                                                                                                                                                                                        | 5 connections     |                                           | 140MT-C-W455 |
|    | Three-phase Compact Busbar for MPCBs — 64 A Max Continuous Current <ul style="list-style-type: none"> <li>• 54 mm (2.13 in.) spacing</li> <li>• For use with side-mounted auxiliary contact</li> </ul>                                                                                                                 | 2 connections     | 140MT-C, -D                               | 140MT-C-W542 |
|                                                                                     |                                                                                                                                                                                                                                                                                                                        | 3 connections     |                                           | 140MT-C-W543 |
|                                                                                     |                                                                                                                                                                                                                                                                                                                        | 4 connections     |                                           | 140MT-C-W544 |
|                                                                                     |                                                                                                                                                                                                                                                                                                                        | 5 connections     |                                           | 140MT-C-W545 |
|    | Three-phase Compact Busbar for 80 A MPCBs— 120 A Max. Continuous Current <ul style="list-style-type: none"> <li>• 55 mm (2.165 in.) spacing</li> <li>• For use with front-mounted auxiliary contact</li> </ul>                                                                                                         | 2 connections     | 140MT-F                                   | 140MT-F-W552 |
|                                                                                     |                                                                                                                                                                                                                                                                                                                        | 3 connections     |                                           | 140MT-F-W553 |
|    | Terminal Cover <ul style="list-style-type: none"> <li>• For covering of unused compact bus bar terminals IP2X finger protection</li> <li>• Must be ordered in multiples of 10</li> <li>• 10 pieces/pkg</li> </ul>                                                                                                      |                   | 140MT-C, -D                               | 140MT-C-WSN  |
|    |                                                                                                                                                                                                                                                                                                                        |                   | 140MT-F                                   | 140MT-F-WSN  |
|    | Top Hat Rail Adapter — 10 mm (0.39 in.) <ul style="list-style-type: none"> <li>• Adjusts the depth of the 140MT-C to the 140MT-D</li> <li>• Allows the use of compact busbars across both frame sizes</li> <li>• Must be ordered in multiples of 10</li> <li>• 10 pieces/pkg</li> </ul>                                |                   | 140MT-C                                   | 140MT-KBH    |
|   | DIN (#3) symmetrical hat rail <ul style="list-style-type: none"> <li>• 35 mm x 7.5 mm x 1 m (1.4 x 0.3 x 39 in.) long</li> <li>• 10 pieces/package</li> </ul>                                                                                                                                                          |                   | 140MT (all)<br>140UT-D                    | 199-DR1      |
|  | DIN (#3) Symmetrical Rail <ul style="list-style-type: none"> <li>• 35 mm x 15 mm x 1 m (1.4 x 0.6 x 39 in.) long</li> <li>• Top Hat Rail (DIN #3 Symmetrical Rail)</li> <li>• 5 pieces/package</li> </ul>                                                                                                              |                   | 140MT (all)<br>140UT-D                    | 1492-DR9     |
|  | Current Limiter <ul style="list-style-type: none"> <li>• Operational voltage <math>U_e</math>: 690V</li> <li>• Rated impulse-withstand voltage <math>U_{imp}</math>: 6 kV</li> <li>• Thermal current <math>I_{th}</math> <ul style="list-style-type: none"> <li>– IEC: 64 A</li> <li>– UL: 52 A</li> </ul> </li> </ul> |                   | 140MT-C, -D                               | 140MT-D-CL   |
|  | Plastic Enclosure <ul style="list-style-type: none"> <li>• IP66, Type 4X</li> <li>• Chemical-resistant plastic construction</li> </ul>                                                                                                                                                                                 | Red/yellow handle | 140MT-C up to:<br>13 A (IEC)<br>16 A (UL) | 140MT-C-ENRY |
|                                                                                     |                                                                                                                                                                                                                                                                                                                        | Black/grey handle | 140MT-C up to:<br>13 A (IEC)<br>16 A (UL) | 140MT-C-ENN  |