

SACC-DSI-M12FS-8CON-M16/1,0 - Device connector rear mounting



1410520
<https://www.phoenixcontact.com/pc/products/1410520>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Device connector rear mounting, Socket, straight, coding: A, on free cable end, Rear mounting, M16 x 1.5, Individual wires, 0.25 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1238850

Commercial data

Item number	1410520
Packing unit	1 pc
Minimum order quantity	5 pc
Product key	ABQCHB
GTIN	4046356900645
Weight per piece (including packing)	40.933 g
Weight per piece (excluding packing)	40.2 g
Customs tariff number	85444290
Country of origin	DE

SACC-DSI-M12FS-8CON-M16/1,0 - Device connector rear mounting



1410520

<https://www.phoenixcontact.com/pc/products/1410520>

Technical data

Notes

Order information:	Lock nut is included in the scope of delivery
General	Contact connection method: Crimp connection

Mounting

Mounting type	Rear mounting M16 x 1.5
---------------	-------------------------

Product properties

Product type	Circular connectors (device side)
No. of cable outlets	1
Coding	A
Thread type	M12

Connection data

Conductor connection

Connection method	Individual wires
Contact connection type	Socket
Conductor cross section	0.25 mm²

Connector

Connection 1

Head design	Socket
Head cable outlet	straight
Coding	A

Connection 2

Head design	free cable end
-------------	----------------

Cable/line

Cable cross section	0.25 mm²
AWG signal line	24

SACC-DSI-M12FS-8CON-M16/1,0 - Device connector rear mounting



1410520
<https://www.phoenixcontact.com/pc/products/1410520>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/1410520>

	UL Recognized			
	Approval ID: E118976-20100522			
	Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
	30 V	2 A	24 - 24	-

	cULus Recognized			
	Approval ID: E221474-20140616			
	Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
	30 V	2 A	24 - 22	-

SACC-DSI-M12FS-8CON-M16/1,0 - Device connector rear mounting



1410520

<https://www.phoenixcontact.com/pc/products/1410520>

Classifications

ECLASS

ECLASS-11.0	27440103
ECLASS-12.0	27440103
ECLASS-13.0	27440103

ETIM

ETIM 8.0	EC003570
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

SACC-DSI-M12FS-8CON-M16/1,0 - Device connector rear mounting



1410520
<https://www.phoenixcontact.com/pc/products/1410520>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	9a7f6a67-653b-4451-869c-84232fe6c2d0

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com