

REDUC-K-KV-M40/M25 BK - Reducing adapter



1410741

<https://www.phoenixcontact.com/in/products/1410741>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Reducing adapter, connecting thread: M40 x 1.5, color: jet black, with flat gasket

Product description

Reduced M40 to M25

Commercial data

Item number	1410741
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BF7
Product key	BF7DZX
Catalog page	Page 700 (C-2-2019)
GTIN	4046356873222
Weight per piece (including packing)	15.569 g
Weight per piece (excluding packing)	14.668 g
Customs tariff number	39269097
Country of origin	DE

REDUC-K-KV-M40/M25 BK - Reducing adapter



1410741

<https://www.phoenixcontact.com/in/products/1410741>

Technical data

Product properties

Product type	Reducing adapter
Seal present	yes
Manufacturer	Jacob
Manufacturer Designation	M40M25 PA/SW/FD

Data management status

Article revision	00
------------------	----

Connection data

Tightening torque	5 ... 7.5 Nm
-------------------	--------------

Dimensions

Dimensional drawing	
Width	50.50 mm
Length	16 mm
Length of the connecting thread	10 mm
Length without connecting thread	6 mm
Diameter	40 mm
Connecting thread diameter	40 mm
Wrench size, union nut	46 mm
Hexagon angular dimension	50.5 mm
Thread type connection side	M40 x 1.5
Thread pitch	1.5 mm
Thread type on seal side	M25

Material specifications

Color	black (RAL 9005)
Material	Polyamide fiberglass reinforced
Flammability rating according to UL 94	HB
Seal material	NBR

Cable/line

Halogen-free	no
--------------	----

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65 (Depends on the screw connection used)
----------------------	---

REDUC-K-KV-M40/M25 BK - Reducing adapter



1410741

<https://www.phoenixcontact.com/in/products/1410741>

Ambient temperature (operation)	-30 °C ... 100 °C
---------------------------------	-------------------

Mounting

Assembly note	With corresponding screw connection: IP65
---------------	---

REDUC-K-KV-M40/M25 BK - Reducing adapter




1410741


<https://www.phoenixcontact.com/in/products/1410741>

Drawings

Dimensional drawing



Dimensional drawing



REDUC-K-KV-M40/M25 BK - Reducing adapter



1410741

<https://www.phoenixcontact.com/in/products/1410741>

Classifications

ECLASS

ECLASS-11.0	27144492
ECLASS-12.0	27144492
ECLASS-13.0	27140806

ETIM

ETIM 9.0	EC000938
----------	----------

UNSPSC

UNSPSC 21.0	31261500
-------------	----------

REDUC-K-KV-M40/M25 BK - Reducing adapter



1410741

<https://www.phoenixcontact.com/in/products/1410741>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.
A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420
info@phoenixcontact.co.in