

HC-EVO-B10-HHFS-EL-AL - Housing



1411453

<https://www.phoenixcontact.com/pc/products/1411453>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



HEAVYCON EVO sleeve housing, EMC version, without powder coating, with bayonet flange for EVO screw connection, B10, for single locking latch, height: 80 mm, without EVO screw connection.

Your advantages

- Flexible cable outlet direction, lateral or straight

Commercial data

Item number	1411453
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	BF7APM
Catalog page	Page 605 (C-2-2019)
GTIN	4046356932608
Weight per piece (including packing)	187.6 g
Weight per piece (excluding packing)	183.6 g
Customs tariff number	85389099
Country of origin	DE

HC-EVO-B10-HHFS-EL-AL - Housing



1411453

<https://www.phoenixcontact.com/pc/products/1411453>

Technical data


Notes

General	For contact inserts HC-B10, BB18, DD42, M, K8/24
---------	--

Product properties

Product type	Housing with locking latch
Application	Standard
Type	B10
No. of cable outlets	1
Housing type	Sleeve housing
Cable outlet	straight
Pg screw connection	none

Dimensions

Dimensional drawing	
Width	44 mm
Height	80 mm
Length	73 mm

Material specifications

Housing material	Die-cast aluminum, salt water resistant
Housing surface material	uncoated
Impact strength	IK08

Mechanical properties

Mechanical data

Locking type	Pin
--------------	-----

Mounting

Assembly instructions	The sleeve base housing must be supplemented with the EVO screw connection. The EVO screw connection is available in 4 sizes. It enables the creation of a straight or a lateral cable outlet. The EVO screw connection is assembled by hand or using a pipe wrench.
-----------------------	--

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP66
	IP67

HC-EVO-B10-HHFS-EL-AL - Housing



1411453

<https://www.phoenixcontact.com/pc/products/1411453>

Enclosure rating (NEMA)	4 (UL 50e)
	4X (UL 50e)
	12 (UL 50e)
Impact strength	IK08
Ambient temperature (operation)	-40 °C ... 125 °C

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG

Flachsmarktstraße 8

D-32825 Blomberg

+49 (0) 5235-3 00

info@phoenixcontact.com