

1412228  
<https://www.phoenixcontact.com/pc/products/1412228>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Contact carrier, 4-position, Socket, straight, M8, coding: A, PCB mounting, SMD reflow, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1308257

Your advantages

- Reduced mounting costs thanks to two-piece device connector
- Packaging available for automated pick and place assembly
- All common pin assignments and codings available
- Easy device integration thanks to mechanical port screw connections with threaded attachment, press-in contour or direct integration in the front plate
- Optional shield connection and seal for the device when not plugged in

Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 1412228       |
| Packing unit                         | 60 pc         |
| Minimum order quantity               | 60 pc         |
| Product key                          | ABQHCS        |
| GTIN                                 | 4046356988216 |
| Weight per piece (including packing) | 2.876 g       |
| Weight per piece (excluding packing) | 2.745 g       |
| Customs tariff number                | 85366990      |
| Country of origin                    | DE            |

# SACC-CIP-M8FS-4P SMD T - Contact carrier



1412228

<https://www.phoenixcontact.com/pc/products/1412228>

## Technical data

### Notes

|                    |  |
|--------------------|--|
| Notes on operation | The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration. |
|--------------------|--|

### Product properties

|                     |                |
|---------------------|----------------|
| Product type        | Contact insert |
| Application         | Signal         |
| Number of positions | 4              |
| Seal present        | yes            |
| Shielded            | no             |
| Coding              | A              |
| Thread type         | M8             |

### Data management status

|                  |    |
|------------------|----|
| Article revision | 01 |
|------------------|----|

### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
|----------------------|-----|

### Electrical properties

|                       |                            |
|-----------------------|----------------------------|
| Contact resistance    | $\leq 3 \text{ m}\Omega$   |
| Insulation resistance | $\geq 100 \text{ M}\Omega$ |
| Nominal voltage $U_N$ | 48 V AC                    |
|                       | 60 V DC                    |
| Nominal current $I_N$ | 4 A                        |

### Connection data

|                   |            |
|-------------------|------------|
| Connection method | SMD reflow |
|-------------------|------------|

### Material specifications

|  |      |
|--|------|
| Flammability rating according to UL 94 | V0   |
| Seal material                          | FKM  |
| Contact material                       | CuZn |
| Contact surface material               | Au   |
| Contact carrier material               | PA   |

### Connector

#### Connection 1

|                   |          |
|-------------------|----------|
| Head design       | Socket   |
| Head cable outlet | straight |

# SACC-CIP-M8FS-4P SMD T - Contact carrier



1412228

<https://www.phoenixcontact.com/pc/products/1412228>

|                  |    |
|------------------|----|
| Head thread type | M8 |
| Coding           | A  |

## Mechanical properties

### Mechanical data

|                             |       |
|-----------------------------|-------|
| Insertion/withdrawal cycles | > 100 |
|-----------------------------|-------|

## Environmental and real-life conditions

### Ambient conditions

|  |  |
|--|--|
| Degree of protection (when plugged in) | IP67 (correctly plugged in and locked)           |
| Degree of protection                   | IP67   |
| Ambient temperature (operation)        | -25 °C ... 105 °C (Plug / socket)                |
|  | -40 °C ... 105 °C (without mechanical actuation) |

## Standards and regulations

### M8

|                          |                 |
|--------------------------|-----------------|
| Standard designation     | M8 connector    |
| Standards/specifications | IEC 61076-2-104 |

## Mounting

|               |              |
|---------------|--------------|
| Mounting type | PCB mounting |
|---------------|--------------|

## Packaging specifications

|                   |      |
|-------------------|------|
| Type of packaging | Tray |
|-------------------|------|

# SACC-CIP-M8FS-4P SMD T - Contact carrier


1412228

<https://www.phoenixcontact.com/pc/products/1412228>



## Drawings

Schematic diagram



Pin assignment M8 socket, 4-pos., view female side

# SACC-CIP-M8FS-4P SMD T - Contact carrier



1412228

<https://www.phoenixcontact.com/pc/products/1412228>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/1412228>

|  |                       |                       |                   |                             |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
| <div> <b>cULus Recognized</b><br/>Approval ID: E221474-20160506</div> |                       |                       |                   |                             |
|  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|  | 60 V                  | 4 A                   | -                 | -                           |

# SACC-CIP-M8FS-4P SMD T - Contact carrier



1412228

<https://www.phoenixcontact.com/pc/products/1412228>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27440102 |
| ECLASS-12.0 | 27440116 |
| ECLASS-13.0 | 27440116 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002635 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# SACC-CIP-M8FS-4P SMD T - Contact carrier



1412228

<https://www.phoenixcontact.com/pc/products/1412228>

## Environmental product compliance

### EU RoHS

|   |      |
|---|------|
| Fulfills EU RoHS substance requirements | Yes  |
| Exemption                               | 6(c) |

### China RoHS

|  |   |
|--|---|
| Environment friendly use period (EFUP) | EFUP-50   |
|  | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |

### EU REACH SVHC

|                                     |                                      |
|-------------------------------------|--------------------------------------|
| REACH candidate substance (CAS No.) | Lead(CAS: 7439-92-1)                 |
| SCIP                                | 46a92a47-cd3c-49ed-90e8-5ee6ba8f9f99 |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstraße 8  
D-32825 Blomberg  
+49 (0) 5235-3 00  
[info@phoenixcontact.com](mailto:info@phoenixcontact.com)