1412628

https://www.phoenixcontact.com/us/products/1412628

PHŒNIX CONTACT

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sleeve housing B10, for single locking latch, material: Die-cast aluminum, salt water resistant, cable outlets: 1, lateral, 1x Pg21, height: 57 mm, cable gland: none, Standard

Your advantages

· Good shielding in the event of electromagnetic interference

Commercial data

Item number	1412628
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF56
Product key	BF7APB
Catalog page	Page 606 (C-2-2019)
GTIN	4055626059549
Weight per piece (including packing)	153.5 g
Weight per piece (excluding packing)	150 g
Customs tariff number	85389099
Country of origin	PL

1412628

https://www.phoenixcontact.com/us/products/1412628

Technical data

Notes

General	for contact inserts HC-B10, BB18, DD42, M, K8/24, HV03
General	also available as a powder-coated or color version: 1372752 HC- STA-B10-HLFS-1STP21-EL/

Product properties

Product type	Housing with locking latch
Housing type	Sleeve housing
Application	Standard
Туре	B10
No. of cable outlets	1
Type of the screw connection	1x Pg21
Туре	Low design
Cable outlet	lateral
Pg screw connection	none

Dimensions

Dimensional drawing	
Width	44 mm
Height	57 mm
Length	73 mm

Material specifications

Housing material	Die-cast aluminum, salt water resistant
Housing surface material	uncoated

Mechanical properties

Type of the screw connection	1x Pg21
Locking type	Pin

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP66
	IP67
Enclosure rating (NEMA)	4 (UL 50e)
	4X (UL 50e)
	12 (UL 50e)



https://www.phoenixcontact.com/us/products/1412628


	PH	Œ	N	IX
Ĭ Ý				Ĩ


Impact strength	IK08
Ambient temperature (operation)	-40 °C 125 °C



https://www.phoenixcontact.com/us/products/1412628

Drawings





PHŒN

X

Dimensional drawing

1412628

https://www.phoenixcontact.com/us/products/1412628



Approvals

🌣 To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1412628

DN App	IV proval ID: TAE000037S
.?\\	CUL Recognized Approval ID: E255026
91	UL Recognized Approval ID: E255026
	EAC Approval ID: RU C-DE.AI30.B.01102
EAC	EAC Approval ID: RU C-DE.BL08.B.00511
cU	Lus Recognized

1412628

https://www.phoenixcontact.com/us/products/1412628



Classifications

ECLASS

ECLASS-11.0	27440202
ECLASS-12.0	27440202
ECLASS-13.0	27440202

ETIM

	ETIM 9.0	EC000437	
UNSPSC			
	UNSPSC 21.0	31261500	

1412628

https://www.phoenixcontact.com/us/products/1412628

PHŒNIX CONTACT

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions		
China RoHS			
Environment friendly use period (EFUP)	EFUP-E		
	No hazardous substances above the limits		
EU REACH SVHC			
REACH candidate substance (CAS No.)	No substance above 0.1 wt%		

1412628

https://www.phoenixcontact.com/us/products/1412628



Accessories

G-INS-PG21-M68N-NNES-S - Cable gland

1411175 https://www.phoenixcontact.com/us/products/1411175



Cable gland, material for screw connection: Brass, nickel-plated, application: Standard, external cable diameter 13 mm ... 18 mm, shielding: no, connecting thread: Pg21, color: silver, with O-ring

G-INSEC-PG21-M68N-NNES-S - Cable gland

1411200

https://www.phoenixcontact.com/us/products/1411200



Cable gland, material for screw connection: Brass, nickel-plated, application: EMC, external cable diameter 13 mm ... 18 mm, shielding: yes, connecting thread: Pg21, color: silver, with O-ring

1412628

https://www.phoenixcontact.com/us/products/1412628



US-EMLP (20X9) CUS - Plastic label

0830085

https://www.phoenixcontact.com/us/products/0830085

Plastic label, can be ordered: by card, white, labeled according to customer specifications, mounting type: adhesive, lettering field size: 20 x 9 mm, Number of individual labels: 75



HC-B10-HCWS-PLR-BK - Protective cover

1346528 https://www.phoenixcontact.com/us/products/1346528



Protective cover B10, with single locking latch, protective cover material: PC, height: 26.3 mm, seal: yes

1412628

https://www.phoenixcontact.com/us/products/1412628



US-EMLP-HA (20X9) - Plastic label

0830989

https://www.phoenixcontact.com/us/products/0830989



Plastic label, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: adhesive, lettering field size: 20 x 9 mm, Number of individual labels: 70

WP-G HF IP66 PG21 BK - Screw connection

3240892 https://www.phoenixcontact.com/us/products/3240892



Cable gland, Pg thread, IP66 protection, straight

1412628

https://www.phoenixcontact.com/us/products/1412628

WP-G HF IP69K PG21 BK - Screw connection

3240878

https://www.phoenixcontact.com/us/products/3240878

Cable gland, Pg thread, IP68/69k protection, straight



WP-GA HF IP66 PG21 BK - Screw connection

3240920 https://www.phoenixcontact.com/us/products/3240920

Cable gland, Pg thread, IP66 protection, angled



PHŒNIX CONTACT

1412628

https://www.phoenixcontact.com/us/products/1412628

PHŒNIX CONTACT

WP-GR HF IP66 PG21 BK - Screw connection

3240948

https://www.phoenixcontact.com/us/products/3240948



Cable gland, Pg thread, IP66 protection, with strain relief

WP-GR HF IP69K PG21 BK - Screw connection

3240934 https://www.phoenixcontact.com/us/products/3240934



Cable gland, Pg thread, IP68/69k protection, with strain relief

1412628

https://www.phoenixcontact.com/us/products/1412628

WP-G PP HF PG21 - Screw connection

3240992

https://www.phoenixcontact.com/us/products/3240992

Cable gland made from PP with Pg thread, IP65 protection



WP-GT PP HF PG21 - Screw connection

3241006 https://www.phoenixcontact.com/us/products/3241006



Cable gland made from PP with Pg thread, rotatable, IP54 protection

PHŒN

1412628

https://www.phoenixcontact.com/us/products/1412628

PHŒNIX CONTACT

WP-G BRASS IP40 PG21 - Screw connection

3241041

https://www.phoenixcontact.com/us/products/3241041

Cable gland made from brass with Pg thread, IP40 protection



WP-GT BRASS PG21 - Screw connection

3241027 https://www.phoenixcontact.com/us/products/3241027



Cable gland made from brass with Pg thread, rotatable, IP40 protection

1412628

https://www.phoenixcontact.com/us/products/1412628

PHŒNIX CONTACT

WP-G BRASS IP65 PG21 - Screw connection

3241055

https://www.phoenixcontact.com/us/products/3241055

Cable gland made from brass with Pg thread, IP65 protection



Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com