## HC-STA-B16-HLFS-1TTM32-EL-AL - Housing



1412730

https://www.phoenixcontact.com/us/products/1412730

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sleeve housing B16, for single locking latch, material: Die-cast aluminum, salt water resistant, cable outlets: 1, straight, 1x M32, height: 60 mm, cable gland: none, Standard

## Your advantages

• Good shielding in the event of electromagnetic interference

#### Commercial data

Item number	1412730
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF56
Product key	BF7APB
Catalog page	Page 620 (C-2-2019)
GTIN	4055626060040
Weight per piece (including packing)	198 g
Weight per piece (excluding packing)	191.7 g
Customs tariff number	85389099
Country of origin	PL

# HC-STA-B16-HLFS-1TTM32-EL-AL - Housing



1412730

https://www.phoenixcontact.com/us/products/1412730

## Technical data

#### Notes

General	For contact inserts HC-B16, BB32, D40, DD72, HS6, HV6, M, K
General	also available as a powder-coated or color version: 1373046 HC-STA-B16-HLFS-1TTM32-EL/

### Product properties

Product type	Housing with locking latch
Housing type	Sleeve housing
Application	Standard
Туре	B16
No. of cable outlets	1
Type of the screw connection	1x M32
Cable outlet	straight
Pg screw connection	none

#### **Dimensions**

Dimensional drawing	3 93,5
Width	44 mm
Height	60 mm
Length	93.5 mm

### Material specifications

Housing material	Die-cast aluminum, salt water resistant
Housing surface material	uncoated
Impact strength	IK08

### Mechanical properties

#### Mechanical data

Type of the screw connection	1x M32
Locking type	Pin

## Environmental and real-life conditions

#### Ambient conditions

Ambient Conditions	
Degree of protection	IP66
	IP67
Enclosure rating (NEMA)	4 (UL 50e)
	4X (UL 50e)

## HC-STA-B16-HLFS-1TTM32-EL-AL - Housing



1412730

https://www.phoenixcontact.com/us/products/1412730

	12 (UL 50e)
Impact strength	IK08
Ambient temperature (operation)	-40 °C 125 °C

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com