

HC-STA-B24-HLWD-1STM25-EL-AL - Housing



1412793

<https://www.phoenixcontact.com/gb/products/1412793>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sleeve housing B24, with double locking latch, material: Die-cast aluminum, salt water resistant, cable outlets: 1, lateral, 1x M25, height: 60 mm, cable gland: none, Standard

Your advantages

- Good shielding in the event of electromagnetic interference

Commercial data

Item number	1412793
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF7APB
Product key	BF7APB
Catalog page	Page 642 (C-2-2019)
GTIN	4055626060590
Weight per piece (including packing)	267.7 g
Weight per piece (excluding packing)	267.7 g
Customs tariff number	85389099
Country of origin	PL

HC-STA-B24-HLWD-1STM25-EL-AL - Housing



1412793

<https://www.phoenixcontact.com/gb/products/1412793>

Technical data


Notes

General	for contact inserts HC-B24, BB46, D64, DD108, HV10/16, M
General	also available as a powder-coated or color version: 1373271 HC-STA-B24-HLWD-1STM25-EL/...

Product properties

Product type	Housing with locking latch
Housing type	Sleeve housing
Application	Standard
Type	B24
No. of cable outlets	1
Type of the screw connection	1x M25
Cable outlet	lateral
Pg screw connection	none

Dimensions

Dimensional drawing	
Width	44 mm
Height	60 mm
Length	120 mm

Material specifications

Flammability rating according to UL 94	V0 (Interlock)
Housing material	Die-cast aluminum, salt water resistant
Housing surface material	uncoated
Locking latch material	PA

Mechanical properties

Mechanical data

Type of the screw connection	1x M25
Locking type	Latch

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP66
	IP67
	4 (UL 50e)

HC-STA-B24-HLWD-1STM25-EL-AL - Housing



1412793

<https://www.phoenixcontact.com/gb/products/1412793>

Enclosure rating (NEMA)	4X (UL 50e)
	12 (UL 50e)
Impact strength	IK09
Ambient temperature (operation)	-40 °C ... 125 °C

HC-STA-B24-HLWD-1STM25-EL-AL - Housing


1412793

<https://www.phoenixcontact.com/gb/products/1412793>



Drawings

Dimensional drawing



Dimensional drawing

HC-STA-B24-HLWD-1STM25-EL-AL - Housing



1412793

<https://www.phoenixcontact.com/gb/products/1412793>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/gb/products/1412793>

**DNV**
Approval ID: TAE000037S

**cUL Recognized**
Approval ID: E255026

**UL Recognized**
Approval ID: E255026

**EAC**
Approval ID: RU C-DE.AI30.B.01102

**EAC**
Approval ID: RU C-DE.BL08.B.00511

cULus Recognized

HC-STA-B24-HLWD-1STM25-EL-AL - Housing



1412793

<https://www.phoenixcontact.com/gb/products/1412793>

Classifications

ECLASS

ECLASS-11.0	27440202
ECLASS-12.0	27440202
ECLASS-13.0	27440202

ETIM

ETIM 9.0	EC000437
----------	----------

UNSPSC

UNSPSC 21.0	31261500
-------------	----------

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

HC-STA-B24-HLWD-1STM25-EL-AL - Housing



1412793

<https://www.phoenixcontact.com/gb/products/1412793>

Accessories

G-INS-M25-M68N-NNES-S - Cable gland

1411165

<https://www.phoenixcontact.com/gb/products/1411165>



Cable gland, material for screw connection: Brass, nickel-plated, application: Standard, external cable diameter 11 mm ... 17 mm, shielding: no, connecting thread: M25 x 1.5, color: silver, with O-ring

G-INSEC-M25-S68N-NCRS-S - Cable gland

1411190

<https://www.phoenixcontact.com/gb/products/1411190>



Cable gland, material for screw connection: Brass, nickel-plated, application: EMC, external cable diameter 11 mm ... 16 mm, shielding: yes, connecting thread: M25 x 1.5, color: silver, with O-ring

HC-STA-B24-HLWD-1STM25-EL-AL - Housing



1412793

<https://www.phoenixcontact.com/gb/products/1412793>

US-EMLP (20X9) CUS - Plastic label

0830085

<https://www.phoenixcontact.com/gb/products/0830085>

Plastic label, can be ordered: by card, white, labeled according to customer specifications, mounting type: adhesive, lettering field size: 20 x 9 mm, Number of individual labels: 75



HC-STA-B10-24-DL-PLBK - Housing brackets

1412886

<https://www.phoenixcontact.com/gb/products/1412886>

Double locking latch for B10 / B16 / B24 housing, HC-EVO....AL and HC-STA....AL



HC-STA-B24-HLWD-1STM25-EL-AL - Housing

1412793

<https://www.phoenixcontact.com/gb/products/1412793>



HC-B24-HCFD-PR-BK - Protective cover

1346551

<https://www.phoenixcontact.com/gb/products/1346551>

Protective cover B24, for double locking latch, protective cover material: PC, height: 26.3 mm, seal: yes



US-EMLP-HA (20X9) - Plastic label

0830989

<https://www.phoenixcontact.com/gb/products/0830989>

Plastic label, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: adhesive, lettering field size: 20 x 9 mm, Number of individual labels: 70



HC-STA-B24-HLWD-1STM25-EL-AL - Housing

1412793

<https://www.phoenixcontact.com/gb/products/1412793>



WP-G HF IP66 M25 BK - Screw connection

3240899

<https://www.phoenixcontact.com/gb/products/3240899>

Cable gland, metric thread, IP66 protection, straight



WP-G HF IP69K M25 BK - Screw connection

3240885

<https://www.phoenixcontact.com/gb/products/3240885>

Cable gland, metric thread, IP68/69k protection, straight



HC-STA-B24-HLWD-1STM25-EL-AL - Housing

1412793

<https://www.phoenixcontact.com/gb/products/1412793>



WP-GA HF IP66 M25 BK - Screw connection

3240927

<https://www.phoenixcontact.com/gb/products/3240927>

Cable gland, metric thread, IP66 protection, angled



WP-GA HF IP69K M25 BK - Screw connection

3240913

<https://www.phoenixcontact.com/gb/products/3240913>

Cable gland, metric thread, IP68/69k protection, angled



HC-STA-B24-HLWD-1STM25-EL-AL - Housing

1412793

<https://www.phoenixcontact.com/gb/products/1412793>



WP-GR HF IP66 M25 BK - Screw connection

3240955

<https://www.phoenixcontact.com/gb/products/3240955>



Cable gland, metric thread, IP66 protection, with strain relief

WP-GR HF IP69K M25 BK - Screw connection

3240941

<https://www.phoenixcontact.com/gb/products/3240941>



Cable gland, metric thread, IP68/69k protection, with strain relief

HC-STA-B24-HLWD-1STM25-EL-AL - Housing



1412793

<https://www.phoenixcontact.com/gb/products/1412793>

WP-G PP HF M25 - Screw connection

3240999

<https://www.phoenixcontact.com/gb/products/3240999>

Cable gland made from PP with metric thread, IP65 protection



WP-GT PP HF M25 - Screw connection

3241013

<https://www.phoenixcontact.com/gb/products/3241013>

Cable gland made from PP with metric thread, rotatable, IP54 protection



HC-STA-B24-HLWD-1STM25-EL-AL - Housing



1412793

<https://www.phoenixcontact.com/gb/products/1412793>

WP-G BRASS IP40 M25 - Screw connection

3241048

<https://www.phoenixcontact.com/gb/products/3241048>

Cable gland made from brass with metric thread, IP40 protection



WP-GT BRASS M25 - Screw connection

3241034

<https://www.phoenixcontact.com/gb/products/3241034>

Cable gland made from brass with metric thread, rotatable, IP40 protection



HC-STA-B24-HLWD-1STM25-EL-AL - Housing

1412793

<https://www.phoenixcontact.com/gb/products/1412793>



WP-G BRASS IP65 M25 - Screw connection

3241062

<https://www.phoenixcontact.com/gb/products/3241062>

Cable gland made from brass with metric thread, IP65 protection



Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd

Halesfield 13, Telford

Shropshire, TF7 4PG

01952 681700

info@phoenixcontact.co.uk