

HC-STA-B10-SLFDC-2SSM25-ELC-AL - Housing



1412831

<https://www.phoenixcontact.com/gb/products/1412831>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Box mounting bases B10, for double locking latch, material: Die-cast aluminum, salt water resistant, protective cover material: PC, cable outlets: 2, lateral, 2x M25, height: 54 mm, cable gland: none, protective cover: yes, Standard

Your advantages

- Good shielding in the event of electromagnetic interference

Commercial data

Item number	1412831
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF7APB
Product key	BF7APB
Catalog page	Page 613 (C-2-2019)
GTIN	4055626060903
Weight per piece (including packing)	207.1 g
Weight per piece (excluding packing)	206 g
Customs tariff number	85389099
Country of origin	PL

HC-STA-B10-SLFDC-2SSM25-ELC-AL - Housing



1412831

<https://www.phoenixcontact.com/gb/products/1412831>

Technical data


Notes

General	For contact inserts HC-B10, BB18, DD42, M, K8/24
General	also available as a powder-coated or color version: 1372796 HC-STA-B10-SLFDC-2SSM25-EL/.../...

Product properties

Product type	Housing with locking latch
Housing type	Box mounting bases
Application	Standard
Type	B10
No. of cable outlets	2
Type of the screw connection	2x M25
Protective cover	yes
Cable outlet	lateral
Pg screw connection	none

Dimensions

Dimensional drawing	
Width	52 mm
Height	54 mm
Length	92 mm
Hole diameter	5.5 mm

Material specifications

Flammability rating according to UL 94	V0 (Protective cover)
Seal material	NBR, conductive
Housing material	Die-cast aluminum, salt water resistant
Housing surface material	uncoated
Material, protective cover	PC

Mechanical properties

Mechanical data

Type of the screw connection	2x M25
Locking type	Pin

Mounting

Assembly note	One opening is sealed with a plastic filler plug and can be opened using a screwdriver.
---------------	---


Environmental and real-life conditions

Ambient conditions

Degree of protection	IP66 (when plugged in)
	IP67 (when plugged in)
	IP54 (with closed protective cover)
Impact strength	IK09
Ambient temperature (operation)	-40 °C ... 125 °C

Drawings

Dimensional drawing




Dimensional drawing


1412831


<https://www.phoenixcontact.com/gb/products/1412831>


Approvals


To download certificates, visit the product detail page: <https://www.phoenixcontact.com/gb/products/1412831>

**DNV**
Approval ID: TAE000037S

**EAC**
Approval ID: RU C-DE.AI30.B.01102

**EAC**
Approval ID: RU C-DE.BL08.B.00511

**cUL Recognized**
Approval ID: E255026

**UL Recognized**
Approval ID: E255026

cULus Recognized

Classifications

ECLASS

ECLASS-11.0	27440202
ECLASS-12.0	27440202
ECLASS-13.0	27440202

ETIM

ETIM 9.0	EC000437
----------	----------

UNSPSC

UNSPSC 21.0	31261500
-------------	----------

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

1412831

<https://www.phoenixcontact.com/gb/products/1412831>

Accessories

G-INS-M25-M68N-NNES-S - Cable gland

1411165

<https://www.phoenixcontact.com/gb/products/1411165>



Cable gland, material for screw connection: Brass, nickel-plated, application: Standard, external cable diameter 11 mm ... 17 mm, shielding: no, connecting thread: M25 x 1.5, color: silver, with O-ring

G-INSEC-M25-S68N-NCRS-S - Cable gland

1411190

<https://www.phoenixcontact.com/gb/products/1411190>



Cable gland, material for screw connection: Brass, nickel-plated, application: EMC, external cable diameter 11 mm ... 16 mm, shielding: yes, connecting thread: M25 x 1.5, color: silver, with O-ring

HC-STA-B10-SLFDC-2SSM25-ELC-AL - Housing



1412831

<https://www.phoenixcontact.com/gb/products/1412831>

HC-B10-SP-CBK - Profile gasket

1411479

<https://www.phoenixcontact.com/gb/products/1411479>



Profile gasket for HEAVYCON EVO supporting base element type B10, conductive

HC-B10-BC-HI-PLBK - Protective cover

1407693

<https://www.phoenixcontact.com/gb/products/1407693>



Protective cover B10, for single locking latch, protective cover material: PC, height: 19.1 mm, seal: no

HC-STA-B10-SLFDC-2SSM25-ELC-AL - Housing

1412831

<https://www.phoenixcontact.com/gb/products/1412831>



HC-STA-B10-DC-PL - Protective cover

1421101

<https://www.phoenixcontact.com/gb/products/1421101>



Protective cover, design: B10

WP-G HF IP66 M25 BK - Screw connection

3240899

<https://www.phoenixcontact.com/gb/products/3240899>



Cable gland, metric thread, IP66 protection, straight

HC-STA-B10-SLFDC-2SSM25-ELC-AL - Housing

1412831

<https://www.phoenixcontact.com/gb/products/1412831>



WP-G HF IP69K M25 BK - Screw connection

3240885

<https://www.phoenixcontact.com/gb/products/3240885>

Cable gland, metric thread, IP68/69k protection, straight



WP-GA HF IP66 M25 BK - Screw connection

3240927

<https://www.phoenixcontact.com/gb/products/3240927>

Cable gland, metric thread, IP66 protection, angled



HC-STA-B10-SLFDC-2SSM25-ELC-AL - Housing

1412831

<https://www.phoenixcontact.com/gb/products/1412831>



WP-GA HF IP69K M25 BK - Screw connection

3240913

<https://www.phoenixcontact.com/gb/products/3240913>

Cable gland, metric thread, IP68/69k protection, angled



WP-GR HF IP66 M25 BK - Screw connection

3240955

<https://www.phoenixcontact.com/gb/products/3240955>

Cable gland, metric thread, IP66 protection, with strain relief



HC-STA-B10-SLFDC-2SSM25-ELC-AL - Housing

1412831

<https://www.phoenixcontact.com/gb/products/1412831>



WP-GR HF IP69K M25 BK - Screw connection

3240941

<https://www.phoenixcontact.com/gb/products/3240941>



Cable gland, metric thread, IP68/69k protection, with strain relief

WP-G PP HF M25 - Screw connection

3240999

<https://www.phoenixcontact.com/gb/products/3240999>



Cable gland made from PP with metric thread, IP65 protection

HC-STA-B10-SLFDC-2SSM25-ELC-AL - Housing



1412831

<https://www.phoenixcontact.com/gb/products/1412831>

WP-GT PP HF M25 - Screw connection

3241013

<https://www.phoenixcontact.com/gb/products/3241013>



Cable gland made from PP with metric thread, rotatable, IP54 protection

WP-G BRASS IP40 M25 - Screw connection

3241048

<https://www.phoenixcontact.com/gb/products/3241048>



Cable gland made from brass with metric thread, IP40 protection

HC-STA-B10-SLFDC-2SSM25-ELC-AL - Housing



1412831

<https://www.phoenixcontact.com/gb/products/1412831>

WP-GT BRASS M25 - Screw connection

3241034

<https://www.phoenixcontact.com/gb/products/3241034>

Cable gland made from brass with metric thread, rotatable, IP40 protection



WP-G BRASS IP65 M25 - Screw connection

3241062

<https://www.phoenixcontact.com/gb/products/3241062>

Cable gland made from brass with metric thread, IP65 protection



Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk