

HC-STA-B10-SLWS-2SSP16-ELC-AL - Housing



1412842

<https://www.phoenixcontact.com/gb/products/1412842>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Box mounting bases B10, with single locking latch, material: Die-cast aluminum, salt water resistant, cable outlets: 2, lateral, 2x Pg16, height: 54.6 mm, cable gland: none, Standard

Your advantages

- Good shielding in the event of electromagnetic interference

Commercial data

Item number	1412842
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF7APB
Product key	BF7APB
Catalog page	Page 605 (C-2-2019)
GTIN	4055626060996
Weight per piece (including packing)	203.2 g
Weight per piece (excluding packing)	196.29 g
Customs tariff number	85389099
Country of origin	PL

Technical data


Notes

General	For contact inserts HC-B10, BB18, DD42, M, K8/24
General	also available as a powder-coated or color version: 1372789 HC-STA-B10-SLWS-2SSP16-EL/.../...

Product properties

Product type	Housing with locking latch
Housing type	Box mounting bases
Application	Standard
Type	B10
No. of cable outlets	2
Type of the screw connection	2x Pg16
Cable outlet	lateral
Pg screw connection	none

Dimensions

Dimensional drawing	
Width	52 mm
Height	54.6 mm
Length	92 mm
Hole diameter	5.5 mm

Material specifications

Flammability rating according to UL 94	V0 (Interlock)
Seal material	NBR, conductive
Housing material	Die-cast aluminum, salt water resistant
Housing surface material	uncoated
Locking latch material	PA

Mechanical properties

Mechanical data

Type of the screw connection	2x Pg16
Locking type	Latch

Mounting

Assembly note	One opening is sealed with a plastic filler plug and can be opened using a screwdriver.
---------------	---

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP66
	IP67
Enclosure rating (NEMA)	4 (UL 50e)
	4X (UL 50e)
	12 (UL 50e)
Impact strength	IK08
Ambient temperature (operation)	-40 °C ... 125 °C

HC-STA-B10-SLWS-2SSP16-ELC-AL - Housing




1412842

<https://www.phoenixcontact.com/gb/products/1412842>

Drawings

Dimensional drawing



Dimensional drawing

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/gb/products/1412842>

**DNV**
Approval ID: TAE000037S

**cUL Recognized**
Approval ID: E255026

**UL Recognized**
Approval ID: E255026

**EAC**
Approval ID: RU C-DE.AI30.B.01102

**EAC**
Approval ID: RU C-DE.BL08.B.00511

cULus Recognized

1412842

<https://www.phoenixcontact.com/gb/products/1412842>

Classifications

ECLASS

ECLASS-11.0	27440202
ECLASS-12.0	27440202
ECLASS-13.0	27440202

ETIM

ETIM 9.0	EC000437
----------	----------

UNSPSC

UNSPSC 21.0	31261500
-------------	----------

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

1412842

<https://www.phoenixcontact.com/gb/products/1412842>

Accessories

G-INS-PG16-S68N-NNES-S - Cable gland

1411174

<https://www.phoenixcontact.com/gb/products/1411174>



Cable gland, material for screw connection: Brass, nickel-plated, application: Standard, external cable diameter 10 mm ... 14 mm, shielding: no, connecting thread: Pg16, color: silver, with O-ring

G-INSEC-PG16-S68N-NNES-S - Cable gland

1411199

<https://www.phoenixcontact.com/gb/products/1411199>



Cable gland, material for screw connection: Brass, nickel-plated, application: EMC, external cable diameter 10 mm ... 14 mm, shielding: yes, connecting thread: Pg16, color: silver, with O-ring

HC-STA-B10-SLWS-2SSP16-ELC-AL - Housing



1412842

<https://www.phoenixcontact.com/gb/products/1412842>

HC-B10-SP-CBK - Profile gasket

1411479

<https://www.phoenixcontact.com/gb/products/1411479>

Profile gasket for HEAVYCON EVO supporting base element type B10, conductive



HC-STA-B10-SL-PLBK - Housing brackets

1412804

<https://www.phoenixcontact.com/gb/products/1412804>

Single locking latch for B10 housing, HC-EVO....AL and HC-STA....AL



HC-STA-B10-SLWS-2SSP16-ELC-AL - Housing

1412842

<https://www.phoenixcontact.com/gb/products/1412842>



HC-B10-BC-HI-PLBK - Protective cover

1407693

<https://www.phoenixcontact.com/gb/products/1407693>

Protective cover B10, for single locking latch, protective cover material: PC, height: 19.1 mm, seal: no



HC-B10-BCFS-P-BK - Protective cover

1346526

<https://www.phoenixcontact.com/gb/products/1346526>

Protective cover B10, for single locking latch, protective cover material: PC, height: 26.3 mm, seal: no



HC-STA-B10-SLWS-2SSP16-ELC-AL - Housing

1412842

<https://www.phoenixcontact.com/gb/products/1412842>



HC-STA-B10-DC-PL - Protective cover

1421101

<https://www.phoenixcontact.com/gb/products/1421101>



Protective cover, design: B10

WP-G HF IP66 PG16 BK - Screw connection

3240891

<https://www.phoenixcontact.com/gb/products/3240891>



Cable gland, Pg thread, IP66 protection, straight

HC-STA-B10-SLWS-2SSP16-ELC-AL - Housing

1412842

<https://www.phoenixcontact.com/gb/products/1412842>



WP-G HF IP69K PG16 BK - Screw connection

3240877

<https://www.phoenixcontact.com/gb/products/3240877>

Cable gland, Pg thread, IP68/69k protection, straight



WP-GA HF IP66 PG16 BK - Screw connection

3240919

<https://www.phoenixcontact.com/gb/products/3240919>

Cable gland, Pg thread, IP66 protection, angled



HC-STA-B10-SLWS-2SSP16-ELC-AL - Housing

1412842

<https://www.phoenixcontact.com/gb/products/1412842>



WP-GA HF IP69K PG16 BK - Screw connection

3240905

<https://www.phoenixcontact.com/gb/products/3240905>

Cable gland, Pg thread, IP68/69k protection, angled



WP-GR HF IP66 PG16 BK - Screw connection

3240947

<https://www.phoenixcontact.com/gb/products/3240947>

Cable gland, Pg thread, IP66 protection, with strain relief



HC-STA-B10-SLWS-2SSP16-ELC-AL - Housing



1412842

<https://www.phoenixcontact.com/gb/products/1412842>

WP-GR HF IP69K PG16 BK - Screw connection

3240933

<https://www.phoenixcontact.com/gb/products/3240933>



Cable gland, Pg thread, IP68/69k protection, with strain relief

WP-G PP HF PG16 - Screw connection

3240991

<https://www.phoenixcontact.com/gb/products/3240991>



Cable gland made from PP with Pg thread, IP65 protection

HC-STA-B10-SLWS-2SSP16-ELC-AL - Housing



1412842

<https://www.phoenixcontact.com/gb/products/1412842>

WP-GT PP HF PG16 - Screw connection

3241005

<https://www.phoenixcontact.com/gb/products/3241005>



Cable gland made from PP with Pg thread, rotatable, IP54 protection

WP-G BRASS IP40 PG16 - Screw connection

3241040

<https://www.phoenixcontact.com/gb/products/3241040>



Cable gland made from brass with Pg thread, IP40 protection

HC-STA-B10-SLWS-2SSP16-ELC-AL - Housing



1412842

<https://www.phoenixcontact.com/gb/products/1412842>

WP-GT BRASS PG16 - Screw connection

3241026

<https://www.phoenixcontact.com/gb/products/3241026>

Cable gland made from brass with Pg thread, rotatable, IP40 protection



WP-G BRASS IP65 PG16 - Screw connection

3241054

<https://www.phoenixcontact.com/gb/products/3241054>

Cable gland made from brass with Pg thread, IP65 protection



Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk