

HC-STA-B16-SLFDC-2SSM32-ELC-AL - Housing



1412850

<https://www.phoenixcontact.com/us/products/1412850>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Box mounting bases B16, for double locking latch, material: Die-cast aluminum, salt water resistant, protective cover material: PC, cable outlets: 2, lateral, 2x M32, height: 68 mm, cable gland: none, protective cover: yes, Standard

Your advantages

- Good shielding in the event of electromagnetic interference

Commercial data

Item number	1412850
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF56
Product key	BF7APB
Catalog page	Page 627 (C-2-2019)
GTIN	4055626060729
Weight per piece (including packing)	311.1 g
Weight per piece (excluding packing)	305.3 g
Customs tariff number	85389099
Country of origin	CN

General	For contact inserts HC-B16, BB32, D40, DD72, HS6, HV6, M, K
General	also available as a powder-coated or color version: 1372785 HC-STA-B16-SLFDC-2SSM32-EL/.../...

Product type	Housing with locking latch
Housing type	Box mounting bases
Application	Standard
Type	B16
No. of cable outlets	2
Type of the screw connection	2x M32
Type	Low design
Protective cover	yes
Cable outlet	lateral
Pg screw connection	none

Dimensional drawing	
	<p>The technical drawing consists of two orthographic projections. The left projection is a front view showing the main body of the sensor with a central cable entry point. It includes dimension lines indicating a total length of 117.5 mm, a mounting hole diameter of Ø5.5 mm, and a base width of 57 mm. The right projection is a side view showing the profile of the device, highlighting a base width of 57 mm and a depth of 45 mm.</p>
Width	57 mm
Height	68 mm
Length	117.5 mm
Hole diameter	5.5 mm

Flammability rating according to UL 94	V0 (Protective cover)
Seal material	NBR, conductive
Housing material	Die-cast aluminum, salt water resistant
Housing surface material	uncoated
Material, protective cover	PC

Type of the screw connection	2x M32
Locking type	Pin

HC-STA-B16-SLFDC-2SSM32-ELC-AL - Housing



1412850

<https://www.phoenixcontact.com/us/products/1412850>

Tightening torque	2 Nm ... 3 Nm (for M5 mounting screws on the surface-mount housing)
-------------------	---

Mounting

Assembly note	One opening is sealed with a plastic filler plug and can be opened using a screwdriver.
---------------	---

Environmental and real-life conditions

Ambient conditions	
Degree of protection	IP66 (when plugged in)
	IP67 (when plugged in)
	IP54 (with closed protective cover)
Impact strength	IK09
Ambient temperature (operation)	-40 °C ... 125 °C

HC-STA-B16-SLFDC-2SSM32-ELC-AL - Housing


1412850

<https://www.phoenixcontact.com/us/products/1412850>



Drawings

Dimensional drawing



Dimensional drawing


1412850


<https://www.phoenixcontact.com/us/products/1412850>


Approvals


To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1412850>

**DNV**
Approval ID: TAE000037S

**EAC**
Approval ID: RU C-DE.AI30.B.01102

**EAC**
Approval ID: RU C-DE.BL08.B.00511

**cUL Recognized**
Approval ID: E255026

**UL Recognized**
Approval ID: E255026

cULus Recognized

HC-STA-B16-SLFDC-2SSM32-ELC-AL - Housing



1412850

<https://www.phoenixcontact.com/us/products/1412850>

Classifications

ECLASS

ECLASS-11.0	27440202
ECLASS-12.0	27440202
ECLASS-13.0	27440202

ETIM

ETIM 9.0	EC000437
----------	----------

UNSPSC

UNSPSC 21.0	31261500
-------------	----------

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

HC-STA-B16-SLFDC-2SSM32-ELC-AL - Housing



1412850

<https://www.phoenixcontact.com/us/products/1412850>

Accessories

G-INS-M32-M68N-NNES-S - Cable gland

1411166

<https://www.phoenixcontact.com/us/products/1411166>



Cable gland, material for screw connection: Brass, nickel-plated, application: Standard, external cable diameter 15 mm ... 21 mm, shielding: no, connecting thread: M32 x 1.5, color: silver, with O-ring

G-INSEC-M32-M68N-NCRS-S - Cable gland

1411191

<https://www.phoenixcontact.com/us/products/1411191>



Cable gland, material for screw connection: Brass, nickel-plated, application: EMC, external cable diameter 14 mm ... 21 mm, shielding: yes, connecting thread: M32 x 1.5, color: silver, with O-ring

HC-STA-B16-SLFDC-2SSM32-ELC-AL - Housing

1412850

<https://www.phoenixcontact.com/us/products/1412850>



HC-B16-SP-CBK - Profile gasket

1411480

<https://www.phoenixcontact.com/us/products/1411480>



Profile gasket for HEAVYCON EVO supporting base element type B16, conductive

HC-B16-BC-HI-PLBK - Protective cover

1407694

<https://www.phoenixcontact.com/us/products/1407694>



Protective cover B16, for single locking latch, protective cover material: PC, height: 19 mm, seal: no

HC-STA-B16-SLFDC-2SSM32-ELC-AL - Housing

1412850

<https://www.phoenixcontact.com/us/products/1412850>



HC-STA-B16-DC-PL - Protective cover

1421102

<https://www.phoenixcontact.com/us/products/1421102>



Protective cover, design: B16

WP-G HF IP66 M32 BK - Screw connection

3240900

<https://www.phoenixcontact.com/us/products/3240900>



Cable gland, metric thread, IP66 protection, straight

HC-STA-B16-SLFDC-2SSM32-ELC-AL - Housing

1412850

<https://www.phoenixcontact.com/us/products/1412850>



WP-G HF IP69K M32 BK - Screw connection

3240886

<https://www.phoenixcontact.com/us/products/3240886>

Cable gland, metric thread, IP68/69k protection, straight



WP-GA HF IP66 M32 BK - Screw connection

3240928

<https://www.phoenixcontact.com/us/products/3240928>

Cable gland, metric thread, IP66 protection, angled



HC-STA-B16-SLFDC-2SSM32-ELC-AL - Housing

1412850

<https://www.phoenixcontact.com/us/products/1412850>



WP-GA HF IP69K M32 BK - Screw connection

3240914

<https://www.phoenixcontact.com/us/products/3240914>

Cable gland, metric thread, IP68/69k protection, angled



WP-GR HF IP66 M32 BK - Screw connection

3240956

<https://www.phoenixcontact.com/us/products/3240956>

Cable gland, metric thread, IP66 protection, with strain relief



HC-STA-B16-SLFDC-2SSM32-ELC-AL - Housing

1412850

<https://www.phoenixcontact.com/us/products/1412850>



WP-GR HF IP69K M32 BK - Screw connection

3240942

<https://www.phoenixcontact.com/us/products/3240942>



Cable gland, metric thread, IP68/69k protection, with strain relief

WP-G PP HF M32 - Screw connection

3241000

<https://www.phoenixcontact.com/us/products/3241000>



Cable gland made from PP with metric thread, IP65 protection

HC-STA-B16-SLFDC-2SSM32-ELC-AL - Housing



1412850

<https://www.phoenixcontact.com/us/products/1412850>

WP-GT PP HF M32 - Screw connection

3241014

<https://www.phoenixcontact.com/us/products/3241014>



Cable gland made from PP with metric thread, rotatable, IP54 protection

WP-G BRASS IP40 M32 - Screw connection

3241049

<https://www.phoenixcontact.com/us/products/3241049>



Cable gland made from brass with metric thread, IP40 protection

HC-STA-B16-SLFDC-2SSM32-ELC-AL - Housing



1412850

<https://www.phoenixcontact.com/us/products/1412850>

WP-GT BRASS M32 - Screw connection

3241035

<https://www.phoenixcontact.com/us/products/3241035>

Cable gland made from brass with metric thread, rotatable, IP40 protection



WP-G BRASS IP65 M32 - Screw connection

3241063

<https://www.phoenixcontact.com/us/products/3241063>

Cable gland made from brass with metric thread, IP65 protection



Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com