

HC-STA-B16-SLWD-2SSP21-ELC-AL - Housing



1412857

<https://www.phoenixcontact.com/gb/products/1412857>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Box mounting bases B16, with double locking latch, material: Die-cast aluminum, salt water resistant, cable outlets: 2, lateral, 2x Pg21, height: 68 mm, cable gland: none, Standard

Your advantages

- Good shielding in the event of electromagnetic interference

Commercial data

Item number	1412857
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF7APB
Product key	BF7APB
Catalog page	Page 623 (C-2-2019)
GTIN	4055626060781
Weight per piece (including packing)	302.9 g
Weight per piece (excluding packing)	304 g
Customs tariff number	85389099
Country of origin	PL

HC-STA-B16-SLWD-2SSP21-ELC-AL - Housing



1412857

<https://www.phoenixcontact.com/gb/products/1412857>

Technical data


Notes

General	For contact inserts HC-B16, BB32, D40, DD72, HS6, HV6, M, K
General	also available as a powder-coated or color version: 1372641 HC-STA-B16-SLWD-2SSP21-EL/.../...

Product properties

Product type	Housing with locking latch
Housing type	Box mounting bases
Application	Standard
Type	B16
No. of cable outlets	2
Type of the screw connection	2x Pg21
Cable outlet	lateral
Pg screw connection	none

Dimensions

Dimensional drawing	
Width	57 mm
Height	68 mm
Length	117.5 mm
Hole diameter	5.5 mm

Material specifications

Flammability rating according to UL 94	V0 (Interlock)
Seal material	NBR, conductive
Housing material	Die-cast aluminum, salt water resistant
Housing surface material	uncoated
Locking latch material	PA

Mechanical properties

Mechanical data

Type of the screw connection	2x Pg21
Locking type	Latch

Mounting

Assembly note	One opening is sealed with a plastic filler plug and can be opened using a screwdriver.
---------------	---

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP66
	IP67
Enclosure rating (NEMA)	4 (UL 50e)
	4X (UL 50e)
	12 (UL 50e)
Impact strength	IK09
Ambient temperature (operation)	-40 °C ... 125 °C

HC-STA-B16-SLWD-2SSP21-ELC-AL - Housing


1412857

<https://www.phoenixcontact.com/gb/products/1412857>



Drawings

Dimensional drawing



Dimensional drawing

1412857

<https://www.phoenixcontact.com/gb/products/1412857>

Approvals

 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/gb/products/1412857>

DNV

Approval ID: TAE000037S



cUL Recognized

Approval ID: E255026



UL Recognized

Approval ID: E255026



EAC

Approval ID: RU C-DE.AI30.B.01102



EAC

Approval ID: RU C-DE.BL08.B.00511

cULus Recognized

1412857

<https://www.phoenixcontact.com/gb/products/1412857>

Classifications

ECLASS

ECLASS-11.0	27440202
ECLASS-12.0	27440202
ECLASS-13.0	27440202

ETIM

ETIM 9.0	EC000437
----------	----------

UNSPSC

UNSPSC 21.0	31261500
-------------	----------

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

1412857

<https://www.phoenixcontact.com/gb/products/1412857>

Accessories

G-INS-PG21-M68N-NNES-S - Cable gland

1411175

<https://www.phoenixcontact.com/gb/products/1411175>



Cable gland, material for screw connection: Brass, nickel-plated, application: Standard, external cable diameter 13 mm ... 18 mm, shielding: no, connecting thread: Pg21, color: silver, with O-ring

G-INSEC-PG21-M68N-NNES-S - Cable gland

1411200

<https://www.phoenixcontact.com/gb/products/1411200>



Cable gland, material for screw connection: Brass, nickel-plated, application: EMC, external cable diameter 13 mm ... 18 mm, shielding: yes, connecting thread: Pg21, color: silver, with O-ring

HC-STA-B16-SLWD-2SSP21-ELC-AL - Housing



1412857

<https://www.phoenixcontact.com/gb/products/1412857>

HC-B16-SP-CBK - Profile gasket

1411480

<https://www.phoenixcontact.com/gb/products/1411480>



Profile gasket for HEAVYCON EVO supporting base element type B16, conductive

HC-STA-B10-24-DL-PLBK - Housing brackets

1412886

<https://www.phoenixcontact.com/gb/products/1412886>



Double locking latch for B10 / B16 / B24 housing, HC-EVO....AL and HC-STA....AL

HC-STA-B16-SLWD-2SSP21-ELC-AL - Housing



1412857

<https://www.phoenixcontact.com/gb/products/1412857>

HC-B16-BC-HI-PLBK - Protective cover

1407694

<https://www.phoenixcontact.com/gb/products/1407694>

Protective cover B16, for single locking latch, protective cover material: PC, height: 19 mm, seal: no



HC-B16-BCFD-P-BK - Protective cover

1346539

<https://www.phoenixcontact.com/gb/products/1346539>

Protective cover B16, for double locking latch, protective cover material: PC, height: 26.4 mm, seal: no



HC-STA-B16-SLWD-2SSP21-ELC-AL - Housing

1412857

<https://www.phoenixcontact.com/gb/products/1412857>



HC-STA-B16-DC-PL - Protective cover

1421102

<https://www.phoenixcontact.com/gb/products/1421102>



Protective cover, design: B16

WP-G HF IP66 PG21 BK - Screw connection

3240892

<https://www.phoenixcontact.com/gb/products/3240892>



Cable gland, Pg thread, IP66 protection, straight

HC-STA-B16-SLWD-2SSP21-ELC-AL - Housing

1412857

<https://www.phoenixcontact.com/gb/products/1412857>



WP-G HF IP69K PG21 BK - Screw connection

3240878

<https://www.phoenixcontact.com/gb/products/3240878>



Cable gland, Pg thread, IP68/69k protection, straight

WP-GA HF IP66 PG21 BK - Screw connection

3240920

<https://www.phoenixcontact.com/gb/products/3240920>



Cable gland, Pg thread, IP66 protection, angled

HC-STA-B16-SLWD-2SSP21-ELC-AL - Housing

1412857

<https://www.phoenixcontact.com/gb/products/1412857>



WP-GR HF IP66 PG21 BK - Screw connection

3240948

<https://www.phoenixcontact.com/gb/products/3240948>



Cable gland, Pg thread, IP66 protection, with strain relief

WP-GR HF IP69K PG21 BK - Screw connection

3240934

<https://www.phoenixcontact.com/gb/products/3240934>



Cable gland, Pg thread, IP68/69k protection, with strain relief

HC-STA-B16-SLWD-2SSP21-ELC-AL - Housing



1412857

<https://www.phoenixcontact.com/gb/products/1412857>

WP-G PP HF PG21 - Screw connection

3240992

<https://www.phoenixcontact.com/gb/products/3240992>

Cable gland made from PP with Pg thread, IP65 protection



WP-GT PP HF PG21 - Screw connection

3241006

<https://www.phoenixcontact.com/gb/products/3241006>

Cable gland made from PP with Pg thread, rotatable, IP54 protection



HC-STA-B16-SLWD-2SSP21-ELC-AL - Housing



1412857

<https://www.phoenixcontact.com/gb/products/1412857>

WP-G BRASS IP40 PG21 - Screw connection

3241041

<https://www.phoenixcontact.com/gb/products/3241041>

Cable gland made from brass with Pg thread, IP40 protection



WP-GT BRASS PG21 - Screw connection

3241027

<https://www.phoenixcontact.com/gb/products/3241027>

Cable gland made from brass with Pg thread, rotatable, IP40 protection



HC-STA-B16-SLWD-2SSP21-ELC-AL - Housing

1412857

<https://www.phoenixcontact.com/gb/products/1412857>



WP-G BRASS IP65 PG21 - Screw connection

3241055

<https://www.phoenixcontact.com/gb/products/3241055>

Cable gland made from brass with Pg thread, IP65 protection



Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd

Halesfield 13, Telford

Shropshire, TF7 4PG

01952 681700

info@phoenixcontact.co.uk