

1412881

https://www.phoenixcontact.com/au/products/1412881

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Box mounting bases B24, with single locking latch, material: Die-cast aluminum, salt water resistant, protective cover material: PC, cable outlets: 2, lateral, 2x M25, height: 68 mm, cable gland: none, protective cover: yes, Standard

### Your advantages

• Good shielding in the event of electromagnetic interference

### Commercial data

Item number	1412881
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF7APB
Product key	BF7APB
Catalog page	Page 633 (C-2-2019)
GTIN	4055626061306
Weight per piece (including packing)	402.2 g
Weight per piece (excluding packing)	390.891 g
Customs tariff number	85389099
Country of origin	CN



1412881

https://www.phoenixcontact.com/au/products/1412881

### Technical data

### Notes

General	for contact inserts HC-B24, BB46, D64, DD108, HV10/16, M
General	also available as a powder-coated or color version: 1372717 HC-STA-B24-SLWSC-2SSM25-EL//

### Product properties

Product type	Housing with locking latch
Housing type	Box mounting bases
Application	Standard
Туре	B24
No. of cable outlets	2
Type of the screw connection	2x M25
Туре	Low design
Protective cover	yes
Cable outlet	lateral
Pg screw connection	none

#### **Dimensions**

Dimensional drawing	05.5 132 144 57
Width	57 mm
Height	68 mm
Length	144 mm
Hole diameter	5.5 mm

### Material specifications

Flammability rating according to UL 94	V0 (Interlock)
	V0 (Protective cover)
Seal material	NBR, conductive
Housing material	Die-cast aluminum, salt water resistant
Housing surface material	uncoated
Material, protective cover	PC
Locking latch material	PA

### Mechanical properties

#### Mechanical data

Type of the screw connection	2x M25
Locking type	Latch



1412881

https://www.phoenixcontact.com/au/products/1412881

### Connection data

	Tightening torque	2 Nm 3 Nm (for M5 mounting screws on the surface-mount housing)
М	ounting	
	Assembly note	One opening is sealed with a plastic filler plug and can be opened using a screwdriver

### Environmental and real-life conditions

#### Ambient conditions

Degree of protection	IP66 (with locked protective cover)
	IP67 (when plugged in)
Impact strength	IK08
Ambient temperature (operation)	-40 °C 125 °C




1412881

https://www.phoenixcontact.com/au/products/1412881

### Drawings

### Dimensional drawing



Dimensional drawing



1412881

https://www.phoenixcontact.com/au/products/1412881

### **Approvals**

☼ To download certificates, visit the product detail page: https://www.phoenixcontact.com/au/products/1412881

DNV

Approval ID: TAE000037S



EAC

Approval ID: RU C-DE.Al30.B.01102



EAC

Approval ID: RU C-DE.BL08.B.00511



cUL Recognized

Approval ID: E255026



**UL Recognized** 

Approval ID: E255026

cULus Recognized



1412881

https://www.phoenixcontact.com/au/products/1412881

### Classifications

UNSPSC 21.0

### **ECLASS**

ECLASS-11.0	27440202	
ECLASS-12.0	27440202	
ECLASS-13.0	27440202	
ETIM		
ETIM 9.0	EC000437	
UNSPSC		

31261500



1412881

https://www.phoenixcontact.com/au/products/1412881

### Environmental product compliance

		:oF	$\sim$
тι	JK	() [	כו

Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%



1412881

https://www.phoenixcontact.com/au/products/1412881

### Accessories

### G-INS-M25-M68N-NNES-S - Cable gland

1411165

https://www.phoenixcontact.com/au/products/1411165



Cable gland, material for screw connection: Brass, nickel-plated, application: Standard, external cable diameter 11 mm ... 17 mm, shielding: no, connecting thread: M25 x 1.5, color: silver, with O-ring

### G-INSEC-M25-S68N-NCRS-S - Cable gland

1411190

https://www.phoenixcontact.com/au/products/1411190



Cable gland, material for screw connection: Brass, nickel-plated, application: EMC, external cable diameter 11 mm  $\dots$  16 mm, shielding: yes, connecting thread: M25 x 1.5, color: silver, with O-ring



1412881

https://www.phoenixcontact.com/au/products/1412881

### HC-M-KV-M25(1ASI) - Cable gland

1584020

https://www.phoenixcontact.com/au/products/1584020



Metal screw connection for an AS-Interface flat-ribbon conductor, thread type  $^{\rm M25}$ 

### HC-B24-SP-CBK - Profile gasket

1411482

https://www.phoenixcontact.com/au/products/1411482



Profile gasket for HEAVYCON EVO supporting base element type B24, conductive



1412881

https://www.phoenixcontact.com/au/products/1412881

### HC-STA-B24-SL-PLBK - Housing brackets

1412885

https://www.phoenixcontact.com/au/products/1412885



Single locking latch for B24 housing, HC-EVO....AL and HC-STA....AL

#### HC-B24-BC-HI-PLBK - Protective cover

1407695

https://www.phoenixcontact.com/au/products/1407695

Protective cover B24, for single locking latch, protective cover material: PC, height: 19 mm, seal: no





1412881

https://www.phoenixcontact.com/au/products/1412881

### HC-STA-B24-DC-PL - Protective cover

1421103

https://www.phoenixcontact.com/au/products/1421103



Protective cover, design: B24

### WP-G HF IP66 M25 BK - Screw connection

3240899

https://www.phoenixcontact.com/au/products/3240899



Cable gland, metric thread, IP66 protection, straight



1412881

https://www.phoenixcontact.com/au/products/1412881

### WP-G HF IP69K M25 BK - Screw connection

3240885

https://www.phoenixcontact.com/au/products/3240885



Cable gland, metric thread, IP68/69k protection, straight

### WP-GA HF IP66 M25 BK - Screw connection

3240927

https://www.phoenixcontact.com/au/products/3240927

Cable gland, metric thread, IP66 protection, angled





1412881

https://www.phoenixcontact.com/au/products/1412881

### WP-GA HF IP69K M25 BK - Screw connection

3240913

https://www.phoenixcontact.com/au/products/3240913

Cable gland, metric thread, IP68/69k protection, angled



### WP-GR HF IP66 M25 BK - Screw connection

3240955

https://www.phoenixcontact.com/au/products/3240955







1412881

https://www.phoenixcontact.com/au/products/1412881

### WP-GR HF IP69K M25 BK - Screw connection

3240941

https://www.phoenixcontact.com/au/products/3240941



Cable gland, metric thread, IP68/69k protection, with strain relief

### WP-G PP HF M25 - Screw connection

3240999

https://www.phoenixcontact.com/au/products/3240999



Cable gland made from PP with metric thread, IP65 protection



1412881

https://www.phoenixcontact.com/au/products/1412881

### WP-GT PP HF M25 - Screw connection

3241013

https://www.phoenixcontact.com/au/products/3241013



Cable gland made from PP with metric thread, rotatable, IP54 protection

### WP-G BRASS IP40 M25 - Screw connection

3241048

https://www.phoenixcontact.com/au/products/3241048



Cable gland made from brass with metric thread, IP40 protection



1412881

https://www.phoenixcontact.com/au/products/1412881

### WP-GT BRASS M25 - Screw connection

3241034

https://www.phoenixcontact.com/au/products/3241034



Cable gland made from brass with metric thread, rotatable, IP40 protection

#### WP-G BRASS IP65 M25 - Screw connection

3241062

https://www.phoenixcontact.com/au/products/3241062



Cable gland made from brass with metric thread, IP65 protection

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT PTY Ltd Unit 7, 2-8 South Street Rydalmere NSW 2116 1300 786 411 customerservice@phoenixcontact.com.au