

# HC-STA-B24-SLWSC-2SSP21-ELC-AL - Housing



1412883

<https://www.phoenixcontact.com/us/products/1412883>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Box mounting bases B24, with single locking latch, material: Die-cast aluminum, salt water resistant, protective cover material: PC, cable outlets: 2, lateral, 2x Pg21, height: 68 mm, cable gland: none, protective cover: yes, Standard

## Your advantages

- Good shielding in the event of electromagnetic interference

## Commercial data

Item number	1412883
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF56
Product key	BF7APB
Catalog page	Page 633 (C-2-2019)
GTIN	4055626061320
Weight per piece (including packing)	393 g
Weight per piece (excluding packing)	380 g
Customs tariff number	85389099
Country of origin	CN

# HC-STA-B24-SLWSC-2SSP21-ELC-AL - Housing



1412883

<https://www.phoenixcontact.com/us/products/1412883>

## Technical data


### Notes

General	for contact inserts HC-B24, BB46, D64, DD108, HV10/16, M
General	also available as a powder-coated or color version: 1372658 HC-STA-B24-SLWSC-2SSP21-EL/.../...

### Product properties

Product type	Housing with locking latch
Housing type	Box mounting bases
Application	Standard
Type	B24
No. of cable outlets	2
Type of the screw connection	2x Pg21
Type	Low design
Protective cover	yes
Cable outlet	lateral
Pg screw connection	none

### Dimensions

Dimensional drawing	
Width	57 mm
Height	68 mm
Length	144 mm
Hole diameter	5.5 mm

### Material specifications

Flammability rating according to UL 94	V0 (Interlock)
	V0 (Protective cover)
Seal material	NBR, conductive
Housing material	Die-cast aluminum, salt water resistant
Housing surface material	uncoated
Material, protective cover	PC
Locking latch material	PA

### Mechanical properties

#### Mechanical data

Type of the screw connection	2x Pg21
Locking type	Latch

# HC-STA-B24-SLWSC-2SSP21-ELC-AL - Housing



1412883

<https://www.phoenixcontact.com/us/products/1412883>

## Connection data

Tightening torque	2 Nm ... 3 Nm (for M5 mounting screws on the surface-mount housing)
-------------------	---

## Mounting

Assembly note	One opening is sealed with a plastic filler plug and can be opened using a screwdriver.
---------------	---

## Environmental and real-life conditions

Ambient conditions	
Degree of protection	IP66 (with locked protective cover)
	IP67 (when plugged in)
Impact strength	IK08
Ambient temperature (operation)	-40 °C ... 125 °C

# HC-STA-B24-SLWSC-2SSP21-ELC-AL - Housing




1412883

<https://www.phoenixcontact.com/us/products/1412883>

## Drawings

Dimensional drawing



Dimensional drawing


1412883


<https://www.phoenixcontact.com/us/products/1412883>


Approvals


To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1412883>

**DNV**  
Approval ID: TAE000037S

**EAC**  
Approval ID: RU C-DE.AI30.B.01102

**EAC**  
Approval ID: RU C-DE.BL08.B.00511

**cUL Recognized**  
Approval ID: E255026

**UL Recognized**  
Approval ID: E255026

**cULus Recognized**

1412883

<https://www.phoenixcontact.com/us/products/1412883>

## Classifications

### ECLASS

ECLASS-11.0	27440202
ECLASS-12.0	27440202
ECLASS-13.0	27440202

### ETIM

ETIM 9.0	EC000437
----------	----------

### UNSPSC

UNSPSC 21.0	31261500
-------------	----------

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

1412883

<https://www.phoenixcontact.com/us/products/1412883>

## Accessories

### G-INS-PG21-M68N-NNES-S - Cable gland

1411175

<https://www.phoenixcontact.com/us/products/1411175>



Cable gland, material for screw connection: Brass, nickel-plated, application: Standard, external cable diameter 13 mm ... 18 mm, shielding: no, connecting thread: Pg21, color: silver, with O-ring

---

### G-INSEC-PG21-M68N-NNES-S - Cable gland

1411200

<https://www.phoenixcontact.com/us/products/1411200>



Cable gland, material for screw connection: Brass, nickel-plated, application: EMC, external cable diameter 13 mm ... 18 mm, shielding: yes, connecting thread: Pg21, color: silver, with O-ring



# HC-STA-B24-SLWSC-2SSP21-ELC-AL - Housing

1412883

<https://www.phoenixcontact.com/us/products/1412883>



## HC-B24-SP-CBK - Profile gasket

1411482

<https://www.phoenixcontact.com/us/products/1411482>



Profile gasket for HEAVYCON EVO supporting base element type B24, conductive

---

## HC-STA-B24-SL-PLBK - Housing brackets

1412885

<https://www.phoenixcontact.com/us/products/1412885>



Single locking latch for B24 housing, HC-EVO....AL and HC-STA....AL

# HC-STA-B24-SLWSC-2SSP21-ELC-AL - Housing

1412883

<https://www.phoenixcontact.com/us/products/1412883>



## HC-B24-BC-HI-PLBK - Protective cover

1407695

<https://www.phoenixcontact.com/us/products/1407695>

Protective cover B24, for single locking latch, protective cover material: PC, height: 19 mm, seal: no



---

## HC-STA-B24-DC-PL - Protective cover

1421103

<https://www.phoenixcontact.com/us/products/1421103>

Protective cover, design: B24



# HC-STA-B24-SLWSC-2SSP21-ELC-AL - Housing

1412883

<https://www.phoenixcontact.com/us/products/1412883>



## WP-G HF IP66 PG21 BK - Screw connection

3240892

<https://www.phoenixcontact.com/us/products/3240892>

Cable gland, Pg thread, IP66 protection, straight



---

## WP-G HF IP69K PG21 BK - Screw connection

3240878

<https://www.phoenixcontact.com/us/products/3240878>

Cable gland, Pg thread, IP68/69k protection, straight



# HC-STA-B24-SLWSC-2SSP21-ELC-AL - Housing

1412883

<https://www.phoenixcontact.com/us/products/1412883>



## WP-GA HF IP66 PG21 BK - Screw connection

3240920

<https://www.phoenixcontact.com/us/products/3240920>

Cable gland, Pg thread, IP66 protection, angled



---

## WP-GR HF IP66 PG21 BK - Screw connection

3240948

<https://www.phoenixcontact.com/us/products/3240948>

Cable gland, Pg thread, IP66 protection, with strain relief



# HC-STA-B24-SLWSC-2SSP21-ELC-AL - Housing

1412883

<https://www.phoenixcontact.com/us/products/1412883>



## WP-GR HF IP69K PG21 BK - Screw connection

3240934

<https://www.phoenixcontact.com/us/products/3240934>



Cable gland, Pg thread, IP68/69k protection, with strain relief

---

## WP-G PP HF PG21 - Screw connection

3240992

<https://www.phoenixcontact.com/us/products/3240992>



Cable gland made from PP with Pg thread, IP65 protection

# HC-STA-B24-SLWSC-2SSP21-ELC-AL - Housing



1412883

<https://www.phoenixcontact.com/us/products/1412883>

## WP-GT PP HF PG21 - Screw connection

3241006

<https://www.phoenixcontact.com/us/products/3241006>



Cable gland made from PP with Pg thread, rotatable, IP54 protection

---

## WP-G BRASS IP40 PG21 - Screw connection

3241041

<https://www.phoenixcontact.com/us/products/3241041>



Cable gland made from brass with Pg thread, IP40 protection

# HC-STA-B24-SLWSC-2SSP21-ELC-AL - Housing



1412883

<https://www.phoenixcontact.com/us/products/1412883>

## WP-GT BRASS PG21 - Screw connection

3241027

<https://www.phoenixcontact.com/us/products/3241027>

Cable gland made from brass with Pg thread, rotatable, IP40 protection



---

## WP-G BRASS IP65 PG21 - Screw connection

3241055

<https://www.phoenixcontact.com/us/products/3241055>

Cable gland made from brass with Pg thread, IP65 protection



---

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)