

SACC-DSI-M12FSB-5CON-M16/0,8 - Device connector rear mounting



1413176
<https://www.phoenixcontact.com/us/products/1413176>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Device connector rear mounting, 5-position, Socket, straight, M12, coding: B, on free cable end, Rear wall/screw mounting, M16 x 1.5, Individual wires, cable length: 0.8 m, 0.34 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1239011

Commercial data

Item number	1413176
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AB24
Product key	ABQCHB
GTIN	4046356990837
Weight per piece (including packing)	41.8 g
Weight per piece (excluding packing)	31.7 g
Customs tariff number	85444290
Country of origin	DE

SACC-DSI-M12FSB-5CON-M16/0,8 - Device connector rear mounting



1413176

<https://www.phoenixcontact.com/us/products/1413176>

Technical data

Notes

Order information:	Lock nut is included in the scope of delivery
General	Contact connection method: Crimp connection

Safety note

Safety note	<p>WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.</p> <ul style="list-style-type: none">• WARNING: Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible.• WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.• The products are suitable for applications in plant, controller, and electrical device engineering.• When operating the connectors in outdoor applications, they must be separately protected against environmental influences.• Assembled products may not be manipulated or improperly opened.• Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products).• When using the product in direct connection with third-party manufacturers, the user is responsible.• For operating voltages > 50 V AC, conductive connector housings must be grounded• Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards.• Observe the corresponding technical data. You will find information:<ul style="list-style-type: none">o On the producto On the packing labelo In the supplied documentationo Online at phoenixcontact.com/products under the product• Only use tools recommended by Phoenix Contact• Use a protective cap to protect connectors that are not in use. The suitable accessories are available online in the accessory section of the product at phoenixcontact.com/products• Ensure that the protective or functional ground has been properly connected.• VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or
-------------	---

SACC-DSI-M12FSB-5CON-M16/0,8 - Device connector rear mounting



1413176

<https://www.phoenixcontact.com/us/products/1413176>

connector

- The connector warms up in normal operation. Depending on the ambient conditions, the surface of the connector can continue to warm up. In this case, the user is responsible for posting warnings (e.g. DIN EN ISO 13732-1:2008-12).

Mounting

Mounting type

Rear wall/screw mounting M16 x 1.5

Product properties

Product type

Circular connectors (device side)

Number of positions

5

No. of cable outlets

1

Coding

B

Thread type

M12

Insulation characteristics

Overvoltage category

III

Degree of pollution

3

Material specifications

Flammability rating according to UL 94

V0

Electrical properties

Rated surge voltage

1.5 kV AC

Nominal voltage U_N

60 V

Nominal current I_N

4 A

Connection data

Conductor connection

Connection method

Individual wires

Contact connection type

Socket

Conductor cross section

0.34 mm²

Connector

Connection 1

Head design

Socket

Head cable outlet

straight

Head thread type

M12

Coding

B

Connection 2

Head design

free cable end

SACC-DSI-M12FSB-5CON-M16/0,8 - Device connector rear mounting



1413176

<https://www.phoenixcontact.com/us/products/1413176>

Cable/line

Cable length	0.8 m
Cable cross section	0.34 mm ²

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP67 (When plugged in)
	IP65 (When plugged in)
Ambient temperature (operation)	-25 °C ... 85 °C


Standards and regulations


Standards/specifications	according to IEC 61076-2-101
--------------------------	------------------------------


1413176
<https://www.phoenixcontact.com/us/products/1413176>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1413176>

<div> cUL Recognized Approval ID: E118976-20100522</div>				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	60 V	4 A	22 - 22	-

<div> UL Recognized Approval ID: E118976-20100522</div>				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	60 V	4 A	22 - 22	-

<div> cULus Recognized Approval ID: E221474-20140616</div>				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	60 V	4 A	22 - 20	-

cULus Recognized				
------------------	--	--	--	--

SACC-DSI-M12FSB-5CON-M16/0,8 - Device connector rear mounting



1413176

<https://www.phoenixcontact.com/us/products/1413176>

Classifications

ECLASS

ECLASS-11.0	27440109
ECLASS-12.0	27440109
ECLASS-13.0	27440109

ETIM

ETIM 8.0	EC003569
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

SACC-DSI-M12FSB-5CON-M16/0,8 - Device connector rear mounting



1413176
<https://www.phoenixcontact.com/us/products/1413176>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	63f11d7f-848c-416e-b09b-e2ba8a395a4e

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com