

FO patch cable - FOC-SC:A-SC:A-GZ04/1 - 1413828

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid
(<http://phoenixcontact.com/download>)



Assembled FO cable, zip cord cable, multi-mode fiberglass 62.5/125 µm, OM1, connector: SC duplex/SC duplex, degree of protection: IP20, for installation in cable ducts or control cabinets

Why buy this product

- ✓ Multi-mode patch cable for indoor installation
- ✓ Ideal for use in distributor systems and for connecting termination devices
- ✓ All components satisfy UL 94, V0
- ✓ 2.8 mm single elements made from halogen-free and flame-retardant material
- ✓ Interferometer tests at every stage of the certification process
- ✓ Excellent mechanical and optical properties
- ✓ Satisfies optical and mechanical industry standards
- ✓ Connector with UPC polishing for optimum attenuation values
- ✓ Individual test report with ≤ 0.3 dB insertion loss, measured according to IEC 61300-3-4
- ✓ Individual test report with ≥ 35 dB return loss, measured according to IEC 61300-3-6
- ✓ Comprehensively tested according to IEC 61753-122-2 and IEC 61753-1 Cat. C
- ✓ Temperature fluctuation test according to IEC 61300-2-1
- ✓ Vibration test according to IEC 61300-2-1
- ✓ Tensile strength of the cable connection according to IEC 61300-2-5



Key Commercial Data

Packing unit	1 STK
GTIN	 4 055626 009667
GTIN	4055626009667

Technical data

Standards and Regulations

Halogen-free	According to IEC 60754-2
Flammability rating according to UL 94	V0

FO patch cable - FOC-SC:A-SC:A-GZ04/1 - 1413828

Approvals

Approvals

Approvals

UL Listed

Ex Approvals

Approval details

UL Listed



<http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm> E308814-20070105

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>