

HC-M-02-CT-M - Contact insert module



1414360

<https://www.phoenixcontact.com/us/products/1414360>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Contact insert module, number of positions: 2, power contacts: 2, control contacts: 0, Pin, Crimp connection, 830 V, 40 A, 1.5 mm² ... 10 mm², application: Power

Commercial data

Item number	1414360
Packing unit	5 pc
Minimum order quantity	1 pc
Sales key	BF62
Product key	BF7ACE
Catalog page	Page 575 (C-2-2019)
GTIN	4055626025032
Weight per piece (including packing)	11.8 g
Weight per piece (excluding packing)	10.926 g
Customs tariff number	85389099
Country of origin	PL

HC-M-02-CT-M - Contact insert module



1414360

<https://www.phoenixcontact.com/us/products/1414360>

Technical data

Notes

General	For HEAVYCON housing type B6 to B48, HC-M-B...MF-... hinged module carrier frame required, CK4,0..... crimp contacts, crimp contacts not supplied as standard.
General	Connectors may be operated only when there is no load/voltage.

Mounting

Assembly note	To ensure correct use, installation in housing with IP54 protection or better is required
---------------	---

Product properties

Product type	Modular contact insert
Series	HC-M-02
Application	Power
Number of positions	2
Connection profile	2
Contact numbering	1 - 2
Number of module slots	1
No. of power contacts	2
No. of control contacts	0
Contact material type	turned

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Data management status

Article revision	02
------------------	----

Connection data

Connection technology

Connection technology	Crimp connection
Connection in acc. with standard	IEC / EN

Conductor connection

Conductor cross section	1.5 mm² ... 10 mm²
Connection cross section AWG	16 ... 8
Stripping length of the individual wire	9 mm (for 1.5 ... 2.5 mm²)
	14 mm (for 4 mm² ... 6 mm²)
	14 mm (for 10 mm²)

Dimensions


HC-M-02-CT-M - Contact insert module



1414360

<https://www.phoenixcontact.com/us/products/1414360>

Dimensional drawing



Width	34.2 mm
Height	43.7 mm
Length	14.6 mm

Mechanical characteristics

Contact diameter	4 mm
------------------	------

Electrical properties

Rated voltage (III/2) contacts	1000 V
Rated voltage (III/3)	830 V
Rated surge voltage (III/2)	8 kV
Rated surge voltage (III/3)	8 kV
Rated surge voltage	8 kV
Rated current	40 A

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 500
-----------------------------	-------

Material specifications

Flammability rating according to UL 94	V0
Contact material	Copper alloy
Contact surface material	Ag
Contact carrier material	PC
Standards/regulations	PC: Fire protection in rail vehicles - requirement sets R22, R23, and R24 acc. to DIN EN 45545-2 (Risk level HL1 - HL3)

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-40 °C ... 125 °C
---------------------------------	-------------------

Standards and regulations

Testing

Standards/regulations	PC: Fire protection in rail vehicles - requirement sets R22, R23, and R24 acc. to DIN EN 45545-2 (Risk level HL1 - HL3)
-----------------------	---

HC-M-02-CT-M - Contact insert module


1414360

<https://www.phoenixcontact.com/us/products/1414360>



Drawings

Schematic diagram



Connector pin assignment, connection side


HC-M-02-CT-M - Contact insert module



1414360


<https://www.phoenixcontact.com/us/products/1414360>

Dimensional drawing



Male insert

Diagram



Derating diagram

HC-M-02-CT-M - Contact insert module



1414360

<https://www.phoenixcontact.com/us/products/1414360>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1414360>

DNV Approval ID: TAE000037S				
---------------------------------------	--	--	--	--

 CSA Approval ID: 13631				
	Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
	600 V	34 A	- 10	-

 UL Recognized Approval ID: E118976				
	Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
	600 V	42 A	- 10	-

 UL Recognized Approval ID: E468743				
	Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
	600 V	42 A	-	-

HC-M-02-CT-M - Contact insert module



1414360

<https://www.phoenixcontact.com/us/products/1414360>

Classifications

ECLASS

ECLASS-11.0	27440217
ECLASS-12.0	27440217
ECLASS-13.0	27440217

ETIM

ETIM 9.0	EC000438
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

HC-M-02-CT-M - Contact insert module



1414360
<https://www.phoenixcontact.com/us/products/1414360>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%
EF3.0 Climate Change	
CO2e kg	0.07 kg CO2e

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com