

QPD W 2PE1,5 4-9 M20 FC BK - Panel feed-through



1414686

<https://www.phoenixcontact.com/us/products/1414686>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Panel feed-through, product family: QPD, connection method: Spade connection (For slip-on sleeves according to DIN 46247-2)/ IDC connection, number of positions: 2+PE, M20, Pin, 0.5 mm² ... 1.5 mm², 690 V, 15 A, PA, black, with QUICKON nut, coding: Coding profile, external cable diameter: 5 mm ... 7 mm and 7 mm ... 9.5 mm, 1.5 mm²

Your advantages

- Innovative and time saving - QUICKON fast connection for time saving of up to 80 % for on-site connection
- Robust throughout: housing with IP68/IP69K and IK07 protection for a wide range of applications
- Safer connection with mechanical coding to protect against mismatching, and touch-proof protection in accordance with DIN EN 0105
- Efficient - by using panel feed-throughs, devices no longer need to be opened in order to connect cables

Commercial data

Item number	1414686
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF50
Product key	BF6AAA
Catalog page	Page 478 (C-2-2019)
GTIN	4055626031392
Weight per piece (including packing)	31.871 g
Weight per piece (excluding packing)	30.998 g
Customs tariff number	85366990
Country of origin	PL

QPD W 2PE1,5 4-9 M20 FC BK - Panel feed-through



1414686

<https://www.phoenixcontact.com/us/products/1414686>

Technical data

Product properties

Product type	Panel feed-through
Product family	QPD
Type	QPD 3x1,5
Number of positions	3
Connection profile	2+PE
Position marking	1, 2, PE
Number of connections	10
Number of connections per position	1
Coding	Coding profile

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Connection data

Connection technology

Connection method On the device side	Spade connection (For slip-on sleeves according to DIN 46247-2)
	IDC connection
Frequency of connections between conductors of the same cross section	max. 10

Conductor connection

Conductor cross section flexibel	0.5 mm ² ... 1.5 mm ²
	0.5 mm ² ... 1.5 mm ²
Connection cross section AWG	20 ... 16
Tightening torque Union nut	8 Nm
	5 Nm

Dimensions

Dimensional drawing	
Width	25 mm
Height	25 mm
Length	61.3 mm
Diameter	25 mm
Dimensions of slip-on connection	4.8 x 0.8 mm

Electrical properties

QPD W 2PE1,5 4-9 M20 FC BK - Panel feed-through



1414686

<https://www.phoenixcontact.com/us/products/1414686>

Rated surge voltage (II/2)	8 kV
Rated surge voltage (III/2)	8 kV
Rated surge voltage (III/3)	6 kV
Rated current	15 A
Contact resistance	< 3 mΩ
rated voltage (II/2)	1000 V
rated voltage (III/2)	1000 V
Rated voltage (III/3)	690 V
Nominal voltage U_N	690 V AC
	690 V DC
Nominal current I_N	15 A

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	max. 50
-----------------------------	---------

Material specifications

Color	black (RAL 9005)
Material Housing	PA
	Cu
	Silver-plated
Flammability rating according to UL 94	V0
Material wire insulation	PVC/PE/TPE/rubber

Cable/line

Structure of individual litz in acc. with VDE 0295 / smallest wire diameter	VDE 0295 class 1 to 6/min. 0.15 mm
External cable diameter	5 mm ... 7 mm
	7 mm ... 9.5 mm
Wire diameter including insulation	1.6 mm ... 3 mm
Position marking	1, 2, PE
Cable cross section	1.5 mm ²
Material wire insulation	PVC/PE/TPE/rubber

Mounting

Mounting type	Front mounting M20
---------------	--------------------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP66
	IP68 (2 m / 24 h)
	IP69K
Ambient temperature (operation)	-40 °C ... 100 °C
Temperature when conductor connected	-5 °C ... 50 °C

QPD W 2PE1,5 4-9 M20 FC BK - Panel feed-through



1414686


<https://www.phoenixcontact.com/us/products/1414686>

Ambient temperature (storage/transport)


-40 °C ... 100 °C

Drawings

Dimensional drawing



Diagram




Derating diagram

QPD W 2PE1,5 4-9 M20 FC BK - Panel feed-through



1414686

<https://www.phoenixcontact.com/us/products/1414686>



Housing cutout

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1414686>



IECEE CB Scheme
Approval ID: DE1-65875



EAC
Approval ID: RU C-DE.BL08.B.00511



DNV GL
Approval ID: TAE00003J5



VDE Zeichengenehmigung
Approval ID: 40029149

	UL Listed Approval ID: E468743			
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	Use group keine			
	600 V	8 A	-	- 16

	cUL Listed Approval ID: E468743			
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	Use group keine			
	600 V	8 A	- 16	-

cULus Listed

QPD W 2PE1,5 4-9 M20 FC BK - Panel feed-through



1414686

<https://www.phoenixcontact.com/us/products/1414686>

Classifications

ECLASS

ECLASS-11.0	27440602
ECLASS-12.0	27440602
ECLASS-13.0	27440602

ETIM

ETIM 9.0	EC002566
----------	----------

UNSPSC

UNSPSC 21.0	39121500
-------------	----------

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

QPD W 2PE1,5 4-9 M20 FC BK - Panel feed-through



1414686

<https://www.phoenixcontact.com/us/products/1414686>

Accessories

CP-QPD 3/4X1,5 - Coding profile

1414729

<https://www.phoenixcontact.com/us/products/1414729>




Coding profile red, for pushing into the QUICKON dome and connector, can be positioned in 90° steps.

Q-MU-M20 BK - Flat nut

1586099

<https://www.phoenixcontact.com/us/products/1586099>



Flat nut, color: black

QPD W 2PE1,5 4-9 M20 FC BK - Panel feed-through

1414686

<https://www.phoenixcontact.com/us/products/1414686>



QPD QSK BK 3/4X1,5 FS - Protective cap

1414722

<https://www.phoenixcontact.com/us/products/1414722>

Protective cap, plastic, for QUICKON connection, black, with retaining cord, IP68



QPD QSK 3/4X1,5 - Protective cap

1414723

<https://www.phoenixcontact.com/us/products/1414723>

Protective cap plastic, for QPD-QUICKON connection 3(4) x 1.5 mm², IP50



QPD W 2PE1,5 4-9 M20 FC BK - Panel feed-through

1414686

<https://www.phoenixcontact.com/us/products/1414686>



SEALING PLUG 7X16 RD - Closing cap

1400255

<https://www.phoenixcontact.com/us/products/1400255>


Closing cap, color: red



QPD W 2PE1,5 4-9 M20 0,5 BK - Panel feed-through

1414684

<https://www.phoenixcontact.com/us/products/1414684>



Panel feed-through, product family: QPD, connection method: Single wires/ IDC connection, number of positions: 2+PE, M20, Pin, 0.5 mm² ... 1.5 mm², 690 V, 17.5 A, PA, black, with QUICKON nut, coding: Coding profile, external cable diameter: 5 mm ... 7 mm and 7 mm ... 9.5 mm, 1.5 mm², cable length: 0.5 m

QPD W 2PE1,5 4-9 M20 FC BK - Panel feed-through

1414686

<https://www.phoenixcontact.com/us/products/1414686>



QPD W 2PE1,5 4-9 M20 1,0 BK - Panel feed-through

1414685

<https://www.phoenixcontact.com/us/products/1414685>



Panel feed-through, product family: QPD, connection method: Single wires/ IDC connection, number of positions: 2+PE, M20, Pin, 0.5 mm² ... 1.5 mm², 690 V, 17.5 A, PA, black, with QUICKON nut, coding: Coding profile, external cable diameter: 5 mm ... 7 mm and 7 mm ... 9.5 mm, 1.5 mm², cable length: 1 m

QPD C 2PE1,5 1X4-9 BK - Conductor connector

1414699

<https://www.phoenixcontact.com/us/products/1414699>



Conductor connector, product family: QPD, connection method: IDC connection, number of positions: 2+PE, 0.5 mm² ... 1.5 mm², 690 V, 17.5 A, PA, black, with one QUICKON nut, coding: Coding profile, external cable diameter: 5 mm ... 7 mm and 7 mm ... 9.5 mm

QPD W 2PE1,5 4-9 M20 FC BK - Panel feed-through

1414686

<https://www.phoenixcontact.com/us/products/1414686>



QPD C 2PE1,5 2X4-9 BK - Conductor connector

1414700

<https://www.phoenixcontact.com/us/products/1414700>



Conductor connector, product family: QPD, connection method: IDC connection, number of positions: 2+PE, 0.5 mm² ... 1.5 mm², 690 V, 17.5 A, PA, black, With two QUICKON nuts, coding: Coding profile, external cable diameter: 5 mm ... 7 mm and 7 mm ... 9.5 mm

QPD T 2PE1,5 2X4-9 BK - T distributor

1414711

<https://www.phoenixcontact.com/us/products/1414711>



T distributor, product family: QPD, connection method: IDC connection, number of positions: 2+PE, 0.5 mm² ... 1.5 mm², 690 V, 17.5 A, PA, black, With two QUICKON nuts, coding: Coding profile, external cable diameter: 5 mm ... 7 mm and 7 mm ... 9.5 mm

QPD W 2PE1,5 4-9 M20 FC BK - Panel feed-through



1414686

<https://www.phoenixcontact.com/us/products/1414686>

QPD T 2PE1,5 3X4-9 BK - T distributor

1414712

<https://www.phoenixcontact.com/us/products/1414712>



T distributor, product family: QPD, connection method: IDC connection, number of positions: 2+PE, 0.5 mm² ... 1.5 mm², 690 V, 17.5 A, PA, black, With three QUICKON nuts, coding: Coding profile, external cable diameter: 5 mm ... 7 mm and 7 mm ... 9.5 mm

QPD H 2PE1,5 4X4-9 BK - H distributor

1414719

<https://www.phoenixcontact.com/us/products/1414719>



H distributor, product family: QPD, connection method: IDC connection, number of positions: 2+PE, 0.5 mm² ... 1.5 mm², 690 V, 17.5 A, PA, black, with four QUICKON nuts, coding: Coding profile, external cable diameter: 5 mm ... 7 mm and 7 mm ... 9.5 mm, with a sealing bolt

QPD W 2PE1,5 4-9 M20 FC BK - Panel feed-through



1414686

<https://www.phoenixcontact.com/us/products/1414686>

QPD N 2PE1,5 4-9 BK - Nut

1415099

<https://www.phoenixcontact.com/us/products/1415099>



Nut, product family: QPD, connection method: IDC connection, number of positions: 2+PE, 0.5 mm² ... 1.5 mm², 690 V, 17.5 A, PA, black, external cable diameter: 5 mm ... 7 mm and 7 mm ... 9.5 mm

QPD P 2PE1,5 4-9 BK - Connector

1414705

<https://www.phoenixcontact.com/us/products/1414705>



Connector, product family: QPD, connection method: IDC connection, number of positions: 2+PE, 0.5 mm² ... 1.5 mm², 690 V, 17.5 A, PA, black, with QUICKON nut, coding: Coding profile, external cable diameter: 5 mm ... 7 mm and 7 mm ... 9.5 mm

QPD W 2PE1,5 4-9 M20 FC BK - Panel feed-through



1414686

<https://www.phoenixcontact.com/us/products/1414686>

QSS 22 - Socket wrench

1670206

<https://www.phoenixcontact.com/us/products/1670206>



Allen wrench, for loosening and fastening the QUICKON union nut, WAF 22 mm

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com