

QPD C 2PE1,5 1X8-13 BK - Conductor connector



1414701

<https://www.phoenixcontact.com/us/products/1414701>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Conductor connector, product family: QPD, connection method: IDC connection, number of positions: 2+PE, 0.5 mm² ... 1.5 mm², 690 V, 17.5 A, PA, black, with one QUICKON nut, coding: Coding profile, external cable diameter: 10 mm ... 13 mm

Your advantages

- Innovative and time saving - QUICKON fast connection for time saving of up to 80 % for on-site connection
- Robust throughout: housing with IP68/IP69K and IK07 protection for a wide range of applications
- Safer connection with mechanical coding to protect against mismatching, and touch-proof protection in accordance with DIN EN 0105
- Easy and safe - with the cable connector, you can repair or extend cables quickly, in combination with the connector as well as the coupling connection

Commercial data

Item number	1414701
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF50
Product key	BF6CAA
Catalog page	Page 475 (C-2-2019)
GTIN	4055626031637
Weight per piece (including packing)	33.6 g
Weight per piece (excluding packing)	33.7 g
Customs tariff number	85366990
Country of origin	PL

QPD C 2PE1,5 1X8-13 BK - Conductor connector



1414701

<https://www.phoenixcontact.com/us/products/1414701>

Technical data

Product properties

Product type	Cable connector
Product family	QPD
Type	QPD 3x1,5
Number of positions	3
Connection profile	2+PE
Position marking	1, 2, PE
Number of connections per position	1
Coding	Coding profile

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Dimensions

Dimensional drawing	
Width	25 mm
Height	25 mm
Length	73.6 mm
Diameter	25 mm

Connection data

Connection technology

Frequency of connections between conductors of the same cross section	max. 10
---	---------

Conductor connection

Tightening torque	8 Nm
	5 Nm
	8 Nm
	5 Nm

Electrical properties

Rated surge voltage (II/2)	8 kV
Rated surge voltage (III/2)	8 kV
Rated surge voltage (III/3)	6 kV
Rated current	17.5 A
Contact resistance	< 3 mΩ
rated voltage (II/2)	1000 V

QPD C 2PE1,5 1X8-13 BK - Conductor connector



1414701

<https://www.phoenixcontact.com/us/products/1414701>

rated voltage (III/2)	1000 V
Rated voltage (III/3)	690 V
Nominal voltage U_N	690 V AC
	690 V DC
Nominal current I_N	17.5 A

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	max. 50
-----------------------------	---------

Material specifications

Color	black (RAL 9005)
Material Housing	PA
	Cu
	Silver-plated
Flammability rating according to UL 94	V0
Material wire insulation	PVC/PE/TPE/rubber

Cable/line

Structure of individual litz in acc. with VDE 0295 / smallest wire diameter	VDE 0295 class 1 to 6/min. 0.15 mm
External cable diameter	10 mm ... 13 mm
Wire diameter including insulation	1.6 mm ... 3 mm
Position marking	1, 2, PE
Halogen-free	yes

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP66
	IP68 (2 m / 24 h)
	IP69K
Ambient temperature (operation)	-40 °C ... 100 °C
Temperature when conductor connected	-5 °C ... 50 °C
Ambient temperature (storage/transport)	-40 °C ... 100 °C

QPD C 2PE1,5 1X8-13 BK - Conductor connector




1414701

<https://www.phoenixcontact.com/us/products/1414701>

Drawings

Dimensional drawing



Dimensional drawing

QPD C 2PE1,5 1X8-13 BK - Conductor connector



1414701

<https://www.phoenixcontact.com/us/products/1414701>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1414701>



IECEE CB Scheme
Approval ID: DE1-65875



EAC
Approval ID: RU C-DE.BL08.B.00511



DNV GL
Approval ID: TAE00003J5



VDE Zeichengenehmigung
Approval ID: 40029149

	UL Listed Approval ID: E468743			
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	Use group keine			
	600 V	8 A	-	- 16

	cUL Listed Approval ID: E468743			
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	Use group keine			
	600 V	8 A	- 16	-

cULus Listed

QPD C 2PE1,5 1X8-13 BK - Conductor connector



1414701

<https://www.phoenixcontact.com/us/products/1414701>

Classifications

ECLASS

ECLASS-11.0	27440605
ECLASS-12.0	27440605
ECLASS-13.0	27440605

ETIM

ETIM 9.0	EC002560
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

QPD C 2PE1,5 1X8-13 BK - Conductor connector



1414701

<https://www.phoenixcontact.com/us/products/1414701>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

QPD C 2PE1,5 1X8-13 BK - Conductor connector



1414701

<https://www.phoenixcontact.com/us/products/1414701>

Mandatory accessories

QPD P 2PE1,5 8-13 BK - Connector

1414706

<https://www.phoenixcontact.com/us/products/1414706>



Connector, product family: QPD, connection method: IDC connection, number of positions: 2+PE, 0.5 mm² ... 1.5 mm², 690 V, 17.5 A, PA, black, with QUICKON nut, coding: Coding profile, external cable diameter: 10 mm ... 13 mm

QPD N 2PE1,5 8-13 BK - Nut

1415100

<https://www.phoenixcontact.com/us/products/1415100>



Nut, product family: QPD, connection method: IDC connection, number of positions: 2+PE, 0.5 mm² ... 1.5 mm², 690 V, 17.5 A, PA, black, external cable diameter: 10 mm ... 13 mm

Accessories

QPD C 2PE1,5 1X8-13 BK - Conductor connector



1414701

<https://www.phoenixcontact.com/us/products/1414701>

CP-QPD 3/4X1,5 - Coding profile

1414729

<https://www.phoenixcontact.com/us/products/1414729>



Coding profile red, for pushing into the QUICKON dome and connector, can be positioned in 90° steps.

SEALING PLUG 10X16 RD - Closing cap

1400284

<https://www.phoenixcontact.com/us/products/1400284>



Closing cap, for threads pluggable, color: red

QPD C 2PE1,5 1X8-13 BK - Conductor connector

1414701

<https://www.phoenixcontact.com/us/products/1414701>



QPD QSK BK 3/4X1,5 FS - Protective cap

1414722

<https://www.phoenixcontact.com/us/products/1414722>

Protective cap, plastic, for QUICKON connection, black, with retaining cord, IP68



QPD QSK 3/4X1,5 - Protective cap

1414723

<https://www.phoenixcontact.com/us/products/1414723>

Protective cap plastic, for QPD-QUICKON connection 3(4) x 1.5 mm², IP50



QPD C 2PE1,5 1X8-13 BK - Conductor connector

1414701

<https://www.phoenixcontact.com/us/products/1414701>



QPD W 2PE1,5 8-13 M20 0,5 BK - Panel feed-through

1414687

<https://www.phoenixcontact.com/us/products/1414687>



Panel feed-through, product family: QPD, connection method: Single wires/ IDC connection, number of positions: 2+PE, M20, Pin, 0.5 mm² ... 1.5 mm², 690 V, 17.5 A, PA, black, with QUICKON nut, coding: Coding profile, external cable diameter: 10 mm ... 13 mm, 1.5 mm², cable length: 0.5 m

QPD W 2PE1,5 8-13 M20 1,0 BK - Panel feed-through

1414688

<https://www.phoenixcontact.com/us/products/1414688>



Panel feed-through, product family: QPD, connection method: Single wires/ IDC connection, number of positions: 2+PE, M20, Pin, 0.5 mm² ... 1.5 mm², 690 V, 17.5 A, PA, black, with QUICKON nut, coding: Coding profile, external cable diameter: 10 mm ... 13 mm, 1.5 mm², cable length: 1 m

QPD C 2PE1,5 1X8-13 BK - Conductor connector

1414701

<https://www.phoenixcontact.com/us/products/1414701>



QPD W 2PE1,5 8-13 M20 FC BK - Panel feed-through

1414689

<https://www.phoenixcontact.com/us/products/1414689>



Panel feed-through, product family: QPD, connection method: Spade connection (For slip-on sleeves according to DIN 46247-2)/ IDC connection, number of positions: 2+PE, M20, Pin, 0.5 mm² ... 1.5 mm², 690 V, 15 A, PA, black, with QUICKON nut, coding: Coding profile, external cable diameter: 10 mm ... 13 mm, 1.5 mm²

QPD C 2PE1,5 2X8-13 BK - Conductor connector

1414702

<https://www.phoenixcontact.com/us/products/1414702>



Conductor connector, product family: QPD, connection method: IDC connection, number of positions: 2+PE, 0.5 mm² ... 1.5 mm², 690 V, 17.5 A, PA, black, With two QUICKON nuts, coding: Coding profile, external cable diameter: 10 mm ... 13 mm

QPD C 2PE1,5 1X8-13 BK - Conductor connector

1414701

<https://www.phoenixcontact.com/us/products/1414701>



QPD T 2PE1,5 2X8-13 BK - T distributor

1414713

<https://www.phoenixcontact.com/us/products/1414713>



T distributor, product family: QPD, connection method: IDC connection, number of positions: 2+PE, 0.5 mm² ... 1.5 mm², 690 V, 17.5 A, PA, black, With two QUICKON nuts, coding: Coding profile, external cable diameter: 10 mm ... 13 mm

QPD T 2PE1,5 3X8-13 BK - T distributor

1414714

<https://www.phoenixcontact.com/us/products/1414714>



T distributor, product family: QPD, connection method: IDC connection, number of positions: 2+PE, 0.5 mm² ... 1.5 mm², 690 V, 17.5 A, PA, black, With three QUICKON nuts, coding: Coding profile, external cable diameter: 10 mm ... 13 mm

QPD C 2PE1,5 1X8-13 BK - Conductor connector

1414701

<https://www.phoenixcontact.com/us/products/1414701>



QPD H 2PE1,5 4X8-13 BK - H distributor

1414720

<https://www.phoenixcontact.com/us/products/1414720>



H distributor, product family: QPD, connection method: IDC connection, number of positions: 2+PE, 0.5 mm² ... 1.5 mm², 690 V, 17.5 A, PA, black, with four QUICKON nuts, coding: Coding profile, external cable diameter: 10 mm ... 13 mm, with a sealing bolt

QSS 22 - Socket wrench

1670206

<https://www.phoenixcontact.com/us/products/1670206>



Allen wrench, for loosening and fastening the QUICKON union nut, WAF 22 mm

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com