

QPD N 2PE1,5 4-9 BK - Nut

1415099

<https://www.phoenixcontact.com/pc/products/1415099>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Nut, product family: QPD, connection method: IDC connection, number of positions: 2+PE, 0.5 mm² ... 1.5 mm², 690 V, 17.5 A, PA, black, external cable diameter: 5 mm ... 7 mm and 7 mm ... 9.5 mm

Your advantages

- Innovative and time saving - QUICKON fast connection for time saving of up to 80 % for on-site connection
- Robust throughout: housing with IP68/IP69K and IK07 protection for a wide range of applications

Commercial data

Item number	1415099
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	BF6UCX
Catalog page	Page 472 (C-2-2019)
GTIN	4055626037639
Weight per piece (including packing)	18.8 g
Weight per piece (excluding packing)	17.7 g
Customs tariff number	85366990
Country of origin	PL

Technical data

Product properties

Product type	Installation pressure nut
Product family	QPD
Type	QPD 3x1,5
Number of positions	3
Connection profile	2+PE
Position marking	1, 2, PE
Number of connections	10

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated surge voltage (II/2)	8 kV
Rated surge voltage (III/2)	8 kV
Rated surge voltage (III/3)	8 kV
Rated current	17.5 A
rated voltage (II/2)	1000 V
rated voltage (III/2)	1000 V
Rated voltage (III/3)	690 V
Nominal voltage U_N	690 V AC
	690 V DC
Nominal current I_N	17.5 A

Connection data

Connection technology

Connection method On the field side	IDC connection
Frequency of connections between conductors of the same cross section	max. 10

Conductor connection

Conductor cross section flexibel	0.5 mm ² ... 1.5 mm ²
	0.5 mm ² ... 1.5 mm ²
Connection cross section AWG	20 ... 16
Tightening torque Union nut	8 Nm

Material specifications

Color	black (RAL 9005)
Material Housing	PA
Flammability rating according to UL 94	V0
Material wire insulation	PVC/PE/TPE/rubber

QPD N 2PE1,5 4-9 BK - Nut

1415099

<https://www.phoenixcontact.com/pc/products/1415099>



Contact carrier material	PA
--------------------------	----

Cable/line

Structure of individual litz in acc. with VDE 0295 / smallest wire diameter	VDE 0295 class 1 to 6/min. 0.15 mm
External cable diameter	5 mm ... 7 mm
	7 mm ... 9.5 mm
Wire diameter including insulation	1.6 mm ... 3 mm
Position marking	1, 2, PE
Material wire insulation	PVC/PE/TPE/rubber

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP66
	IP68 (2 m / 24 h)
	IP69K
Ambient temperature (operation)	-40 °C ... 100 °C
Temperature when conductor connected	-5 °C ... 50 °C
Ambient temperature (storage/transport)	-40 °C ... 80 °C

QPD N 2PE1,5 4-9 BK - Nut


1415099

<https://www.phoenixcontact.com/pc/products/1415099>



Drawings

Dimensional drawing



Dimensional drawing of the QPD nut 5x2,5

QPD N 2PE1,5 4-9 BK - Nut

1415099

<https://www.phoenixcontact.com/pc/products/1415099>



Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/1415099>



IECEE CB Scheme
Approval ID: DE1-65875



DNV GL
Approval ID: TAE00003J5



VDE Zeichengenehmigung
Approval ID: 40029149

 UL Listed Approval ID: E468743				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
Use group keine				
	600 V	8 A	-	- 16

 cUL Listed Approval ID: E468743				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
Use group keine				
	600 V	8 A	- 16	-

cULus Listed

QPD N 2PE1,5 4-9 BK - Nut

1415099

<https://www.phoenixcontact.com/pc/products/1415099>



Classifications

ECLASS

ECLASS-11.0	27440691
ECLASS-13.0	27440691
ECLASS-12.0	27440691

ETIM

ETIM 9.0	EC002863
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

QPD N 2PE1,5 4-9 BK - Nut

1415099

<https://www.phoenixcontact.com/pc/products/1415099>



Mandatory accessories

QPD W 2PE1,5 4-9 M20 0,5 BK - Panel feed-through

1414684

<https://www.phoenixcontact.com/pc/products/1414684>



Panel feed-through, product family: QPD, connection method: Single wires/ IDC connection, number of positions: 2+PE, M20, Pin, 0.5 mm² ... 1.5 mm², 690 V, 17.5 A, PA, black, with QUICKON nut, coding: Coding profile, external cable diameter: 5 mm ... 7 mm and 7 mm ... 9.5 mm, 1.5 mm², cable length: 0.5 m

QPD W 2PE1,5 4-9 M20 1,0 BK - Panel feed-through

1414685

<https://www.phoenixcontact.com/pc/products/1414685>



Panel feed-through, product family: QPD, connection method: Single wires/ IDC connection, number of positions: 2+PE, M20, Pin, 0.5 mm² ... 1.5 mm², 690 V, 17.5 A, PA, black, with QUICKON nut, coding: Coding profile, external cable diameter: 5 mm ... 7 mm and 7 mm ... 9.5 mm, 1.5 mm², cable length: 1 m

QPD N 2PE1,5 4-9 BK - Nut

1415099

<https://www.phoenixcontact.com/pc/products/1415099>



QPD W 2PE1,5 4-9 M20 FC BK - Panel feed-through

1414686

<https://www.phoenixcontact.com/pc/products/1414686>



Panel feed-through, product family: QPD, connection method: Spade connection (For slip-on sleeves according to DIN 46247-2)/ IDC connection, number of positions: 2+PE, M20, Pin, 0.5 mm² ... 1.5 mm², 690 V, 15 A, PA, black, with QUICKON nut, coding: Coding profile, external cable diameter: 5 mm ... 7 mm and 7 mm ... 9.5 mm, 1.5 mm²

QPD C 2PE1,5 1X4-9 BK - Conductor connector

1414699

<https://www.phoenixcontact.com/pc/products/1414699>



Conductor connector, product family: QPD, connection method: IDC connection, number of positions: 2+PE, 0.5 mm² ... 1.5 mm², 690 V, 17.5 A, PA, black, with one QUICKON nut, coding: Coding profile, external cable diameter: 5 mm ... 7 mm and 7 mm ... 9.5 mm

QPD N 2PE1,5 4-9 BK - Nut

1415099

<https://www.phoenixcontact.com/pc/products/1415099>



QPD C 2PE1,5 2X4-9 BK - Conductor connector

1414700

<https://www.phoenixcontact.com/pc/products/1414700>



Conductor connector, product family: QPD, connection method: IDC connection, number of positions: 2+PE, 0.5 mm² ... 1.5 mm², 690 V, 17.5 A, PA, black, With two QUICKON nuts, coding: Coding profile, external cable diameter: 5 mm ... 7 mm and 7 mm ... 9.5 mm

QPD P 2PE1,5 4-9 BK - Connector

1414705

<https://www.phoenixcontact.com/pc/products/1414705>



Connector, product family: QPD, connection method: IDC connection, number of positions: 2+PE, 0.5 mm² ... 1.5 mm², 690 V, 17.5 A, PA, black, with QUICKON nut, coding: Coding profile, external cable diameter: 5 mm ... 7 mm and 7 mm ... 9.5 mm

QPD N 2PE1,5 4-9 BK - Nut

1415099

<https://www.phoenixcontact.com/pc/products/1415099>



QPD T 2PE1,5 2X4-9 BK - T distributor

1414711

<https://www.phoenixcontact.com/pc/products/1414711>



T distributor, product family: QPD, connection method: IDC connection, number of positions: 2+PE, 0.5 mm² ... 1.5 mm², 690 V, 17.5 A, PA, black, With two QUICKON nuts, coding: Coding profile, external cable diameter: 5 mm ... 7 mm and 7 mm ... 9.5 mm

QPD T 2PE1,5 3X4-9 BK - T distributor

1414712

<https://www.phoenixcontact.com/pc/products/1414712>



T distributor, product family: QPD, connection method: IDC connection, number of positions: 2+PE, 0.5 mm² ... 1.5 mm², 690 V, 17.5 A, PA, black, With three QUICKON nuts, coding: Coding profile, external cable diameter: 5 mm ... 7 mm and 7 mm ... 9.5 mm

QPD N 2PE1,5 4-9 BK - Nut

1415099

<https://www.phoenixcontact.com/pc/products/1415099>



QPD H 2PE1,5 4X4-9 BK - H distributor

1414719

<https://www.phoenixcontact.com/pc/products/1414719>



H distributor, product family: QPD, connection method: IDC connection, number of positions: 2+PE, 0.5 mm² ... 1.5 mm², 690 V, 17.5 A, PA, black, with four QUICKON nuts, coding: Coding profile, external cable diameter: 5 mm ... 7 mm and 7 mm ... 9.5 mm, with a sealing bolt

QPD W 2PE1,5 M20 0,5 BK - Panel feed-through

1414690

<https://www.phoenixcontact.com/pc/products/1414690>



Panel feed-through, product family: QPD, connection method: Single wires (Welded-on), number of positions: 2+PE, M20, 0.5 mm² ... 1.5 mm², 690 V, 17.5 A, PA, black, without QUICKON nut, coding: Coding profile, 1.5 mm², wires cut flat at the end, cable length: 0.5 m

QPD N 2PE1,5 4-9 BK - Nut

1415099

<https://www.phoenixcontact.com/pc/products/1415099>



QPD W 2PE1,5 M20 1,0 BK - Panel feed-through

1414691

<https://www.phoenixcontact.com/pc/products/1414691>



Panel feed-through, product family: QPD, connection method: Single wires, number of positions: 2+PE, M20, 0.5 mm² ... 1.5 mm², 690 V, 17.5 A, PA, black, without QUICKON nut, coding: Coding profile, 1.5 mm², cable length: 1 m

QPD W 2PE1,5 M20 FC BK - Panel feed-through

1414692

<https://www.phoenixcontact.com/pc/products/1414692>



Panel feed-through, product family: QPD, connection method: Spade connection (For slip-on sleeves according to DIN 46247-2), number of positions: 2+PE, M20, 0.5 mm² ... 1.5 mm², 690 V, 15 A, PA, black, without QUICKON nut, coding: Coding profile, 1.5 mm²

QPD N 2PE1,5 4-9 BK - Nut

1415099

<https://www.phoenixcontact.com/pc/products/1415099>



QPD H 2PE1,5 BK - H distributor

1414721

<https://www.phoenixcontact.com/pc/products/1414721>



H distributor, product family: QPD, connection method: IDC connection/
QUICKON fast connection, number of positions: 2+PE, 0.5 mm² ... 1.5 mm², 690
V, 17.5 A, PA, black, without QUICKON nut, coding: Coding profile

Accessories

CP-QPD 3/4X1,5 - Coding profile

1414729

<https://www.phoenixcontact.com/pc/products/1414729>



Coding profile red, for pushing into the QUICKON dome and connector, can be
positioned in 90° steps.

QPD N 2PE1,5 4-9 BK - Nut

1415099

<https://www.phoenixcontact.com/pc/products/1415099>



SEALING PLUG 7X16 RD - Closing cap

1400255

<https://www.phoenixcontact.com/pc/products/1400255>

Closing cap, color: red



QSS 22 - Socket wrench

1670206

<https://www.phoenixcontact.com/pc/products/1670206>

Allen wrench, for loosening and fastening the QUICKON union nut, WAF 22 mm



Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com