


MBK 5/E BU - Mini feed-through terminal block



1415115

<https://www.phoenixcontact.com/us/products/1415115>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Mini feed-through terminal block, nom. voltage: 500 V, nominal current: 32 A, number of connections: 2, connection method: Screw connection, 1 level, cross section: 0.2 mm² - 4 mm², mounting type: NS 15, color: blue

Your advantages

- Space saving thanks to compact design and mounting option on a 15 mm DIN rail
- Clear arrangement thanks to marking of all terminal points
- Easy potential distribution thanks to standardized plug-in bridges

Commercial data

| | |
|--------------------------------------|--------------------|
| Item number | 1415115 |
| Packing unit | 1 pc |
| Minimum order quantity | 50 pc |
| Sales key | BE12 |
| Product key | BE1261 |
| Catalog page | Page 125 (CL-2002) |
| GTIN | 4017918021405 |
| Weight per piece (including packing) | 7.98 g |
| Weight per piece (excluding packing) | 7.45 g |
| Customs tariff number | 85369010 |
| Country of origin | PL |

MBK 5/E BU - Mini feed-through terminal block



1415115

<https://www.phoenixcontact.com/us/products/1415115>

Technical data

Product properties

| | |
|-----------------------|--------------------------|
| Product type | Miniature terminal block |
| Number of connections | 2 |
| Number of rows | 1 |

Insulation characteristics

| | |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution | 3 |

Electrical properties

| | |
|---|------|
| Rated surge voltage | 6 kV |
| Maximum power dissipation for nominal condition | 0 W |

Connection data

| | |
|---------------------------------|---|
| Number of connections per level | 2 |
|---------------------------------|---|

1 level

| | |
|---|---|
| Screw thread | M3 |
| Tightening torque | 0.6 ... 0.8 Nm |
| Stripping length | 8 mm |
| Internal cylindrical gage | A4 |
| Connection in acc. with standard | IEC 60947-7-1 |
| Conductor cross section rigid | 0.2 mm ² ... 4 mm ² |
| Cross section AWG | 24 ... 12 (converted acc. to IEC) |
| Conductor cross section flexible | 0.2 mm ² ... 4 mm ² |
| Conductor cross section, flexible [AWG] | 24 ... 12 (converted acc. to IEC) |
| Conductor cross-section flexible (ferrule without plastic sleeve) | 0.25 mm ² ... 4 mm ² |
| Flexible conductor cross section (ferrule with plastic sleeve) | 0.25 mm ² ... 2.5 mm ² |
| 2 conductors with same cross section, solid | 0.2 mm ² ... 1.5 mm ² |
| 2 conductors with same cross section, flexible | 0.2 mm ² ... 1.5 mm ² |
| 2 conductors with same cross section, flexible, with ferrule without plastic sleeve | 0.25 mm ² ... 1.5 mm ² |
| 2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve | 0.5 mm ² ... 2.5 mm ² |
| Nominal current | 32 A |
| Maximum load current | 32 A (with 4 mm ² conductor cross section) |
| Nominal voltage | 500 V |

Dimensions

| | |
|-----------------|--------|
| Width | 6.2 mm |
| End cover width | 1 mm |

Material specifications

MBK 5/E BU - Mini feed-through terminal block



1415115

<https://www.phoenixcontact.com/us/products/1415115>

| | |
|---|-------------|
| Color | blue |
| Flammability rating according to UL 94 | V0 |
| Insulating material group | I |
| Insulating material | PA |
| Static insulating material application in cold | -60 °C |
| Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) | 130 °C |
| Relative insulation material temperature index (Elec., UL 746 B) | 130 °C |
| Fire protection for rail vehicles (DIN EN 45545-2) R22 | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R23 | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R24 | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R26 | HL 1 - HL 3 |
| Calorimetric heat release NFPA 130 (ASTM E 1354) | 28 MJ/kg |
| Surface flammability NFPA 130 (ASTM E 162) | passed |
| Specific optical density of smoke NFPA 130 (ASTM E 662) | passed |
| Smoke gas toxicity NFPA 130 (SMP 800C) | passed |

Electrical tests

Surge voltage test

| | |
|-----------------------|-------------|
| Test voltage setpoint | 7.3 kV |
| Result | Test passed |

Temperature-rise test

| | |
|--|-------------------------------------|
| Requirement temperature-rise test | Increase in temperature \leq 45 K |
| Result | Test passed |
| Short-time withstand current 4 mm ² | 0.48 kA |
| Result | Test passed |

Power-frequency withstand voltage

| | |
|-----------------------|-------------|
| Test voltage setpoint | 1.89 kV |
| Result | Test passed |

Mechanical properties

Mechanical data

| | |
|-----------------|-----|
| Open side panel | Yes |
|-----------------|-----|

Mechanical tests

Mechanical strength

| | |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

Attachment on the carrier

| | |
|-------------------------|-------------|
| DIN rail/fixing support | NS 15 |
| Test force setpoint | 1 N |
| Result | Test passed |

MBK 5/E BU - Mini feed-through terminal block



1415115

<https://www.phoenixcontact.com/us/products/1415115>

Test for conductor damage and slackening

| | |
|--------------------------------|------------------------------|
| Rotation speed | 10 rpm |
| Revolutions | 135 |
| Conductor cross section/weight | 0.2 mm ² / 0.2 kg |
| | 4 mm ² / 0.9 kg |
| Result | Test passed |

Environmental and real-life conditions

Needle-flame test

| | |
|------------------|-------------|
| Time of exposure | 30 s |
| Result | Test passed |

Ambient conditions

| | |
|--|---|
| Ambient temperature (storage/transport) | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) |
| Ambient temperature (assembly) | -5 °C ... 70 °C |
| Ambient temperature (actuation) | -5 °C ... 70 °C |
| Permissible humidity (storage/transport) | 30 % ... 70 % |

Standards and regulations

| | |
|----------------------------------|---------------|
| Connection in acc. with standard | IEC 60947-7-1 |
|----------------------------------|---------------|

Mounting

| | |
|---------------|-------|
| Mounting type | NS 15 |
|---------------|-------|

MBK 5/E BU - Mini feed-through terminal block






1415115

<https://www.phoenixcontact.com/us/products/1415115>

Drawings

Circuit diagram



MBK 5/E BU - Mini feed-through terminal block



1415115

<https://www.phoenixcontact.com/us/products/1415115>

Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1415115>

DNV

Approval ID: TAE00001CT



EAC

Approval ID: RU C-DE.BL08.B.00534

MBK 5/E BU - Mini feed-through terminal block



1415115

<https://www.phoenixcontact.com/us/products/1415115>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27141120 |
| ECLASS-13.0 | 27250101 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC000897 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

MBK 5/E BU - Mini feed-through terminal block



1415115

<https://www.phoenixcontact.com/us/products/1415115>

Environmental product compliance


| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

MBK 5/E BU - Mini feed-through terminal block

1415115

<https://www.phoenixcontact.com/us/products/1415115>

Accessories

 Note: Applying some accessories below might limit this product.

IS-K 4 - Bridge bar isolator

1302338

<https://www.phoenixcontact.com/us/products/1302338>



Bridge bar isolator, color: gray


ISSBI 10- 6 - Bridge

0301505

<https://www.phoenixcontact.com/us/products/0301505>



Bridge, pitch: 6 mm, number of positions: 10, color: silver

 Max. current carrying capacity: 24 A

MBK 5/E BU - Mini feed-through terminal block



1415115

<https://www.phoenixcontact.com/us/products/1415115>

FBI 100- 6 - Fixed bridge

0201650

<https://www.phoenixcontact.com/us/products/0201650>



Fixed bridge, pitch: 6.2 mm, number of positions: 100, color: silver


FBI 10- 6 - Fixed bridge

0203250

<https://www.phoenixcontact.com/us/products/0203250>



Fixed bridge, pitch: 6.2 mm, number of positions: 10, color: silver

 Max. current carrying capacity: 34 A

MBK 5/E BU - Mini feed-through terminal block

1415115

<https://www.phoenixcontact.com/us/products/1415115>



FBI 20- 6 - Fixed bridge

0201867

<https://www.phoenixcontact.com/us/products/0201867>



Fixed bridge, pitch: 6.2 mm, number of positions: 20, color: silver


EB 3- 6 - Insertion bridge

0201142

<https://www.phoenixcontact.com/us/products/0201142>



Insertion bridge, pitch: 6.2 mm, number of positions: 3, color: gray

 Max. current carrying capacity: 32 A

MBK 5/E BU - Mini feed-through terminal block

1415115

<https://www.phoenixcontact.com/us/products/1415115>




EB 2- 6 - Insertion bridge

0201155

<https://www.phoenixcontact.com/us/products/0201155>

Insertion bridge, pitch: 6.2 mm, number of positions: 2, color: gray



 Max. current carrying capacity: 32 A


EB 10- 6 - Insertion bridge

0201139

<https://www.phoenixcontact.com/us/products/0201139>

Insertion bridge, pitch: 6.2 mm, number of positions: 10, color: gray



 Max. current carrying capacity: 32 A

MBK 5/E BU - Mini feed-through terminal block

1415115

<https://www.phoenixcontact.com/us/products/1415115>

SBRN 2-9 - Switching jumper

1415238

<https://www.phoenixcontact.com/us/products/1415238>



Switching bridge, 2-pos.

 Max. current carrying capacity: 24 A

SBRN 2-7 - Switching jumper

1413230

<https://www.phoenixcontact.com/us/products/1413230>



Switching jumper, pitch: 7 mm, number of positions: 2, color: silver

 Max. current carrying capacity: 24 A

MBK 5/E BU - Mini feed-through terminal block




1415115

<https://www.phoenixcontact.com/us/products/1415115>

D-MBK/E BU - End cover

1415102

<https://www.phoenixcontact.com/us/products/1415102>



End cover, width: 1 mm, height: 26.2 mm, color: blue

D-MBK/E - End cover

1415021

<https://www.phoenixcontact.com/us/products/1415021>



End cover, width: 1 mm, height: 26.2 mm, color: gray

MBK 5/E BU - Mini feed-through terminal block



1415115

<https://www.phoenixcontact.com/us/products/1415115>

FB-150 METER - Fixed bridge

0201595

<https://www.phoenixcontact.com/us/products/0201595>



Cross connection rail, for fixed bridging of identical inputs and outputs, made of Cu, nickel-plated, 1 m long

RPS - Reducing plug

0201647

<https://www.phoenixcontact.com/us/products/0201647>



Reducing plug, number of positions: 1, color: gray

MBK 5/E BU - Mini feed-through terminal block



1415115

<https://www.phoenixcontact.com/us/products/1415115>

TS-KK 3 - Separating plate

2770215

<https://www.phoenixcontact.com/us/products/2770215>



Separating plate, depth: 16 mm, width: 0.5 mm, height: 14 mm, color: gray

ATP-MBK - Partition plate

1413227

<https://www.phoenixcontact.com/us/products/1413227>



Partition plate, depth: 30.5 mm, width: 2.5 mm, height: 42.5 mm, color: gray

MBK 5/E BU - Mini feed-through terminal block

1415115

<https://www.phoenixcontact.com/us/products/1415115>



BN-ZB 6,2/WH CUS - Marker pin Zack strip

0824276

<https://www.phoenixcontact.com/us/products/0824276>



Marker pin Zack strip, can be ordered: Strip, white, labeled according to customer specifications, mounting type: plug in, for terminal block width: 6.2 mm, lettering field size: 4 x 4 mm

SF-SL 0,6X3,5-100 S-VDE - Screwdriver

1212587

<https://www.phoenixcontact.com/us/products/1212587>



Actuation tool, for ST terminal blocks, VDE insulated, with slimmer insulation integrated in the blade, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip

MBK 5/E BU - Mini feed-through terminal block

1415115

<https://www.phoenixcontact.com/us/products/1415115>



NS 15 UNPERF 2000MM VPE 10 - DIN rail, unperforated

1401695

<https://www.phoenixcontact.com/us/products/1401695>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

NS 15 PERF 2000MM VPE 10 - DIN rail perforated

1401682

<https://www.phoenixcontact.com/us/products/1401682>



DIN rail perforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

MBK 5/E BU - Mini feed-through terminal block

1415115

<https://www.phoenixcontact.com/us/products/1415115>



NS 15 AL PERF 2000MM VPE 10 - DIN rail perforated

1401763

<https://www.phoenixcontact.com/us/products/1401763>



DIN rail perforated, Pack of 10 (20 m), acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

NS 15 WH PERF 2000MM-VPE 10 - DIN rail perforated

1204096

<https://www.phoenixcontact.com/us/products/1204096>



DIN rail perforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

MBK 5/E BU - Mini feed-through terminal block




1415115

<https://www.phoenixcontact.com/us/products/1415115>

E/MBK - End bracket

1401637

<https://www.phoenixcontact.com/us/products/1401637>



End clamp, width: 6.2 mm, color: gray

E/MK - End bracket

1421633

<https://www.phoenixcontact.com/us/products/1421633>



End clamp, width: 6.2 mm, color: gray

MBK 5/E BU - Mini feed-through terminal block

1415115

<https://www.phoenixcontact.com/us/products/1415115>




E/MK 1 - End bracket

1421659

<https://www.phoenixcontact.com/us/products/1421659>

End clamp width: 6 mm, color: gray



PSBJ 3/13/4 - Test plug strip

0201304

<https://www.phoenixcontact.com/us/products/0201304>

Test plug strip, number of positions: 1, color: silver



MBK 5/E BU - Mini feed-through terminal block

1415115

<https://www.phoenixcontact.com/us/products/1415115>



PSB 3/10/4 - Test plug strip

0601292

<https://www.phoenixcontact.com/us/products/0601292>

Test plug strip, number of positions: 1, color: silver



Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com