## MC-35/37-MULTI-67-PVO-BK - Cable feed-through plates



1415241

https://www.phoenixcontact.com/us/products/1415241

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable feed-through plates, no. of conductors: 37, external cable diameter: 4x 6 mm ... 10 mm, 14x 8 mm ... 12 mm, 16x 10 mm ... 14 mm, 2x 12 mm ... 18 mm, 1x 17 mm ... 32 mm, material: galvanized sheet steel (Core), material: TPE-SEBS (external material), color: black, length: 222 mm, width: 92 mm, height: 29.5 mm

## Your advantages

· Oil-resistant according to UL 157

#### Commercial data

Item number	1415241
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF67
Product key	BF7CAX
Catalog page	Page 683 (C-2-2019)
GTIN	4055626039459
Weight per piece (including packing)	308.5 g
Weight per piece (excluding packing)	245 g
Customs tariff number	39269097
Country of origin	FI

# MC-35/37-MULTI-67-PVO-BK - Cable feed-through plates



1415241

https://www.phoenixcontact.com/us/products/1415241

## Technical data

#### Notes

General	incl. mounting screws
General	2 mm thick coated, galvanized sheet steel


## Product properties

Product type	Cable feed-through
No. of conductors	37

#### Connection data

External cable diameter	4x 6 mm 10 mm
Tightening torque	1.5 Nm 2 Nm (Mounting screws)

## Dimensions



## Material specifications

Color	black (RAL 9005)
Material interior	galvanized sheet steel
Material exterior	TPE-SEBS
Flammability rating according to UL 94	V0

#### Cable/line

External cable diameter 6-10 mm	4x 6 mm 10 mm
External cable diameter 8-12 mm	14x 8 mm 12 mm
External cable diameter 10-14 mm	16x 10 mm 14 mm
External cable diameter 12-18 mm	2x 12 mm 18 mm
External cable diameter 17-32 mm	1x 17 mm 32 mm

#### Environmental and real-life conditions

# MC-35/37-MULTI-67-PVO-BK - Cable feed-through plates



1415241

https://www.phoenixcontact.com/us/products/1415241

#### Ambient conditions

Degree of protection	IP66 (Minimum sheet thickness >= 2.5 mm)
	IP67 (Minimum sheet thickness >= 2.5 mm)
Ambient temperature (operation)	-40 °C 100 °C

## Mounting

Assembly instructions	M8 mounting screw, torque: 1.5 - 2.0 Nm, SW5 Allen key
	The mounting screws included should be used for assembly.
	Assembly steps:  1) Fix Multigates with the mounting screws provided (observe torque)  2) Make a hole in the membrane (with a screwdriver) or cut off the tip of the cone
	3) Guide the cable through the opening (from the outside). Withdraw the cable approximately 20 mm (to improve strain relief).

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com