

# SAC-4P-M12MS/ 1,5-PVC - Sensor/actuator cable



1415585

<https://www.phoenixcontact.com/us/products/1415585>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 4-position, PVC, black RAL 9005, Plug straight M12, coding: A, Wiring: unwired, on free cable end, cable length: 1.5 m

## Your advantages

- Easy and safe: 100 % electrically tested plug-in components

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 1415585             |
| Packing unit                         | 1 pc                |
| Minimum order quantity               | 1 pc                |
| Sales key                            | BF03                |
| Product key                          | BF1CCA              |
| Catalog page                         | Page 196 (C-2-2019) |
| GTIN                                 | 4055626049540       |
| Weight per piece (including packing) | 61.7 g              |
| Weight per piece (excluding packing) | 54.18 g             |
| Customs tariff number                | 85444290            |
| Country of origin                    | DE                  |

# SAC-4P-M12MS/ 1,5-PVC - Sensor/actuator cable



1415585

<https://www.phoenixcontact.com/us/products/1415585>

## Technical data

### Product properties

|                      |                       |
|----------------------|-----------------------|
| Product type         | Sensor/actuator cable |
| Number of positions  | 4                     |
| Application          | Standard              |
| No. of cable outlets | 1                     |
| Shielded             | no                    |
| Coding               | A                     |

### Insulation characteristics

|                      |    |
|----------------------|----|
| Overvoltage category | II |
| Degree of pollution  | 3  |

### Material specifications

|                                        |                                             |
|----------------------------------------|---------------------------------------------|
| Flammability rating according to UL 94 | HB                                          |
| Material of grip body                  | TPU, hardly inflammable, self-extinguishing |
| Contact material                       | CuSn                                        |
| Contact surface material               | Ni/Au                                       |
| Contact carrier material               | TPU GF                                      |
| Material for screw connection          | Zinc die-cast, nickel-plated                |

### Electrical properties

|                       |                            |
|-----------------------|----------------------------|
| Insulation resistance | $\geq 100 \text{ M}\Omega$ |
| Nominal voltage $U_N$ | 250 V AC                   |
|                       | 250 V DC                   |
| Nominal current $I_N$ | 4 A                        |
| Protective circuit    | unwired                    |

### Mechanical properties

#### Mechanical data

|                             |            |
|-----------------------------|------------|
| Insertion/withdrawal cycles | $\geq 100$ |
|-----------------------------|------------|

### Signaling

|                        |    |
|------------------------|----|
| Status display         | No |
| Status display present | No |

### Connection data

#### Conductor connection

|                   |        |
|-------------------|--------|
| Tightening torque | 0.4 Nm |
|-------------------|--------|

### Connector

#### Connection 1

# SAC-4P-M12MS/ 1,5-PVC - Sensor/actuator cable



1415585

<https://www.phoenixcontact.com/us/products/1415585>

|                     |                   |
|---------------------|-------------------|
| Type                | Plug straight M12 |
| Number of positions | 4                 |
| Coding type         | A                 |


## Connection 2

|      |                |
|------|----------------|
| Type | free cable end |
|------|----------------|

## Cable/line

|              |       |
|--------------|-------|
| Cable length | 1.5 m |
|--------------|-------|

## PVC black [PVC]

|                                               |                                                                                     |
|-----------------------------------------------|-------------------------------------------------------------------------------------|
| Dimensional drawing                           |  |
| Cable weight                                  | 40 kg/km                                                                            |
| UL AWM Style                                  | 2464 / 1729 (80°C/300 V)                                                            |
| Number of positions                           | 4                                                                                   |
| Shielded                                      | no                                                                                  |
| Cable type                                    | PVC black [PVC]                                                                     |
| Conductor structure signal line               | 19x 0.15 mm                                                                         |
| AWG signal line                               | 22                                                                                  |
| Conductor cross section                       | 4x 0.34 mm <sup>2</sup> (Signal line)                                               |
| Wire diameter incl. insulation                | 1.26 mm ±0.05 mm                                                                    |
| External cable diameter                       | 4.70 mm ±0.15 mm                                                                    |
| Outer sheath, material                        | PVC                                                                                 |
| External sheath, color                        | black RAL 9005                                                                      |
| Conductor material                            | Bare Cu litz wires                                                                  |
| Material wire insulation                      | PVC                                                                                 |
| Single wire, color                            | brown, white, blue, black                                                           |
| Thickness, insulation                         | ≥ 0.23 mm (Core insulation)                                                         |
| Thickness, outer sheath                       | ≥ 0.76 mm                                                                           |
| Overall twist                                 | 4 wires, twisted                                                                    |
| Max. conductor resistance                     | ≤ 57 Ω/km (at 20 °C)                                                                |
| Insulation resistance                         | ≥ 200 MΩ*km (at 20 °C)                                                              |
| Nominal voltage, cable                        | ≤ 300 V                                                                             |
| Test voltage                                  | ≥ 3000 V                                                                            |
| Minimum bending radius, fixed installation    | 5 x D                                                                               |
| Minimum bending radius, flexible installation | 10 x D                                                                              |
| Smallest bending radius, fixed installation   | 24 mm                                                                               |
| Smallest bending radius, movable installation | 47 mm                                                                               |

# SAC-4P-M12MS/ 1,5-PVC - Sensor/actuator cable



1415585

<https://www.phoenixcontact.com/us/products/1415585>

|                                 |                                                 |
|---------------------------------|-------------------------------------------------|
| Flame resistance                | As per UL-Style 2464                            |
| Resistance to oil               | according to DIN EN 60811-2-1, 168 h at 60 °C   |
| Ambient temperature (operation) | -25 °C ... 80 °C (cable, fixed installation)    |
|                                 | -10 °C ... 80 °C (Cable, flexible installation) |

## Environmental and real-life conditions

### Ambient conditions

|                                 |                                  |
|---------------------------------|----------------------------------|
| Degree of protection            | IP65                             |
|                                 | IP67                             |
|                                 | IP68                             |
| Ambient temperature (operation) | -25 °C ... 90 °C (Plug / socket) |


## Standards and regulations

### M12

|                          |                 |
|--------------------------|-----------------|
| Standard designation     | M12 connector   |
| Standards/specifications | IEC 61076-2-101 |

## Drawings

Schematic diagram



Pin assignment M12 plug, 4-pos., A-coded, view plug side

# SAC-4P-M12MS/ 1,5-PVC - Sensor/actuator cable



1415585


<https://www.phoenixcontact.com/us/products/1415585>

Dimensional drawing



Plug, M12 x 1, straight, shielded

Circuit diagram



# SAC-4P-M12MS/ 1,5-PVC - Sensor/actuator cable



1415585

<https://www.phoenixcontact.com/us/products/1415585>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1415585>

|  |                                                |                                |                   |                               |
|--|------------------------------------------------|--------------------------------|-------------------|-------------------------------|
|  | <b>UL Listed</b><br>Approval ID: FILE E 221474 |                                |                   |                               |
|  | Nominal voltage U <sub>N</sub>                 | Nominal current I <sub>N</sub> | Cross section AWG | Cross section mm <sup>2</sup> |
|  | 300 V                                          | 4 A                            | -                 | -                             |

|  |                                                 |                                |                   |                               |
|--|-------------------------------------------------|--------------------------------|-------------------|-------------------------------|
|  | <b>cUL Listed</b><br>Approval ID: FILE E 221474 |                                |                   |                               |
|  | Nominal voltage U <sub>N</sub>                  | Nominal current I <sub>N</sub> | Cross section AWG | Cross section mm <sup>2</sup> |
|  | 300 V                                           | 4 A                            | -                 | -                             |

|  |                                                      |  |  |  |
|--|------------------------------------------------------|--|--|--|
|  | <b>EAC-RoHS</b><br>Approval ID: RU D-DE.HB35.B.00387 |  |  |  |
|  |                                                      |  |  |  |

|                     |  |  |  |  |
|---------------------|--|--|--|--|
| <b>cULus Listed</b> |  |  |  |  |
|---------------------|--|--|--|--|

# SAC-4P-M12MS/ 1,5-PVC - Sensor/actuator cable



1415585

<https://www.phoenixcontact.com/us/products/1415585>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27060311 |
| ECLASS-12.0 | 27060311 |
| ECLASS-13.0 | 27060311 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC001855 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 26121600 |
|-------------|----------|

# SAC-4P-M12MS/ 1,5-PVC - Sensor/actuator cable



1415585

<https://www.phoenixcontact.com/us/products/1415585>

## Environmental product compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)