

1415736

<https://www.phoenixcontact.com/us/products/1415736>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 8-position, PVC, black RAL 9005, free cable end, on Socket angled M12, coding: A, cable length: 10 m

Your advantages

- Easy and safe: 100 % electrically tested plug-in components

Commercial data

Item number	1415736
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF03
Product key	BF1CFA
Catalog page	Page 209 (C-2-2019)
GTIN	4055626052533
Weight per piece (including packing)	519.6 g
Weight per piece (excluding packing)	500 g
Customs tariff number	85444290
Country of origin	PL

Technical data

Product properties

Product type	Sensor/actuator cable
Application	Standard
Number of positions	8
No. of cable outlets	1
Shielded	no
Coding	A

Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Material specifications

Flammability rating according to UL 94	HB
Seal material	NBR
Material of grip body	TPU, hardly inflammable, self-extinguishing
Contact material	CuZn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Material for screw connection	Zinc die-cast, nickel-plated

Electrical properties

Insulation resistance	$\geq 100 \text{ M}\Omega$
Nominal voltage U_N	30 V AC
	30 V DC
Nominal current I_N	2 A

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 100
-----------------------------	------------

Signaling

Status display	No
Status display present	No

Connector

Connection 1

Type	free cable end
------	----------------

Connection 2

Type	Socket angled M12
Number of positions	8

SAC-8P-10,0-PVC/M12FR - Sensor/actuator cable



1415736

<https://www.phoenixcontact.com/us/products/1415736>

Coding type	A
-------------	---

Cable/line

Cable length	10 m
--------------	------

PVC black [PVC]

Dimensional drawing		
Cable weight	54 kg/km	
UL AWM Style	2464 / 1729 (80°C/300 V)	
Number of positions	8	
Shielded	no	
Cable type	PVC black [PVC]	
Conductor structure signal line	14x 0.15 mm	
AWG signal line	24	
Conductor cross section	8x 0.25 mm ² (Signal line)	
Wire diameter incl. insulation	1.17 mm ±0.05 mm	
External cable diameter	5.90 mm ±0.2 mm	
Outer sheath, material	PVC	
External sheath, color	black RAL 9005	
Conductor material	Bare Cu litz wires	
Material wire insulation	PVC	
Single wire, color	white, brown, green, yellow, gray, pink, blue, red	
Thickness, insulation	≥ 0.23 mm	
Thickness, outer sheath	≥ 0.76 mm	
Overall twist	8 wires around filler to the core	
Max. conductor resistance	79 Ω/km (at 20 °C)	
Insulation resistance	≥ 200 MΩ*km (at 20 °C)	
Nominal voltage, cable	≤ 300 V AC	
Test voltage	≥ 3000 V AC	
Minimum bending radius, fixed installation	5 x D	
Minimum bending radius, flexible installation	10 x D	
Smallest bending radius, fixed installation	30 mm	
Smallest bending radius, movable installation	59 mm	
Flame resistance	as per VW-1 in accordance with UL 758	
Resistance to oil	in accordance with DIN EN 60811-2-1	
Ambient temperature (operation)	-25 °C ... 80 °C (cable, fixed installation)	
	-10 °C ... 80 °C (Cable, flexible installation)	

SAC-8P-10,0-PVC/M12FR - Sensor/actuator cable



1415736

<https://www.phoenixcontact.com/us/products/1415736>

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65
	IP67
	IP68
Ambient temperature (operation)	-25 °C ... 90 °C (Plug / socket)

Standards and regulations

Standard designation	M12 connector
Standards/specifications	IEC 61076-2-101

SAC-8P-10,0-PVC/M12FR - Sensor/actuator cable


1415736

<https://www.phoenixcontact.com/us/products/1415736>




Drawings

Circuit diagram




Dimensional drawing



M12 x 1 socket, angled

Schematic diagram



Pin assignment M12 socket, 8-pos., A-coded, view female side

SAC-8P-10,0-PVC/M12FR - Sensor/actuator cable



1415736

<https://www.phoenixcontact.com/us/products/1415736>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1415736>

	UL Listed Approval ID: FILE E 221474			
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	30 V	2 A	-	-

	cUL Listed Approval ID: FILE E 221474			
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	30 V	2 A	-	-

	EAC-RoHS Approval ID: RU D-DE.HB35.B.00387			

cULus Listed

SAC-8P-10,0-PVC/M12FR - Sensor/actuator cable



1415736

<https://www.phoenixcontact.com/us/products/1415736>

Classifications

ECLASS

ECLASS-11.0	27060311
ECLASS-12.0	27060311
ECLASS-13.0	27060311

ETIM

ETIM 9.0	EC001855
----------	----------

UNSPSC

UNSPSC 21.0	26121600
-------------	----------

SAC-8P-10,0-PVC/M12FR - Sensor/actuator cable



1415736

<https://www.phoenixcontact.com/us/products/1415736>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

SAC-8P-10,0-PVC/M12FR - Sensor/actuator cable



1415736

<https://www.phoenixcontact.com/us/products/1415736>

Accessories

WP-CTA POM 13,0 BK - Protective hose adapter

1422884

<https://www.phoenixcontact.com/us/products/1422884>



Protective hose adapter, for corrugated hoses with a nominal size of 13 (10 x 13), corrugated in parallel

WP-PA HF 13,0 BK - Protective hose

3240681

<https://www.phoenixcontact.com/us/products/3240681>



Protective hose, material: PA 6, UV-resistant: yes, flexible, degree of protection: IP68, color: black, flammability rating in acc. with UL 94: V0, inner diameter: 10 mm, Total length: 50 m

SAC-8P-10,0-PVC/M12FR - Sensor/actuator cable

1415736

<https://www.phoenixcontact.com/us/products/1415736>



WP-PA HF-HB 13,0 BK - Protective hose

3240839

<https://www.phoenixcontact.com/us/products/3240839>



Protective hose, material: PA 6, UV-resistant: yes, flexible, degree of protection: IP68, color: black, flammability rating in acc. with UL 94: HB, inner diameter: 10 mm, Total length: 50 m

PROT-M12 MS-PA-CHAIN - Screw plug

1430899

<https://www.phoenixcontact.com/us/products/1430899>

M12 sealing cap with fixing band, for sensor cables, for free M12 sockets



SAC-8P-10,0-PVC/M12FR - Sensor/actuator cable

1415736

<https://www.phoenixcontact.com/us/products/1415736>



SAC-M12-EXCLIP-F - Locking clip

1558991

<https://www.phoenixcontact.com/us/products/1558991>



Locking clip for the socket side of sensor/actuator cables with M12 connector and M12 connectors for assembly, for knurl diameter: 15 mm or for Allen key with a wrench size of 14 mm, prevents the disconnection of plug-in connections without tools

B-STIFT - Marker pen

1051993

<https://www.phoenixcontact.com/us/products/1051993>



Marker pen, for manual labeling of unprinted Zack strips, smear-proof and waterproof, line thickness 0.5 mm

SAC-8P-10,0-PVC/M12FR - Sensor/actuator cable



1415736

<https://www.phoenixcontact.com/us/products/1415736>

CUTFOX-S VDE - Diagonal cutter

1212207

<https://www.phoenixcontact.com/us/products/1212207>



Diagonal cutter for hard (piano wire) and soft wires, VDE 1000 V AC/1500 V DC tested

WIREFOX SAC-1 - Stripping tool

1212757

<https://www.phoenixcontact.com/us/products/1212757>



Stripping pliers, for halogen-free sensor/actuator cables (SAC cables), with PUR and PVC insulation, from Ø of 3.2 to 4.4 mm, any stripping length

SAC-8P-10,0-PVC/M12FR - Sensor/actuator cable



1415736

<https://www.phoenixcontact.com/us/products/1415736>

WIREFOX SAC - Stripping tool

1212623

<https://www.phoenixcontact.com/us/products/1212623>



Stripping pliers, for halogen-free sensor/actuator cables (SAC cables), with PUR and PVC insulation, from Ø of 4.4 to 7 mm, any stripping length

WIREFOX 10 - Stripping tool

1212150

<https://www.phoenixcontact.com/us/products/1212150>



Stripping tool, for cables and conductors from 0.02 - 10 mm², self-adjusting, stripping length of up to 18 mm, cutting capacity of up to 10 mm² stranded/1.5 mm² solid, replaceable stripping blade

SAC-8P-10,0-PVC/M12FR - Sensor/actuator cable



1415736

<https://www.phoenixcontact.com/us/products/1415736>

TSD 04 SAC - Torque screwdriver

1208429

<https://www.phoenixcontact.com/us/products/1208429>



Torque screwdriver, with preset torque of 0.4 Nm and 4 mm hexagonal drive for M12 connectors

TSD-M 1,2NM - Torque screwdriver

1212224

<https://www.phoenixcontact.com/us/products/1212224>



Torque screw driver, accuracy as per EN ISO 6789 standard, adjustable from 0.3 - 1.2 Nm

SAC-8P-10,0-PVC/M12FR - Sensor/actuator cable



1415736

<https://www.phoenixcontact.com/us/products/1415736>

TSD-M SAC-BIT ADAPTER - Adapter insert

1212600

<https://www.phoenixcontact.com/us/products/1212600>



Adapter bit for TSD-M...torque tools, E6.3-1/4" drive with 4 mm hexagon to accommodate SAC bits

SAC BIT M12-D15 - Tool

1208432

<https://www.phoenixcontact.com/us/products/1208432>



Nut for assembling sensor/actuator cables with M12 connector and M12 connectors for assembly, with a knurl diameter of 15 mm, for 4 mm hexagonal drive

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com