

# SAC-2P-10,0-547/MINFR - Power cable



1416519

<https://www.phoenixcontact.com/us/products/1416519>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Power cable, 2-position, PVC, yellow, free cable end, on Socket angled 7/8"-16UNF, coding: A, cable length: 10 m

## Your advantages

- Easy and safe: 100 % electrically tested plug-in components

## Commercial data

|                                      |                                |
|--------------------------------------|--------------------------------|
| Item number                          | 1416519                        |
| Packing unit                         | 1 pc                           |
| Minimum order quantity               | 1 pc                           |
| Note                                 | Made to order (non-returnable) |
| Sales key                            | BF14                           |
| Product key                          | BF1IMA                         |
| GTIN                                 | 4055626221106                  |
| Weight per piece (including packing) | 22.22 g                        |
| Weight per piece (excluding packing) | 22.22 g                        |
| Customs tariff number                | 85444290                       |
| Country of origin                    | MX                             |

# SAC-2P-10,0-547/MINFR - Power cable



1416519

<https://www.phoenixcontact.com/us/products/1416519>

## Technical data

### Product properties

|                      |                       |
|----------------------|-----------------------|
| Product type         | Sensor/actuator cable |
| Application          | Standard              |
| Number of positions  | 2                     |
| No. of cable outlets | 1                     |
| Shielded             | no                    |
| Coding               | A                     |

### Material specifications

|                                        |                   |
|----------------------------------------|-------------------|
| Flammability rating according to UL 94 | V0                |
| Material of grip body                  | PVC               |
| Contact material                       | CuZn              |
| Contact surface material               | Au                |
| Contact carrier material               | PVC               |
| Material for screw connection          | Anodized aluminum |

### Electrical properties

|                       |                            |
|-----------------------|----------------------------|
| Insulation resistance | $\geq 100 \text{ M}\Omega$ |
| Nominal voltage $U_N$ | 300 V AC                   |
|                       | 300 V DC                   |
| Nominal current $I_N$ | 13 A                       |

### Mechanical properties

#### Mechanical data

|                             |     |
|-----------------------------|-----|
| Insertion/withdrawal cycles | 100 |
|-----------------------------|-----|

### Signaling

|                        |    |
|------------------------|----|
| Status display         | no |
| Status display present | No |

### Connection data

#### Conductor connection

|                   |                         |
|-------------------|-------------------------|
| Tightening torque | 10 lb <sub>F</sub> ·in. |
|                   | 1.12 Nm                 |

### Connector

#### Connection 1

|      |                |
|------|----------------|
| Type | free cable end |
|------|----------------|

#### Connection 2

|      |                          |
|------|--------------------------|
| Type | Socket angled 7/8"-16UNF |
|------|--------------------------|

# SAC-2P-10,0-547/MINFR - Power cable



1416519

<https://www.phoenixcontact.com/us/products/1416519>

|                     |   |
|---------------------|---|
| Number of positions | 2 |
| Coding type         | A |

## Cable/line

|              |      |
|--------------|------|
| Cable length | 10 m |
|--------------|------|

### CMX-OUTDOOR-CMG [547]

|                                 |                                                  |
|---------------------------------|--------------------------------------------------|
| Number of positions             | 2                                                |
| Shielded                        | no                                               |
| Cable type                      | CMX-OUTDOOR-CMG [547]                            |
| Conductor cross section         | 2 x AWG 18                                       |
| External cable diameter         | 5.33 mm                                          |
| Outer sheath, material          | PVC                                              |
| External sheath, color          | yellow                                           |
| Conductor material              | Bare Cu litz wires                               |
| Single wire, color              | brown 1, blue 2                                  |
| Nominal voltage, cable          | 300 V                                            |
| Flame resistance                | UL 1581, FT4                                     |
| Other resistance                | UV resistant (720 h) (UL 2556)                   |
| Ambient temperature (operation) | -40 °C ... 105 °C (cable, fixed installation)    |
|                                 | -30 °C ... 105 °C (Cable, flexible installation) |

## Environmental and real-life conditions

### Ambient conditions

|                                 |                                                  |
|---------------------------------|--------------------------------------------------|
| Degree of protection            | IP68                                             |
| Ambient temperature (operation) | -20 °C ... 105 °C (Plug / socket)                |
|                                 | -20 °C ... 105 °C (Plug / socket)                |
|                                 | -40 °C ... 105 °C (cable, fixed installation)    |
|                                 | -30 °C ... 105 °C (Cable, flexible installation) |

# SAC-2P-10,0-547/MINFR - Power cable




1416519

<https://www.phoenixcontact.com/us/products/1416519>


## Drawings

Dimensional drawing



7/8"-16UNF socket, angled

Schematic diagram



Pin assignment, socket, 7/8"-16UNF, 2-pos., view of female side


# SAC-2P-10,0-547/MINFR - Power cable



1416519

<https://www.phoenixcontact.com/us/products/1416519>

Circuit diagram



# SAC-2P-10,0-547/MINFR - Power cable



1416519

<https://www.phoenixcontact.com/us/products/1416519>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27060311 |
| ECLASS-12.0 | 27060311 |
| ECLASS-13.0 | 27060311 |

### ETIM

|          |          |
|----------|----------|
| ETIM 8.0 | EC001855 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 31251501 |
|-------------|----------|

# SAC-2P-10,0-547/MINFR - Power cable



1416519

<https://www.phoenixcontact.com/us/products/1416519>

## Environmental product compliance

|                                         |                                                       |
|-----------------------------------------|-------------------------------------------------------|
| EU RoHS                                 |                                                       |
| Fulfills EU RoHS substance requirements | Not applicable, Not qualified for the European market |
| EU REACH SVHC                           |                                                       |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%                            |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)