

SAC-4P-MINMR/ 2,0-547/MINFR - Power cable



1416605

<https://www.phoenixcontact.com/us/products/1416605>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Power cable, 4-position, PVC, yellow, Plug angled 7/8"-16UNF, on Socket angled 7/8"-16UNF, cable length: 2 m

Your advantages

- Easy and safe: 100 % electrically tested plug-in components

Commercial data

Item number	1416605
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	BF14
Product key	BF1IMA
GTIN	4055626221564
Weight per piece (including packing)	22.22 g
Weight per piece (excluding packing)	22.22 g
Customs tariff number	85444290
Country of origin	MX

SAC-4P-MINMR/ 2,0-547/MINFR - Power cable



1416605

<https://www.phoenixcontact.com/us/products/1416605>

Technical data

Notes

Trade restriction

CE note

The products are offered exclusively for export outside the EU and the European Economic Area.

Product properties

Product type	Sensor/actuator cable
Application	Standard
Number of positions	4
No. of cable outlets	1
Shielded	no
Coding	A

Material specifications

Flammability rating according to UL 94	V0
Material of grip body	PVC
Contact material	CuZn
Contact surface material	Au
Contact carrier material	PVC
Material for screw connection	Anodized aluminum

Electrical properties

Insulation resistance	$\geq 100 \text{ M}\Omega$
Nominal voltage U_N	300 V AC
	300 V DC
Nominal current I_N	10 A

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	100
-----------------------------	-----

Signaling

Status display	no
Status display present	No

Connection data

Conductor connection

Tightening torque	10 lb _f -in.
	1.12 Nm

Connector

SAC-4P-MINMR/ 2,0-547/MINFR - Power cable



1416605

<https://www.phoenixcontact.com/us/products/1416605>

Connection 1

Type	Plug angled 7/8"-16UNF
Number of positions	4


Connection 2

Type	Socket angled 7/8"-16UNF
Number of positions	4

Cable/line

Cable length	2 m
--------------	-----

PVC AWG 18 yellow 105°C [547]

Dimensional drawing		
UL AWM Style	2517 (105 °C / 300 V)	
Number of positions	4	
Shielded	no	
Cable type	PVC AWG 18 yellow 105°C [547]	
Conductor structure signal line	41x 0.16 mm	
AWG signal line	18	
Wire diameter incl. insulation	1.7 mm ±0.03 mm	
External cable diameter	6.00 mm ±0.2 mm	
Outer sheath, material	PVC	
External sheath, color	yellow	
Conductor material	Tin-plated Cu litz wires	
Material wire insulation	PVC	
Single wire, color	brown, white, blue, black	
Overall twist	4 wires, twisted	
Nominal voltage, cable	300 V	
Minimum bending radius, fixed installation	8 x D	
Smallest bending radius, fixed installation	48 mm	
Flame resistance	FT4	
Special properties	C(UL) CMX OUTDOOR-CMG 105 °C	
	UL ITC/PLTC 105 °C	
	CSA AWM I/II A/B FT4 105 °C / 300 V	
Ambient temperature (operation)	-30 °C ... 105 °C (cable, fixed installation)	

Environmental and real-life conditions

SAC-4P-MINMR/ 2,0-547/MINFR - Power cable



1416605

<https://www.phoenixcontact.com/us/products/1416605>

Ambient conditions

Degree of protection	IP68
Ambient temperature (operation)	-20 °C ... 105 °C (Plug / socket)
	-20 °C ... 105 °C (Plug / socket)
	-40 °C ... 105 °C (cable, fixed installation)
	-30 °C ... 105 °C (Cable, flexible installation)

SAC-4P-MINMR/ 2,0-547/MINFR - Power cable




1416605


<https://www.phoenixcontact.com/us/products/1416605>

Drawings

Circuit diagram



Schematic diagram



Pin assignment, socket, 7/8"-16UNF, 4-pos., view of female side


SAC-4P-MINMR/ 2,0-547/MINFR - Power cable

1416605

<https://www.phoenixcontact.com/us/products/1416605>




Dimensional drawing



7/8"-16UNF socket, angled

Dimensional drawing



7/8"-16UNF plug, angled


SAC-4P-MINMR/ 2,0-547/MINFR - Power cable

1416605

<https://www.phoenixcontact.com/us/products/1416605>



Schematic diagram



Pin assignment, plug, 7/8"-16UNF, 4-pos., view of male side

SAC-4P-MINMR/ 2,0-547/MINFR - Power cable



1416605

<https://www.phoenixcontact.com/us/products/1416605>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1416605>



UL Listed
Approval ID: FILE E 221474



cUL Listed
Approval ID: FILE E 221474

cULus Listed

SAC-4P-MINMR/ 2,0-547/MINFR - Power cable



1416605

<https://www.phoenixcontact.com/us/products/1416605>

Classifications

ECLASS

ECLASS-11.0	27060311
ECLASS-12.0	27060311
ECLASS-13.0	27060311

ETIM

ETIM 9.0	EC001855
----------	----------

UNSPSC

UNSPSC 21.0	31251501
-------------	----------

SAC-4P-MINMR/ 2,0-547/MINFR - Power cable



1416605

<https://www.phoenixcontact.com/us/products/1416605>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com