

SAC-4P-MINMS/ 5,0-547 - Power cable



1416621

<https://www.phoenixcontact.com/ca/products/1416621>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Power cable, 4-position, Plug straight 7/8"-16UNF, on free cable end, cable length: 5 m

Your advantages

- Easy and safe: 100 % electrically tested plug-in components

Commercial data

Item number	1416621
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF21
Product key	BF1IMA
GTIN	4055626221663
Weight per piece (including packing)	22.22 g
Weight per piece (excluding packing)	22.22 g
Customs tariff number	85444290
Country of origin	MX

SAC-4P-MINMS/ 5,0-547 - Power cable



1416621

<https://www.phoenixcontact.com/ca/products/1416621>

Technical data

Notes

Trade restriction

CE note	The products are offered exclusively for export outside the EU and the European Economic Area.
---------	--

Product properties

Product type	Sensor/actuator cable
Number of positions	4
Application	Standard
No. of cable outlets	1
Shielded	no
Coding	A

Material specifications

Flammability rating according to UL 94	V0
Material of grip body	PVC
Contact material	CuZn
Contact surface material	Au
Contact carrier material	PVC
Material for screw connection	Anodized aluminum

Electrical properties

Contact resistance	$\leq 5 \text{ m}\Omega$
Insulation resistance	$\geq 100 \text{ M}\Omega$
Nominal voltage U_N	300 V AC
	300 V DC
Nominal current I_N	10 A
Protective circuit	unwired

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	100
-----------------------------	-----

Signaling

Status display	No
Status display present	No

Connection data

Conductor connection

Tightening torque	10 lb _f -in.
	1.12 Nm

SAC-4P-MINMS/ 5,0-547 - Power cable



1416621

<https://www.phoenixcontact.com/ca/products/1416621>

Connector

Connection 1

Type	Plug straight 7/8"-16UNF
------	--------------------------

Connection 2

Type	free cable end
------	----------------

Cable/line

Cable length	5 m
--------------	-----

CMX-OUTDOOR-CMG [547]

Number of positions	3
Shielded	no
Cable type	CMX-OUTDOOR-CMG [547]
Conductor cross section	4 x AWG 18
External cable diameter	5.7 mm
Outer sheath, material	PVC
External sheath, color	yellow
Conductor material	Bare Cu litz wires
Single wire, color	black 1, blue 2, grey 3, brown 4, white 5
Nominal voltage, cable	300 V
Flame resistance	UL 1581, FT4
Other resistance	UV resistant (720 h) (UL 2556)
Ambient temperature (operation)	-40 °C ... 105 °C (cable, fixed installation)
	-30 °C ... 105 °C (Cable, flexible installation)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP68
Ambient temperature (operation)	-20 °C ... 105 °C (Plug / socket)
	-20 °C ... 105 °C (Plug / socket)
	-40 °C ... 105 °C (cable, fixed installation)
	-30 °C ... 105 °C (Cable, flexible installation)

SAC-4P-MINMS/ 5,0-547 - Power cable




1416621


<https://www.phoenixcontact.com/ca/products/1416621>

Drawings

Circuit diagram



Schematic diagram



Pin assignment, plug, 7/8"-16UNF, 4-pos., view of male side


SAC-4P-MINMS/ 5,0-547 - Power cable



1416621

<https://www.phoenixcontact.com/ca/products/1416621>

Dimensional drawing



7/8"-16UNF plug, straight

SAC-4P-MINMS/ 5,0-547 - Power cable



1416621

<https://www.phoenixcontact.com/ca/products/1416621>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/ca/products/1416621>



UL Listed
Approval ID: FILE E 221474



cUL Listed
Approval ID: FILE E 221474

cULus Listed

SAC-4P-MINMS/ 5,0-547 - Power cable



1416621

<https://www.phoenixcontact.com/ca/products/1416621>

Classifications

ECLASS

ECLASS-11.0	27060311
ECLASS-12.0	27060311
ECLASS-13.0	27060311

UNSPSC

UNSPSC 21.0	31251501
-------------	----------

SAC-4P-MINMS/ 5,0-547 - Power cable



1416621

<https://www.phoenixcontact.com/ca/products/1416621>

Environmental product compliance

China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd
8240 Parkhill Drive
Milton, Ontario L9T 5V7
1-800-890-2820
cdinfo@phoenixcontact.ca