

1416805  
<https://www.phoenixcontact.com/us/products/1416805>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Power cable, 4-position, PVC, yellow, Plug angled 7/8"-16UNF, coding: A, on Socket straight 7/8"-16UNF, coding: A, cable length: 5 m

Your advantages

- Easy and safe: 100 % electrically tested plug-in components

Commercial data

|                                      |                                |
|--------------------------------------|--------------------------------|
| Item number                          | 1416805                        |
| Packing unit                         | 1 pc                           |
| Note                                 | Made to order (non-returnable) |
| Sales key                            | BF14                           |
| Product key                          | BF1IMB                         |
| GTIN                                 | 4055626223735                  |
| Weight per piece (including packing) | 22.22 g                        |
| Weight per piece (excluding packing) | 22.22 g                        |
| Customs tariff number                | 85444290                       |
| Country of origin                    | MX                             |

# SAC-4P-MINMR/ 5,0-U20/MINFS - Power cable



1416805

<https://www.phoenixcontact.com/us/products/1416805>

## Technical data

### Notes

#### Trade restriction

|         |                                                                                                |
|---------|------------------------------------------------------------------------------------------------|
| CE note | The products are offered exclusively for export outside the EU and the European Economic Area. |
|---------|------------------------------------------------------------------------------------------------|

### Product properties

|                      |                       |
|----------------------|-----------------------|
| Product type         | Sensor/actuator cable |
| Number of positions  | 4                     |
| Application          | Standard              |
| No. of cable outlets | 1                     |
| Shielded             | no                    |
| Coding               | A                     |

### Material specifications

|                                        |                   |
|----------------------------------------|-------------------|
| Flammability rating according to UL 94 | V0                |
| Material of grip body                  | PVC               |
| Contact material                       | CuZn              |
| Contact surface material               | Au                |
| Contact carrier material               | PVC               |
| Material for screw connection          | Anodized aluminum |

### Electrical properties

|                       |                            |
|-----------------------|----------------------------|
| Insulation resistance | $\geq 100 \text{ M}\Omega$ |
| Nominal voltage $U_N$ | 600 V AC                   |
|                       | 600 V DC                   |
| Nominal current $I_N$ | 10 A                       |
| Protective circuit    | unwired                    |

### Mechanical properties

#### Mechanical data

|                             |     |
|-----------------------------|-----|
| Insertion/withdrawal cycles | 100 |
|-----------------------------|-----|

### Signaling

|                        |    |
|------------------------|----|
| Status display         | No |
| Status display present | No |

### Connection data

#### Conductor connection

|                   |                         |
|-------------------|-------------------------|
| Tightening torque | 10 lb <sub>F</sub> ·in. |
|                   | 1.12 Nm                 |

# SAC-4P-MINMR/ 5,0-U20/MINFS - Power cable



1416805

<https://www.phoenixcontact.com/us/products/1416805>

## Connector

### Connection 1

|                     |                        |
|---------------------|------------------------|
| Type                | Plug angled 7/8"-16UNF |
| Number of positions | 4                      |
| Coding type         | A                      |

### Connection 2

|                     |                            |
|---------------------|----------------------------|
| Type                | Socket straight 7/8"-16UNF |
| Number of positions | 4                          |
| Coding type         | A                          |

## Cable/line

|              |     |
|--------------|-----|
| Cable length | 5 m |
|--------------|-----|

### Yellow, STOOW [U20]

|                                               |                                                  |
|-----------------------------------------------|--------------------------------------------------|
| Number of positions                           | 4                                                |
| Shielded                                      | no                                               |
| Cable type                                    | Yellow, STOOW [U20]                              |
| Conductor cross section                       | 4 x AWG 16                                       |
| External cable diameter                       | 10.70 mm                                         |
| Outer sheath, material                        | PVC                                              |
| External sheath, color                        | yellow                                           |
| Conductor material                            | Bare Cu litz wires                               |
| Single wire, color                            | black 1, white 2, red 3, green 4                 |
| Nominal voltage, cable                        | 600 V                                            |
| Minimum bending radius, fixed installation    | 4 x D                                            |
| Minimum bending radius, flexible installation | 12.5 x D                                         |
| Smallest bending radius, fixed installation   | 43 mm                                            |
| Smallest bending radius, movable installation | 134 mm                                           |
| Flame resistance                              | UL 1581, FT2                                     |
| Resistance to oil                             | Premium oil resistance (jacket and conductor)    |
| Other resistance                              | UV resistant (720 h) (UL 2556)                   |
| Ambient temperature (operation)               | -40 °C ... 105 °C (cable, fixed installation)    |
|                                               | -30 °C ... 105 °C (Cable, flexible installation) |

## Environmental and real-life conditions

### Ambient conditions

|                                 |                                                  |
|---------------------------------|--------------------------------------------------|
| Degree of protection            | IP68                                             |
| Ambient temperature (operation) | -20 °C ... 105 °C (Plug / socket)                |
|                                 | -40 °C ... 105 °C (cable, fixed installation)    |
|                                 | -30 °C ... 105 °C (Cable, flexible installation) |

# SAC-4P-MINMR/ 5,0-U20/MINFS - Power cable



1416805

<https://www.phoenixcontact.com/us/products/1416805>

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)