

HC-M-B10-MF-H - Module carrier frame



1417404

<https://www.phoenixcontact.com/il/products/1417404>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Module carrier frame, size: B10, type : for the sleeve side (A, B, C, ...), 4 mm² ... 6 mm², application: Module carrier frame



Commercial data

Item number	1417404
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	BF7ACD
Catalog page	Page 594 (C-2-2019)
GTIN	4055626112794
Weight per piece (including packing)	57 g
Weight per piece (excluding packing)	57 g
Customs tariff number	85389099
Country of origin	CN

HC-M-B10-MF-H - Module carrier frame



1417404

<https://www.phoenixcontact.com/il/products/1417404>

Technical data

Product properties

Type	B10
Product type	Module carrier frame
Application	Module carrier frame
Number of module slots	3
Type	for the sleeve side (A, B, C, ...)
Series	HC-M-B
	HC-M-02
	HC-M-03
	HC-M-03/04
	HC-M-04
	HC-M-05
	HC-M-06
	HC-M-08
	HC-M-08-GBIT
	HC-M-12
	HC-M-17
	HC-M-20
	HC-M-25
	HC-M-DSUB
	HC-M-EMV
	HC-M-HV
	HC-M-HS
	HC-M-00

Connection data

Conductor connection


Conductor cross section	4 mm² ... 6 mm² (for PE conductor - power side)
	1 mm² ... 2.5 mm² (for PE conductor – control side)
Connection cross section AWG	12 ... 10 (for PE conductor - power side)
	18 ... 14 (for PE conductor – control side)
Tightening torque	0.5 Nm ... 0.8 Nm (Mounting screws for mounting in the HEAVYCON housing)

Dimensions

HC-M-B10-MF-H - Module carrier frame



1417404
<https://www.phoenixcontact.com/il/products/1417404>

Dimensional drawing	
	
Width	34.5 mm
Height	36.2 mm
Length	64 mm

Material specifications

Contact carrier material	Die-cast zinc alloy
--------------------------	---------------------

Mechanical properties

Mechanical data	
Insertion/withdrawal cycles	≥ 500

Environmental and real-life conditions

Ambient conditions	
Ambient temperature (operation)	-40 °C ... 125 °C

Mounting

Assembly instructions	HC-MHR-PE16 (1636981) for PE connection extension to 16 mm².
	Use wire end protection for PE wires (PE connection screws without wire protection) for housings without lateral connectors, max. thread length of the screw connection 12 mm

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT Israel Ltd.
P.O.B. 1799 Industrial Park Hasharon
Quadima 60920
+972-9-8915700
info@phoenixcontact.co.il