

1417414

<https://www.phoenixcontact.com/no/products/1417414>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



H distributor, 5-position, Plug straight M12, coding: A, on Socket straight M12, coding: A and Socket straight M12, coding: A, Thread M12 not rotatable, Parallel distributor

Your advantages

- Safe use in the field, thanks to a high degree of protection
- Reliable signal transmission – 360° shielding in environments with electromagnetic interference

Commercial data

Item number	1417414
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	31BBFS
Product key	BF1GAC
Catalog page	Page 436 (C-2-2019)
GTIN	4046356525138
Weight per piece (including packing)	60.8 g
Weight per piece (excluding packing)	60 g
Customs tariff number	85366990
Country of origin	PL

SAC-5PH-M-F/2XF SH1 SCO - H distributor



1417414

<https://www.phoenixcontact.com/no/products/1417414>

Technical data

Product properties

Product type	H-distributor
Number of positions	5
No. of cable outlets	3
Shielded	yes
Coding	A
Thread type	M12

Insulation characteristics

Overvoltage category	II
Degree of pollution	3


Electrical properties

Insulation resistance	$\geq 100 \text{ M}\Omega$
Nominal voltage U_N	48 V AC
	60 V DC
Nominal current I_N	4 A

Signaling

Status display	No
Status display present	No

Dimensions

Dimensional drawing	
Width	39 mm
Height	16 mm
Length	58.8 mm
Center distance	21 mm

Material specifications

Flammability rating according to UL 94	V0
Seal material	NBR
Material of grip body	TPU, hardly inflammable, self-extinguishing
Contact material	CuZn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Material for screw connection	Zinc die-cast, nickel-plated

SAC-5PH-M-F/2XF SH1 SCO - H distributor



1417414

<https://www.phoenixcontact.com/no/products/1417414>

Connector

Connection 1

Type	Plug straight M12
Coding type	A

Connection 2

Type	Socket straight M12
Coding type	A

Connection 3

Type	Socket straight M12
Coding type	A

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 100
-----------------------------	-------

Environmental and real-life conditions

Ambient conditions


Degree of protection	IP65
	IP67
Ambient temperature (operation)	-25 °C ... 90 °C (Plug / socket)

Standards and regulations

Standard designation	M12 connector
Standards/specifications	IEC 61076-2-101


Drawings

Schematic diagram



Pin assignment M12 male connector, 5-pos., A-coded, male side

Circuit diagram




SAC-5PH-M-F/2XF SH1 SCO - H distributor

1417414


<https://www.phoenixcontact.com/no/products/1417414>

Schematic diagram



Pin assignment M12 socket, 5-pos., A-coded, socket side view

Dimensional drawing



H distributor dimensional drawing

SAC-5PH-M-F/2XF SH1 SCO - H distributor



1417414

<https://www.phoenixcontact.com/no/products/1417414>

Classifications

ECLASS

ECLASS-11.0	27440106
ECLASS-12.0	27440106
ECLASS-13.0	27440106

ETIM

ETIM 9.0	EC002925
----------	----------

UNSPSC

UNSPSC 21.0	31251500
-------------	----------

SAC-5PH-M-F/2XF SH1 SCO - H distributor



1417414

<https://www.phoenixcontact.com/no/products/1417414>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT AS
Strømsveien 344
N-1081 Oslo
+47 22 07 68 00
norge@phoenixcontact.com