

SACC-E-MINM-2CON-NPT12-U20/1,0 - Flush-type connector



1417768
<https://www.phoenixcontact.com/ca/products/1417768>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Flush-type connector, 2-position, Plug, straight, 7/8"-16UNF, on free cable end, Front mounting, with 1/2 inch-14 NPT mounting thread, Individual wires, cable length: 1 m, 1.50 mm², PVC litz wire

Commercial data

Item number	1417768
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF22
Product key	BF2ICA
GTIN	4055626341408
Weight per piece (including packing)	22.22 g
Weight per piece (excluding packing)	22.22 g
Customs tariff number	85444290
Country of origin	MX

SACC-E-MINM-2CON-NPT12-U20/1,0 - Flush-type connector



1417768

<https://www.phoenixcontact.com/ca/products/1417768>

Technical data

Notes

Trade restriction

CE note

The products are offered exclusively for export outside the EU and the European Economic Area.

Mounting

Mounting type

Front mounting, with 1/2 inch-14 NPT mounting thread

Product properties

Product type

Circular connectors (device side)

Number of positions

2

No. of cable outlets

1

Shielded

no

Insulation characteristics

Degree of pollution

3

Material specifications

Flammability rating according to UL 94

V-0

Housing surface material

Al anodized

Contact material

Copper alloy

Contact surface material

Au

Contact carrier material

PVC

Material for screw connection

Anodized aluminum

Electrical properties

Insulation resistance

$\geq 100 \text{ M}\Omega$

Nominal voltage U_N

600 V AC

600 V DC

Nominal current I_N

13 A

Connection data

Conductor connection

Connection method

Individual wires

Contact connection type

Pin

Conductor cross section

1.5 mm²

Tightening torque

10 lb_F·in.

1.12 Nm

Mechanical properties

Mechanical data

SACC-E-MINM-2CON-NPT12-U20/1,0 - Flush-type connector



1417768

<https://www.phoenixcontact.com/ca/products/1417768>

Insertion/withdrawal cycles	> 500
-----------------------------	-------

Connector

Connection 1

Head design	Plug
Head cable outlet	straight
Head thread type	7/8"-16UNF

Connection 2

Head design	free cable end
-------------	----------------

Cable/line

Cable length	1 m
Cable type	PVC litz wire
Wire diameter incl. insulation	2.6 mm
Single wire, color	white 1, black 2
Cable cross section	1.5 mm ²
Conductor structure signal line	26 x AWG 30
AWG signal line	16
Material wire insulation	PVC
Thickness, insulation	Core insulation

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP68
	IP68
Ambient temperature (operation)	-20 °C ... 80 °C (Plug)
	-20 °C ... 80 °C (cable, fixed installation)

Standards and regulations

Standard designation	7/8" connector
Standards/specifications	UL 2238
Note	Suitable for use in Class I, Division 2 Groups A, B, C, D hazardous locations according to ISA standard 12.12.01-2015, section 8.2 and 8.8.3

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd
8240 Parkhill Drive
Milton, Ontario L9T 5V7
1-800-890-2820
cdinfo@phoenixcontact.ca