


SAC-3P-15,0-961/M12FS VA - Bus system cable



1419085

<https://www.phoenixcontact.com/us/products/1419085>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Bus system cable, PROFIBUS PA (31.25 kbps), 3-position, PVC, blue RAL 5015, shielded (Plastic-coated aluminum foil with a drain wire), free cable end, on Socket straight M12, coding: A, cable length: 15 m, For Ex area with high-grade steel knurl

Commercial data

Item number	1419085
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	BF04
Product key	BF1CCG
Catalog page	Page 430 (C-2-2019)
GTIN	4046356541527
Weight per piece (including packing)	982.7 g
Weight per piece (excluding packing)	982.7 g
Customs tariff number	85444290
Country of origin	PL

SAC-3P-15,0-961/M12FS VA - Bus system cable



1419085

<https://www.phoenixcontact.com/us/products/1419085>

Technical data

Notes

General	For applications in circuits of intrinsic safety protection type "i". Electrical values following EN 60079-14.
---------	---

Product properties

Product type	Data cable preassembled
Application	Process technology
Sensor type	PROFIBUS PA
Number of positions	3
No. of cable outlets	1
Shielded	yes
Coding	B

Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Interfaces

Bus system	PROFIBUS PA
Signal type/category	PROFIBUS PA, 31.25 kbps

Signaling

Status display	No
Status display present	No

Electrical properties

Nominal voltage U_N	48 V AC
	60 V DC
Nominal current I_N	4 A
Transmission medium	Copper

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 100
-----------------------------	------------

Material specifications

Flammability rating according to UL 94	HB
Seal material	NBR

Connection data

Pin assignment

1 (Socket) OG (DATA+)

SAC-3P-15,0-961/M12FS VA - Bus system cable



1419085

<https://www.phoenixcontact.com/us/products/1419085>

Contact | Color (signal designation) | Contact (optional)

3 (Socket) | BU (DATA-)

4 (Socket) | SR (shield)

Connector

Connection 1

Type

free cable end

Connection 2

Type

free cable end


Cable/line

Cable length

15 m

Fieldbus FOUNDATION/PROFIBUS PA, blue [961]

Dimensional drawing



Cable weight

56.552 kg/km

Number of positions

2

Shielded

yes

Cable type

Fieldbus FOUNDATION/PROFIBUS PA, blue [961]

Conductor structure

2xAWG18/7 + 1xAWG20/7

Signal speed

0.66 c

Conductor structure signal line

7x 0.40 mm

AWG signal line

18

Conductor cross section

2x 0.75 mm² (Signal line)

1x 0.5 mm² (Drain wire)

Wire diameter incl. insulation

2.24 mm ±0.05 mm

External cable diameter

7.50 mm ±0.25 mm

Outer sheath, material

PVC

External sheath, color

blue RAL 5015

Conductor material

Tin-plated Cu litz wires

Material wire insulation

PO (Signal line)

Single wire, color

blue, orange

Thickness, insulation

0.50 mm

Thickness, outer sheath

1.00 mm

Twisted pairs

2 cores to the pair

Overall twist

One pair with one drain wire and fillers for core

Optical shield covering

100 %

SAC-3P-15,0-961/M12FS VA - Bus system cable



1419085

<https://www.phoenixcontact.com/us/products/1419085>

Max. conductor resistance	≤ 19.35 Ω/km (Signal line)
	26 Ω/km (shield)
Cable capacity	147 pF/m (at 1 kHz, core/shield)
	≤ 3.94 pF/m (capacitance unbalance)
Working capacitance	78 nF (at 1 kHz)
Cable impedance	100 Ω ±20 % (At 31.25 kHz)
Nominal voltage, cable	300 V
Smallest bending radius, fixed installation	75 mm
Tensile strength	260 N
Shield attenuation	3.00 dB/km (at 39 kHz)
Flame resistance	UL 1685 (CSA FT 4)
	UL 1685 (vertical tray)
	UL 1666 (riser)
Special properties	UL standards PLTC-ER and ITC
Ambient temperature (operation)	-40 °C ... 105 °C (cable, fixed installation)


Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65
	IP67
	IP68
	IP69K

Drawings

Schematic diagram



Pin assignment M12 socket, 3-pos., A-coded, view female side


SAC-3P-15,0-961/M12FS VA - Bus system cable



1419085

<https://www.phoenixcontact.com/us/products/1419085>

Dimensional drawing



M12 x 1 socket, straight

SAC-3P-15,0-961/M12FS VA - Bus system cable



1419085

<https://www.phoenixcontact.com/us/products/1419085>

Approvals

 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1419085>



EAC-RoHS

Approval ID: RU D-DE.HB35.B.00387



cULus Listed

Approval ID: E221474

SAC-3P-15,0-961/M12FS VA - Bus system cable



1419085

<https://www.phoenixcontact.com/us/products/1419085>

Classifications

ECLASS

ECLASS-11.0	27060307
ECLASS-12.0	27060307
ECLASS-13.0	27060307

ETIM

ETIM 9.0	EC001855
----------	----------

UNSPSC

UNSPSC 21.0	26121600
-------------	----------

SAC-3P-15,0-961/M12FS VA - Bus system cable



1419085

<https://www.phoenixcontact.com/us/products/1419085>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

SAC-3P-15,0-961/M12FS VA - Bus system cable



1419085

<https://www.phoenixcontact.com/us/products/1419085>

Accessories

WP-CTA POM 13,0 BK - Protective hose adapter

1422884

<https://www.phoenixcontact.com/us/products/1422884>



Protective hose adapter, for corrugated hoses with a nominal size of 13 (10 x 13), corrugated in parallel

WP-PA HF 13,0 BK - Protective hose

3240681

<https://www.phoenixcontact.com/us/products/3240681>



Protective hose, material: PA 6, UV-resistant: yes, flexible, degree of protection: IP68, color: black, flammability rating in acc. with UL 94: V0, inner diameter: 10 mm, Total length: 50 m

SAC-3P-15,0-961/M12FS VA - Bus system cable

1419085

<https://www.phoenixcontact.com/us/products/1419085>



WP-PA HF-HB 13,0 BK - Protective hose

3240839

<https://www.phoenixcontact.com/us/products/3240839>



Protective hose, material: PA 6, UV-resistant: yes, flexible, degree of protection: IP68, color: black, flammability rating in acc. with UL 94: HB, inner diameter: 10 mm, Total length: 50 m

SACC-M12FS-4QO SH PBPA - Data connector

1413934

<https://www.phoenixcontact.com/us/products/1413934>



Data connector, PROFIBUS (31.25 kbps), 2-position, halogen-free, shielded, Socket straight M12, coding: A, Insulation displacement connection, knurl material: Zinc die-cast, nickel-plated, external cable diameter 5 mm ... 9.7 mm

SAC-3P-15,0-961/M12FS VA - Bus system cable



1419085

<https://www.phoenixcontact.com/us/products/1419085>

SACC-M12MS-4QO SH PBPA - Data connector

1413933

<https://www.phoenixcontact.com/us/products/1413933>



Data connector, PROFIBUS (31.25 kbps), 2-position, halogen-free, shielded, Plug straight M12, coding: A, Insulation displacement connection, knurl material: Zinc die-cast, nickel-plated, external cable diameter 5 mm ... 9.7 mm

TSD 04 SAC - Torque screwdriver

1208429

<https://www.phoenixcontact.com/us/products/1208429>



Torque screwdriver, with preset torque of 0.4 Nm and 4 mm hexagonal drive for M12 connectors

SAC-3P-15,0-961/M12FS VA - Bus system cable



1419085

<https://www.phoenixcontact.com/us/products/1419085>

TSD-M 1,2NM - Torque screwdriver

1212224

<https://www.phoenixcontact.com/us/products/1212224>



Torque screw driver, accuracy as per EN ISO 6789 standard, adjustable from 0.3 - 1.2 Nm

TSD-M SAC-BIT ADAPTER - Adapter insert

1212600

<https://www.phoenixcontact.com/us/products/1212600>



Adapter bit for TSD-M...torque tools, E6.3-1/4" drive with 4 mm hexagon to accommodate SAC bits

SAC-3P-15,0-961/M12FS VA - Bus system cable

1419085

<https://www.phoenixcontact.com/us/products/1419085>



SAC BIT M12-W14 - Tool

1212513

<https://www.phoenixcontact.com/us/products/1212513>



Nut for assembling sensor/actuator cables with M12 connector and M12 connectors for assembly, with a hexagonal knurl wrench size of 14 mm, with 4 mm hexagonal drive

CUTFOX 12 - Cable-cutting tool

1212128

<https://www.phoenixcontact.com/us/products/1212128>



Cable cutter, for copper and aluminum up to 12 mm diameter (up to 35 mm²)

SAC-3P-15,0-961/M12FS VA - Bus system cable



1419085

<https://www.phoenixcontact.com/us/products/1419085>

CUTFOX-S VDE - Diagonal cutter

1212207

<https://www.phoenixcontact.com/us/products/1212207>



Diagonal cutter for hard (piano wire) and soft wires, VDE 1000 V AC/1500 V DC tested

VS-CABLE-STRIP-VARIO - Stripping tool

1657407

<https://www.phoenixcontact.com/us/products/1657407>

Stripping tool, for the multi-level stripping of shielded cables



SAC-3P-15,0-961/M12FS VA - Bus system cable



1419085

<https://www.phoenixcontact.com/us/products/1419085>

MICROFOX-SP-1 - Diagonal cutter

1212487

<https://www.phoenixcontact.com/us/products/1212487>



Electronic diagonal cutter, tapered head, without chamfer, with opening spring, non-reflective phosphate-treated surface, punched version

WIREFOX 4 - Stripping tool

1212156

<https://www.phoenixcontact.com/us/products/1212156>



Stripping tool, for cables and conductors (especially for rubber and silicone insulations) from 0.1 - 4 mm², self-adjusting, stripping length of up to 18 mm, cutting capacity of up to 10 mm² stranded/1.5 mm² solid, replaceable stripping blade

SAC-3P-15,0-961/M12FS VA - Bus system cable



1419085

<https://www.phoenixcontact.com/us/products/1419085>

WIREFOX-E 4 - Stripping tool

1212704

<https://www.phoenixcontact.com/us/products/1212704>



Stripping tool, for cables and conductors (especially for rubber and silicone insulations) from 0.1 - 4 mm², self-adjusting, stripping length of up to 18 mm, cutting capacity of up to 10 mm² stranded/1.5 mm² solid, replaceable stripping blade

WIREFOX 10 - Stripping tool

1212150

<https://www.phoenixcontact.com/us/products/1212150>



Stripping tool, for cables and conductors from 0.02 - 10 mm², self-adjusting, stripping length of up to 18 mm, cutting capacity of up to 10 mm² stranded/1.5 mm² solid, replaceable stripping blade

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com