1419244

https://www.phoenixcontact.com/us/products/1419244

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Coupling housings D7, with single locking latch, material: Die-cast aluminum, salt water resistant, protective cover material: PA, cable outlets: 1, straight, 1x M25, height: 60.5 mm, cable gland: none, protective cover: yes, Standard, for socket inserts

Commercial data

Item number	1419244
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF56
Product key	BF7APF
Catalog page	Page 517 (C-2-2019)
GTIN	4055626159751
Weight per piece (including packing)	44.3 g
Weight per piece (excluding packing)	44.2 g
Customs tariff number	85389099
Country of origin	CN

1419244

https://www.phoenixcontact.com/us/products/1419244



Technical data

Notes

General	for contact inserts HC-A03, A04, D07, D08, Q02, Q03, Q04, Q05, Q07, Q12
Product properties	
Product type	Housing with locking latch
Housing type	Coupling housings
Product family	HC-STA-D07
Application	Standard
Туре	D7
No. of cable outlets	1
Type of the screw connection	1x M25
Protective cover	yes
Shielded	no
Cable outlet	straight
Pg screw connection	none

Dimensions

Dimensional drawing	
Width	34.2 mm
Height	60.5 mm
Length	24.2 mm

Material specifications

Flammability rating according to UL 94	V0 (Interlock)
	V0 (Protective cover)
Housing material	Die-cast aluminum, salt water resistant
Housing surface material	uncoated
Material, protective cover	PA
Locking latch material	PA

Mechanical properties

Mechanical data		
Type of the screw connection	1x M25	
Locking type	Latch	

Environmental and real-life conditions



1419244

https://www.phoenixcontact.com/us/products/1419244

Ambient conditions

Degree of protection	IP66
	IP67
Impact strength	IK06
Ambient temperature (operation)	-40 °C 125 °C




1419244

https://www.phoenixcontact.com/us/products/1419244

Drawings

Dimensional drawing



Dimensional drawing



https://www.phoenixcontact.com/us/products/1419244



Approvals

🌣 To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1419244

DNV	
Approval ID: TAE0	J00037S
EAC Approval ID: F	
	RU C-DE.BL08.B.00511
CUL Reco	ognized
Approval ID:	: E255026
UL Recog	gnized
Approval ID:	E255026
cULus Recog	nized
Ū	



https://www.phoenixcontact.com/us/products/1419244



Classifications

ECLASS

ECLASS-11.0	27440202
ECLASS-12.0	27440202
ECLASS-13.0	27440202

ETIM

	ETIM 9.0	EC000437	
UN	UNSPSC		
	UNSPSC 21.0	31261500	

1419244

https://www.phoenixcontact.com/us/products/1419244

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions	
China RoHS		
Environment friendly use period (EFUP)	EFUP-E	
	No hazardous substances above the limits	
EU REACH SVHC		
REACH candidate substance (CAS No.)	No substance above 0.1 wt%	



1419244

https://www.phoenixcontact.com/us/products/1419244



Accessories

G-INS-M25-M68N-NNES-S - Cable gland

1411165

https://www.phoenixcontact.com/us/products/1411165



Cable gland, material for screw connection: Brass, nickel-plated, application: Standard, external cable diameter 11 mm ... 17 mm, shielding: no, connecting thread: M25 x 1.5, color: silver, with O-ring

G-INSEC-M25-S68N-NCRS-S - Cable gland

1411190

https://www.phoenixcontact.com/us/products/1411190



Cable gland, material for screw connection: Brass, nickel-plated, application: EMC, external cable diameter 11 mm ... 16 mm, shielding: yes, connecting thread: M25 x 1.5, color: silver, with O-ring

1419244

https://www.phoenixcontact.com/us/products/1419244



G-INS-M25-M68N-PNES-GY - Cable gland

1411126

https://www.phoenixcontact.com/us/products/1411126



Cable gland, material for screw connection: PA, application: Standard, external cable diameter 11 mm ... 17 mm, shielding: no, connecting thread: M25 x 1.5, color: silver-grey RAL 7001

G-INS-M25-M68N-PNES-BK - Cable gland

1411134 https://www.phoenixcontact.com/us/products/1411134



Cable gland, material for screw connection: PA, application: Standard, external cable diameter 11 mm ... 17 mm, shielding: no, connecting thread: M25 x 1.5, color: jet black RAL 9005

1419244

https://www.phoenixcontact.com/us/products/1419244



US-EMLP (20X9) CUS - Plastic label

0830085

https://www.phoenixcontact.com/us/products/0830085

Plastic label, can be ordered: by card, white, labeled according to customer specifications, mounting type: adhesive, lettering field size: 20 x 9 mm, Number of individual labels: 75



HC-D07-SL-PLBK - Housing brackets

1424440 https://www.phoenixcontact.com/us/products/1424440



Replacement latch for HC-D7 housing

1419244

https://www.phoenixcontact.com/us/products/1419244

CONTACT

HC-STA-D07-BCLFS-PLR-BK - Protective cover

1419270

https://www.phoenixcontact.com/us/products/1419270



Protective cover D7, for single locking latch, material: PA, protective cover material: PA, height: 29.4 mm, seal: yes, Standard, with lanyard, for socket inserts

HC-STA-D07-BCLFS-PL-BK - Protective cover

1419271 https://www.phoenixcontact.com/us/products/1419271



Protective cover D7, for single locking latch, material: PA, protective cover material: PA, height: 29.4 mm, seal: no, Standard, with lanyard, for pin inserts

1419244

https://www.phoenixcontact.com/us/products/1419244

PHŒNIX CONTACT

HC-STA-D07-BCSFS-PLR-BK - Protective cover

1419272

https://www.phoenixcontact.com/us/products/1419272



Protective cover D7, for single locking latch, material: PA, protective cover material: PA, height: 30 mm, seal: yes, Standard, with lanyard, for socket inserts

HC-STA-D07-BCSFS-PL-BK - Protective cover

1419273 https://www.phoenixcontact.com/us/products/1419273



Protective cover D7, for single locking latch, material: PA, protective cover material: PA, height: 30 mm, seal: no, Standard, with lanyard, for pin inserts



https://www.phoenixcontact.com/us/products/1419244

PHŒNIX CONTACT

WP-G HF IP66 M25 BK - Screw connection

3240899

https://www.phoenixcontact.com/us/products/3240899

Cable gland, metric thread, IP66 protection, straight



WP-G HF IP69K M25 BK - Screw connection

3240885 https://www.phoenixcontact.com/us/products/3240885



Cable gland, metric thread, IP68/69k protection, straight



https://www.phoenixcontact.com/us/products/1419244

PHŒNIX CONTACT

WP-GA HF IP66 M25 BK - Screw connection

3240927

https://www.phoenixcontact.com/us/products/3240927

Cable gland, metric thread, IP66 protection, angled



WP-GA HF IP69K M25 BK - Screw connection

3240913 https://www.phoenixcontact.com/us/products/3240913

Cable gland, metric thread, IP68/69k protection, angled





https://www.phoenixcontact.com/us/products/1419244



WP-GR HF IP66 M25 BK - Screw connection

3240955

https://www.phoenixcontact.com/us/products/3240955

Cable gland, metric thread, IP66 protection, with strain relief



WP-GR HF IP69K M25 BK - Screw connection

3240941 https://www.phoenixcontact.com/us/products/3240941



Cable gland, metric thread, IP68/69k protection, with strain relief



https://www.phoenixcontact.com/us/products/1419244

WP-G PP HF M25 - Screw connection

3240999

https://www.phoenixcontact.com/us/products/3240999



Cable gland made from PP with metric thread, IP65 protection

WP-GT PP HF M25 - Screw connection

3241013 https://www.phoenixcontact.com/us/products/3241013



Cable gland made from PP with metric thread, rotatable, IP54 protection



https://www.phoenixcontact.com/us/products/1419244



WP-G BRASS IP40 M25 - Screw connection

3241048

https://www.phoenixcontact.com/us/products/3241048



Cable gland made from brass with metric thread, IP40 protection

WP-GT BRASS M25 - Screw connection

3241034 https://www.phoenixcontact.com/us/products/3241034



Cable gland made from brass with metric thread, rotatable, IP40 protection



https://www.phoenixcontact.com/us/products/1419244



WP-G BRASS IP65 M25 - Screw connection

3241062

https://www.phoenixcontact.com/us/products/3241062

Cable gland made from brass with metric thread, IP65 protection



Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com