

1419246

https://www.phoenixcontact.com/us/products/1419246

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Coupling housings D7, with single locking latch, material: Die-cast aluminum, salt water resistant, protective cover material: PA, cable outlets: 1, straight, 1x M20, height: 60.5 mm, cable gland: none, protective cover: yes, Standard, for pin inserts

Commercial data

Item number	1419246
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF56
Product key	BF7APF
Catalog page	Page 517 (C-2-2019)
GTIN	4055626159775
Weight per piece (including packing)	45 g
Weight per piece (excluding packing)	45 g
Customs tariff number	85389099
Country of origin	CN



1419246

https://www.phoenixcontact.com/us/products/1419246

Technical data

Notes

General	for contact inserts HC-A03, A04, D07, D08, Q02, Q03, Q04, Q05,
	Q07, Q12

Product properties

Product type	Housing with locking latch
Housing type	Coupling housings
Product family	HC-STA-D07
Application	Standard
Туре	D7
No. of cable outlets	1
Type of the screw connection	1x M20
Protective cover	yes
Shielded	no
Cable outlet	straight
Pg screw connection	none

Dimensions

Dimensional drawing	342
Width	34.2 mm
Height	60.5 mm
Length	24.2 mm

Material specifications

Flammability rating according to UL 94	V0 (Interlock)
	V0 (Protective cover)
Housing material	Die-cast aluminum, salt water resistant
Housing surface material	uncoated
Material, protective cover	PA
Locking latch material	PA

Mechanical properties

Mechanical data

Type of the screw connection	1x M20
Locking type	Latch

Environmental and real-life conditions



1419246

https://www.phoenixcontact.com/us/products/1419246

Ambient conditions

Degree of protection	IP66
	IP67
Impact strength	IK06
Ambient temperature (operation)	-40 °C 125 °C




1419246

https://www.phoenixcontact.com/us/products/1419246

Drawings

Dimensional drawing



Dimensional drawing



1419246

https://www.phoenixcontact.com/us/products/1419246

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1419246

DNV

Approval ID: TAE000037S



EAC

Approval ID: RU C-DE.BL08.B.00511



cUL RecognizedApproval ID: E255026





UL Recognized
Approval ID: E255026

cULus Recognized



1419246

https://www.phoenixcontact.com/us/products/1419246

Classifications

ECLASS

	ECLASS-11.0	27440202
	ECLASS-12.0	27440202
	ECLASS-13.0	27440202
ETIM		
	ETIM 9.0	EC000437
UNSPSC		
	UNSPSC 21.0	31261500



1419246

https://www.phoenixcontact.com/us/products/1419246

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%



1419246

https://www.phoenixcontact.com/us/products/1419246

Accessories

G-INS-M20-S68N-NNES-S - Cable gland

1411163

https://www.phoenixcontact.com/us/products/1411163



Cable gland, material for screw connection: Brass, nickel-plated, application: Standard, external cable diameter 6 mm ... 12 mm, shielding: no, connecting thread: M20 x 1.5, color: silver, with O-ring

G-INSEC-M20-S68N-NCRS-S - Cable gland

1411189

https://www.phoenixcontact.com/us/products/1411189



Cable gland, material for screw connection: Brass, nickel-plated, application: EMC, external cable diameter 9 mm \dots 13 mm, shielding: yes, connecting thread: M20 x 1.5, color: silver, with O-ring



1419246

https://www.phoenixcontact.com/us/products/1419246

G-INS-M20-S68N-PNES-GY - Cable gland

1411125

https://www.phoenixcontact.com/us/products/1411125



Cable gland, material for screw connection: PA, application: Standard, external cable diameter 6 mm \dots 12 mm, shielding: no, connecting thread: M20 x 1.5, color: silver-grey RAL 7001

G-INS-M20-S68N-PNES-BK - Cable gland

1411133

https://www.phoenixcontact.com/us/products/1411133



Cable gland, material for screw connection: PA, application: Standard, external cable diameter 6 mm \dots 12 mm, shielding: no, connecting thread: M20 x 1.5, color: jet black RAL 9005



1419246

https://www.phoenixcontact.com/us/products/1419246

US-EMLP (20X9) CUS - Plastic label

0830085

https://www.phoenixcontact.com/us/products/0830085

Plastic label, can be ordered: by card, white, labeled according to customer specifications, mounting type: adhesive, lettering field size: 20 x 9 mm, Number of individual labels: 75



HC-D07-SL-PLBK - Housing brackets

1424440

https://www.phoenixcontact.com/us/products/1424440

Replacement latch for HC-D7 housing





1419246

https://www.phoenixcontact.com/us/products/1419246

HC-STA-D07-BCLFS-PLR-BK - Protective cover

1419270

https://www.phoenixcontact.com/us/products/1419270



Protective cover D7, for single locking latch, material: PA, protective cover material: PA, height: 29.4 mm, seal: yes, Standard, with lanyard, for socket inserts

HC-STA-D07-BCLFS-PL-BK - Protective cover

1419271

https://www.phoenixcontact.com/us/products/1419271

Protective cover D7, for single locking latch, material: PA, protective cover material: PA, height: 29.4 mm, seal: no, Standard, with lanyard, for pin inserts





1419246

https://www.phoenixcontact.com/us/products/1419246

HC-STA-D07-BCSFS-PLR-BK - Protective cover

1419272

https://www.phoenixcontact.com/us/products/1419272



Protective cover D7, for single locking latch, material: PA, protective cover material: PA, height: 30 mm, seal: yes, Standard, with lanyard, for socket inserts

HC-STA-D07-BCSFS-PL-BK - Protective cover

1419273

https://www.phoenixcontact.com/us/products/1419273



Protective cover D7, for single locking latch, material: PA, protective cover material: PA, height: 30 mm, seal: no, Standard, with lanyard, for pin inserts



1419246

https://www.phoenixcontact.com/us/products/1419246

WP-G HF IP66 M20 BK - Screw connection

3240898

https://www.phoenixcontact.com/us/products/3240898



Cable gland, metric thread, IP66 protection, straight

WP-G HF IP69K M20 BK - Screw connection

3240884

https://www.phoenixcontact.com/us/products/3240884



Cable gland, metric thread, IP68/69k protection, straight



1419246

https://www.phoenixcontact.com/us/products/1419246

WP-GA HF IP66 M20 BK - Screw connection

3240926

https://www.phoenixcontact.com/us/products/3240926

Cable gland, metric thread, IP66 protection, angled



WP-GA HF IP69K M20 BK - Screw connection

3240912

https://www.phoenixcontact.com/us/products/3240912

Cable gland, metric thread, IP68/69k protection, angled





1419246

https://www.phoenixcontact.com/us/products/1419246

WP-GR HF IP66 M20 BK - Screw connection

3240954

https://www.phoenixcontact.com/us/products/3240954



Cable gland, metric thread, IP66 protection, with strain relief

WP-GR HF IP69K M20 BK - Screw connection

3240940

https://www.phoenixcontact.com/us/products/3240940



Cable gland, metric thread, IP68/69k protection, with strain relief



1419246

https://www.phoenixcontact.com/us/products/1419246

WP-G PP HF M20 - Screw connection

3240998

https://www.phoenixcontact.com/us/products/3240998



Cable gland made from PP with metric thread, IP65 protection

WP-GT PP HF M20 - Screw connection

3241012

https://www.phoenixcontact.com/us/products/3241012



Cable gland made from PP with metric thread, rotatable, IP54 protection



1419246

https://www.phoenixcontact.com/us/products/1419246

WP-G BRASS IP40 M20 - Screw connection

3241047

https://www.phoenixcontact.com/us/products/3241047



Cable gland made from brass with metric thread, IP40 protection

WP-GT BRASS M20 - Screw connection

3241033

https://www.phoenixcontact.com/us/products/3241033



Cable gland made from brass with metric thread, rotatable, IP40 protection



1419246

https://www.phoenixcontact.com/us/products/1419246

WP-G BRASS IP65 M20 - Screw connection

3241061

https://www.phoenixcontact.com/us/products/3241061



Cable gland made from brass with metric thread, IP65 protection

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com