

1419248

https://www.phoenixcontact.com/us/products/1419248

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Coupling housings D7, with single locking latch, material: Die-cast aluminum, salt water resistant, protective cover material: PA, cable outlets: 1, straight, 1x Pg11, height: 60.5 mm, cable gland: none, protective cover: yes, Standard, for pin inserts

Commercial data

Item number	1419248
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF56
Product key	BF7APF
Catalog page	Page 517 (C-2-2019)
GTIN	4055626159799
Weight per piece (including packing)	46.1 g
Weight per piece (excluding packing)	46.07 g
Customs tariff number	85389099
Country of origin	CN



1419248

https://www.phoenixcontact.com/us/products/1419248

Technical data

Notes

General	for contact inserts HC-A03, A04, D07, D08, Q02, Q03, Q04, Q05,
	Q07, Q12

Product properties

Product type	Housing with locking latch
Housing type	Coupling housings
Product family	HC-STA-D07
Application	Standard
Туре	D7
No. of cable outlets	1
Type of the screw connection	1x Pg11
Protective cover	yes
Shielded	no
Cable outlet	straight
Pg screw connection	none

Dimensions

Dimensional drawing	34.2
Width	34.2 mm
Height	60.5 mm
Length	24.2 mm

Material specifications

Flammability rating according to UL 94	V0 (Interlock)
	V0 (Protective cover)
Housing material	Die-cast aluminum, salt water resistant
Housing surface material	uncoated
Material, protective cover	PA
Locking latch material	PA

Mechanical properties

Mechanical data

Type of the screw connection	1x Pg11
Locking type	Latch

Environmental and real-life conditions



1419248

https://www.phoenixcontact.com/us/products/1419248

Ambient conditions

Degree of protection	IP66
	IP67
Impact strength	IK06
Ambient temperature (operation)	-40 °C 125 °C




1419248

https://www.phoenixcontact.com/us/products/1419248

Drawings

Dimensional drawing



Dimensional drawing



1419248

https://www.phoenixcontact.com/us/products/1419248

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1419248

DNV

Approval ID: TAE000037S



EAC

Approval ID: RU C-DE.BL08.B.00511



Al

cUL RecognizedApproval ID: E255026



UL Recognized
Approval ID: E255026

cULus Recognized



1419248

https://www.phoenixcontact.com/us/products/1419248

Classifications

ECLASS

	ECLASS-11.0	27440202
	ECLASS-12.0	27440202
	ECLASS-13.0	27440202
ETIM		
	ETIM 9.0	EC000437
۱U	NSPSC	
	UNSPSC 21.0	31261500



1419248

https://www.phoenixcontact.com/us/products/1419248

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)

No substance above 0.1 wt%



1419248

https://www.phoenixcontact.com/us/products/1419248

Accessories

G-INS-PG11-S68N-NNES-S - Cable gland

1411172

https://www.phoenixcontact.com/us/products/1411172



Cable gland, material for screw connection: Brass, nickel-plated, application: Standard, external cable diameter 5 mm ... 10 mm, shielding: no, connecting thread: Pg11, color: silver, with O-ring

G-INSEC-PG11-S68N-NNES-S - Cable gland

1411197

https://www.phoenixcontact.com/us/products/1411197



Cable gland, material for screw connection: Brass, nickel-plated, application: EMC, external cable diameter 5 mm ... 10 mm, shielding: yes, connecting thread: Pg11, color: silver, with O-ring



1419248

https://www.phoenixcontact.com/us/products/1419248

G-INS-PG11-S68N-PNES-GY - Cable gland

1411142

https://www.phoenixcontact.com/us/products/1411142



Cable gland, material for screw connection: PA, application: Standard, external cable diameter 5 mm \dots 10 mm, shielding: no, connecting thread: Pg11, color: silver-grey RAL 7001

G-INS-PG11-M68N-PNES-BK - Cable gland

1424497

https://www.phoenixcontact.com/us/products/1424497



Cable gland, material for screw connection: PA, application: Standard, external cable diameter 5 mm ... 10 mm, shielding: no, connecting thread: Pg11, color: jet black RAL 9005



1419248

https://www.phoenixcontact.com/us/products/1419248

US-EMLP (20X9) CUS - Plastic label

0830085

https://www.phoenixcontact.com/us/products/0830085

Plastic label, can be ordered: by card, white, labeled according to customer specifications, mounting type: adhesive, lettering field size: 20 x 9 mm, Number of individual labels: 75



HC-D07-SL-PLBK - Housing brackets

1424440

https://www.phoenixcontact.com/us/products/1424440

Replacement latch for HC-D7 housing





1419248

https://www.phoenixcontact.com/us/products/1419248

HC-STA-D07-BCLFS-PLR-BK - Protective cover

1419270

https://www.phoenixcontact.com/us/products/1419270



Protective cover D7, for single locking latch, material: PA, protective cover material: PA, height: 29.4 mm, seal: yes, Standard, with lanyard, for socket inserts

HC-STA-D07-BCLFS-PL-BK - Protective cover

1419271

https://www.phoenixcontact.com/us/products/1419271

Protective cover D7, for single locking latch, material: PA, protective cover material: PA, height: 29.4 mm, seal: no, Standard, with lanyard, for pin inserts





1419248

https://www.phoenixcontact.com/us/products/1419248

HC-STA-D07-BCSFS-PLR-BK - Protective cover

1419272

https://www.phoenixcontact.com/us/products/1419272



Protective cover D7, for single locking latch, material: PA, protective cover material: PA, height: 30 mm, seal: yes, Standard, with lanyard, for socket inserts

HC-STA-D07-BCSFS-PL-BK - Protective cover

1419273

https://www.phoenixcontact.com/us/products/1419273



Protective cover D7, for single locking latch, material: PA, protective cover material: PA, height: 30 mm, seal: no, Standard, with lanyard, for pin inserts



1419248

https://www.phoenixcontact.com/us/products/1419248

WP-G HF IP66 PG11 BK - Screw connection

3240890

https://www.phoenixcontact.com/us/products/3240890



Cable gland, Pg thread, IP66 protection, straight

WP-G HF IP69K PG11 BK - Screw connection

3240876

https://www.phoenixcontact.com/us/products/3240876



Cable gland, Pg thread, IP68/69k protection, straight



1419248

https://www.phoenixcontact.com/us/products/1419248

WP-GA HF IP66 PG11 BK - Screw connection

3240918

https://www.phoenixcontact.com/us/products/3240918

Cable gland, Pg thread, IP66 protection, angled



WP-GR HF IP66 PG11 BK - Screw connection

3240946

https://www.phoenixcontact.com/us/products/3240946

Cable gland, Pg thread, IP66 protection, with strain relief





1419248

https://www.phoenixcontact.com/us/products/1419248

WP-GR HF IP69K PG11 BK - Screw connection

3240932

https://www.phoenixcontact.com/us/products/3240932



Cable gland, Pg thread, IP68/69k protection, with strain relief

WP-G PP HF PG11 - Screw connection

3240990

https://www.phoenixcontact.com/us/products/3240990



Cable gland made from PP with Pg thread, IP65 protection



1419248

https://www.phoenixcontact.com/us/products/1419248

WP-GT PP HF PG11 - Screw connection

3241004

https://www.phoenixcontact.com/us/products/3241004



Cable gland made from PP with Pg thread, rotatable, IP54 protection

WP-G BRASS IP40 PG11 - Screw connection

3241039

https://www.phoenixcontact.com/us/products/3241039



Cable gland made from brass with Pg thread, IP40 protection



1419248

https://www.phoenixcontact.com/us/products/1419248

WP-GT BRASS PG11 - Screw connection

3241025

https://www.phoenixcontact.com/us/products/3241025



Cable gland made from brass with Pg thread, rotatable, IP40 protection

WP-G BRASS IP65 PG11 - Screw connection

3241053

https://www.phoenixcontact.com/us/products/3241053



Cable gland made from brass with Pg thread, IP65 protection

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com