

1419257

https://www.phoenixcontact.com/us/products/1419257

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sleeve housing D7, for single locking latch, material: PA, cable outlets: 1, lateral, M20, height: 54.5 mm, cable gland: with, Standard

Commercial data

Item number	1419257
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF56
Product key	BF7APD
Catalog page	Page 514 (C-2-2019)
GTIN	4055626159980
Weight per piece (including packing)	26.5 g
Weight per piece (excluding packing)	26 g
Customs tariff number	85389099
Country of origin	CN



1419257

https://www.phoenixcontact.com/us/products/1419257

Technical data

Notes

General	for contact inserts HC-A03, A04, D07, D08, Q02, Q03, Q04, Q05,
	Q07, Q12

Product properties

Product type	Housing with locking latch
Housing type	Sleeve housing
Product family	HC-STA-D07
Application	Standard
Туре	D7
No. of cable outlets	1
Type of the screw connection	M20
Shielded	no
Cable outlet	lateral
Pg screw connection	with

Dimensions

Dimensional drawing	22.4 25.5 25.5 255.5 34.2
Width	26.5 mm
Height	54.5 mm
Length	26.5 mm

Material specifications

Flammability rating according to UL 94	V0 (Housing)
Housing material	PA
Locking latch material	PA

Mechanical properties

Mechanical data

Type of the screw connection	M20
Locking type	Pin

Cable/line

External cable diameter Cable 1	4 mm 10 mm

Connection data

External cable diameter	4 mm 10 mm



1419257

https://www.phoenixcontact.com/us/products/1419257

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP66
Impact strength	IK06
Ambient temperature (operation)	-40 °C 125 °C





1419257

https://www.phoenixcontact.com/us/products/1419257

Drawings

Dimensional drawing





Dimensional drawing



1419257

https://www.phoenixcontact.com/us/products/1419257

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1419257

DNV

Approval ID: TAE000037S



EAC

Approval ID: RU C-DE.BL08.B.00511



1419257

https://www.phoenixcontact.com/us/products/1419257

Classifications

UNSPSC 21.0

ECLASS

ECLASS-11.0	27440202
ECLASS-12.0	27440202
ECLASS-13.0	27440202
ETIM	
ETIM 9.0	EC000437
UNSPSC	

31261500



1419257

https://www.phoenixcontact.com/us/products/1419257

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%



1419257


https://www.phoenixcontact.com/us/products/1419257

Accessories

US-EMLP (20X9) CUS - Plastic label

0830085

https://www.phoenixcontact.com/us/products/0830085





US-EMLP-HA (20X9) - Plastic label

0830989

https://www.phoenixcontact.com/us/products/0830989



Plastic label, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: adhesive, lettering field size: 20×9 mm, Number of individual labels: 70



1419257

https://www.phoenixcontact.com/us/products/1419257

HC-STA-D07-HCLWS-PLR-BK - Protective cover

1419274

https://www.phoenixcontact.com/us/products/1419274



Protective cover D7, with single locking latch, material: PA, protective cover material: PA, height: 30 mm, seal: yes, Standard, with lanyard, for socket inserts

HC-STA-D07-HCLWS-PL-BK - Protective cover

1419275

https://www.phoenixcontact.com/us/products/1419275



Protective cover D7, with single locking latch, material: PA, protective cover material: PA, height: 28 mm, seal: no, Standard, with lanyard, for pin inserts

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com