

HC-EVO-B16-HLWD-PLBK - Housing



1420933

<https://www.phoenixcontact.com/sg/products/1420933>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sleeve housing B16, with double locking latch, material: PA, cable outlets: 1, straight/lateral, height: 63 mm, cable gland: none, Standard

Your advantages

- Flexible cable outlet direction, lateral or straight
- Lower costs than metal version
- Low weight
- Lower risk of condensation

Commercial data

Item number	1420933
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	*****
Product key	BF7APL
Catalog page	Page 626 (C-2-2019)
GTIN	4055626249322
Weight per piece (including packing)	113.9 g
Weight per piece (excluding packing)	111.21 g
Customs tariff number	85389099
Country of origin	PL

HC-EVO-B16-HLWD-PLBK - Housing



1420933

<https://www.phoenixcontact.com/sg/products/1420933>

Technical data

Notes

General	For contact inserts HC-B16, BB32, D40, DD72, HS6, HV6, M, K
---------	---


Product properties

Product type	Housing with locking latch
Housing type	Sleeve housing
Product family	HC-EVO-B
Application	Standard
Type	B16
No. of cable outlets	1
Type	Low design
Shielded	no
Cable outlet	straight
Pg screw connection	none

Data management status

Article revision	01
------------------	----

Dimensions

Dimensional drawing	
Width	43.8 mm
Height	63 mm
Length	93.5 mm

Material specifications

Flammability rating according to UL 94	V0 (Housing) V0 (Interlock)
Housing material	PA
Locking latch material	PA

Mechanical properties

Mechanical data

Locking type	Latch
--------------	-------

Mounting

Assembly note	The sleeve base housing must be supplemented with the EVO screw connection. The EVO screw connection is available in four sizes. It facilitates the creation of a straight or a side cable outlet.
---------------	--

HC-EVO-B16-HLWD-PLBK - Housing



1420933

<https://www.phoenixcontact.com/sg/products/1420933>

	The EVO screw connection is mounted with the aid of, for example, a pipe wrench
--	---

Environmental and real-life conditions

Ambient conditions	
Degree of protection	IP66
Enclosure rating (NEMA)	12 (UL 50e)
Impact strength	IK09
Ambient temperature (operation)	-40 °C ... 125 °C

HC-EVO-B16-HLWD-PLBK - Housing



1420933

<https://www.phoenixcontact.com/sg/products/1420933>



Drawings

Dimensional drawing



Dimensional drawing

HC-EVO-B16-HLWD-PLBK - Housing



1420933

<https://www.phoenixcontact.com/sg/products/1420933>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/sg/products/1420933>



DNV
Approval ID: TAE000037S



cUL Recognized
Approval ID: E255026



UL Recognized
Approval ID: E255026



EAC
Approval ID: RU C-DE.AI30.B.01102



EAC
Approval ID: RU C-DE.BL08.B.00511

cULus Recognized

HC-EVO-B16-HLWD-PLBK - Housing



1420933

<https://www.phoenixcontact.com/sg/products/1420933>

Classifications

ECLASS

ECLASS-11.0	27440202
ECLASS-12.0	27440202
ECLASS-13.0	27440202

ETIM

ETIM 9.0	EC000437
----------	----------

UNSPSC

UNSPSC 21.0	31261500
-------------	----------

HC-EVO-B16-HLWD-PLBK - Housing



1420933

<https://www.phoenixcontact.com/sg/products/1420933>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT SEA Pte. Ltd.
105 Eunos Avenue 3, #04-00
Singapore 409836
+65 6228 4900
marketing@phoenixcontact.com.sg