

# HC-EVO-B24-SHWD-2SSM32-PLRBK - Housing



1421370

<https://www.phoenixcontact.com/pc/products/1421370>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Box mounting bases B24, with double locking latch, material: PA, cable outlets: 2, lateral, 2x M32, height: 84 mm, cable gland: none, Standard, including 2x reducing adapter

## Your advantages

- Flexible cable outlet direction, lateral or straight
- Lower costs than metal version
- Low weight
- Lower risk of condensation

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 1421370             |
| Packing unit                         | 1 pc                |
| Minimum order quantity               | 1 pc                |
| Product key                          | BF7APL              |
| Catalog page                         | Page 636 (C-2-2019) |
| GTIN                                 | 4055626264967       |
| Weight per piece (including packing) | 240.1 g             |
| Weight per piece (excluding packing) | 242.9 g             |
| Customs tariff number                | 85389099            |
| Country of origin                    | PL                  |

# HC-EVO-B24-SHWD-2SSM32-PLRBK - Housing



1421370

<https://www.phoenixcontact.com/pc/products/1421370>

## Technical data

### Notes

|         |                                                                            |
|---------|----------------------------------------------------------------------------|
| General | For contact inserts HC-B24, BB46, D64, DD108, M, K, HV10-I-PT, HV 10-E...C |
|---------|----------------------------------------------------------------------------|


### Product properties

|                              |                            |
|------------------------------|----------------------------|
| Product type                 | Housing with locking latch |
| Housing type                 | Box mounting bases         |
| Product family               | HC-EVO-B                   |
| Application                  | Standard                   |
| Type                         | B24                        |
| No. of cable outlets         | 2                          |
| Type of the screw connection | 2x M32                     |
| Type                         | Tall design                |
| Cable outlet                 | lateral                    |
| Pg screw connection          | none                       |

### Data management status

|                  |    |
|------------------|----|
| Article revision | 02 |
|------------------|----|

### Dimensions

|                     |                                                                                      |
|---------------------|--------------------------------------------------------------------------------------|
| Dimensional drawing |  |
| Width               | 57 mm                                                                                |
| Height              | 84 mm                                                                                |
| Length              | 144 mm                                                                               |
| Hole diameter       | 5.5 mm                                                                               |

### Material specifications

|                                        |                                |
|----------------------------------------|--------------------------------|
| Flammability rating according to UL 94 | V0 (Housing)<br>V0 (Interlock) |
| Seal material                          | NBR                            |
| Housing material                       | PA                             |
| Locking latch material                 | PA                             |

### Mechanical properties

#### Mechanical data

|                              |        |
|------------------------------|--------|
| Type of the screw connection | 2x M32 |
| Locking type                 | Latch  |

# HC-EVO-B24-SHWD-2SSM32-PLRBK - Housing



1421370

<https://www.phoenixcontact.com/pc/products/1421370>

## Connection data

|                   |                                                                     |
|-------------------|---------------------------------------------------------------------|
| Tightening torque | 2 Nm ... 3 Nm (for M5 mounting screws on the surface-mount housing) |
|-------------------|---------------------------------------------------------------------|

## Mounting

|               |                                                                                                         |
|---------------|---------------------------------------------------------------------------------------------------------|
| Assembly note | Two plastic reductions M40 to M32 are provided                                                          |
|               | One of the two openings for the screw connections is sealed but can be broken open using a screwdriver. |

## Environmental and real-life conditions

|                                 |                   |
|---------------------------------|-------------------|
| Ambient conditions              |                   |
| Degree of protection            | IP66              |
| Enclosure rating (NEMA)         | 12 (UL 50e)       |
| Impact strength                 | IK09              |
| Ambient temperature (operation) | -40 °C ... 125 °C |


# HC-EVO-B24-SHWD-2SSM32-PLRBK - Housing

1421370

<https://www.phoenixcontact.com/pc/products/1421370>



## Drawings



Dimensional drawing

# HC-EVO-B24-SHWD-2SSM32-PLRBK - Housing



1421370

<https://www.phoenixcontact.com/pc/products/1421370>

## Approvals

 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/1421370>

**DNV**

Approval ID: TAE000037S



**cUL Recognized**

Approval ID: E255026



**UL Recognized**

Approval ID: E255026



**EAC**

Approval ID: RU C-DE.AI30.B.01102



**EAC**

Approval ID: RU C-DE.BL08.B.00511

**cULus Recognized**

# HC-EVO-B24-SHWD-2SSM32-PLRBK - Housing



1421370

<https://www.phoenixcontact.com/pc/products/1421370>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27440202 |
| ECLASS-12.0 | 27440202 |
| ECLASS-13.0 | 27440202 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC000437 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 31261500 |
|-------------|----------|

# HC-EVO-B24-SHWD-2SSM32-PLRBK - Housing



1421370

<https://www.phoenixcontact.com/pc/products/1421370>

## Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstraße 8  
D-32825 Blomberg  
+49 (0) 5235-3 00  
[info@phoenixcontact.com](mailto:info@phoenixcontact.com)