

CUC-PP-FR19:1U-I-EMPTY:24 BK - Marshalling panel



1422979

<https://www.phoenixcontact.com/us/products/1422979>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Marshalling panel, design: RJ45, degree of protection: IP20, material: PC-GF, connection method: Quick connection, housing size: 1, color: black



Your advantages

- Assembly without special tools
- Rugged design

Commercial data

Item number	1422979
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AB18
Product key	ABNLBA
Catalog page	Page 391 (C-2-2019)
GTIN	4055626319933
Weight per piece (including packing)	810 g
Weight per piece (excluding packing)	810 g
Customs tariff number	85389099
Country of origin	CN

Technical data

Product properties

Product type	Patch panel
Application	Installation slots for RJ45 cable connection module, adapter-free, and various FO couplings
Connection profile	RJ45
No. of cable outlets	24
Number of slots	24


Electrical properties

Insulation resistance	according to IEC 61010-1
Transmission medium	FO

Connection data

Connection method	Quick connection
-------------------	------------------

Dimensions

Dimensional drawing	
Width	482.6 mm
Height	43.6 mm
Depth	83.4 mm

Material specifications

Color	black
Material	Steel, galvanized
Flammability rating according to UL 94	V0
Housing material	PC-GF

Cable/line

Tensile strength short-term/long-term	150N (Modul)
---------------------------------------	--------------

Mechanical properties

Tensile strength short-term/long-term	150N (Modul)
---------------------------------------	--------------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
	IP20
Ambient temperature (operation)	5 °C ... 55 °C

CUC-PP-FR19:1U-I-EMPTY:24 BK - Marshalling panel



1422979

<https://www.phoenixcontact.com/us/products/1422979>

Ambient temperature (storage/transport)	-5 °C ... 55 °C
Ambient temperature (assembly)	-25 °C ... 55 °C

Mounting

Mounting type	19" rack
Assembly instructions	Observe the grounding concept

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com