

HC-M-05L-TPT-M - Contact insert module



1423961

<https://www.phoenixcontact.com/nz/products/1423961>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Contact insert module, number of positions: 5, power contacts: 5, control contacts: 0, number of connections per position: 2, Pin, Push-in connection, 230 V/400 V, 16 A, 0.25 mm² ... 1.5 mm², application: Power

Your advantages

- Easy installation without tools, even when mounted, with push-in connection technology
- Shortest installation time compared to other connection technologies
- Quick and effortless wiring, in particular when space is tight
- Automatic cabling with robots possible
- Safe wiring and operation with color-coded actuators
- Shock and vibration-resistant in accordance with DIN EN 61373
- Double conductor connection per pos.

Commercial data

Item number	1423961
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF7ACE
Product key	BF7ACE
Catalog page	Page 577 (C-2-2019)
GTIN	4055626365800
Weight per piece (including packing)	17.9 g
Weight per piece (excluding packing)	17 g
Country of origin	PL

HC-M-05L-TPT-M - Contact insert module



1423961

<https://www.phoenixcontact.com/nz/products/1423961>

Technical data

Notes

General	Use only flexible conductors with ferrule (in conjunction with CRIMPFOX 6 only)
General	Connectors may be operated only when there is no load/voltage.
General	For HEAVYCON housing type B6 to B48, HC-M-B...MF-... hinged module carrier frame required.

Mounting

Assembly instructions	To ensure correct use, installation in housing with IP54 protection or better is required
-----------------------	---

Product properties

Product type	Modular contact insert
Number of positions	5
Connection profile	5
Contact numbering	1 - 5
Application	Power
Number of connections per position	2
Number of module slots	1
No. of power contacts	5
No. of control contacts	0
Contact material type	rolled
Series	HC-M-05-T

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Connection data

Connection technology

Connection technology	Push-in connection
Number of connections per position	2

Conductor connection

Conductor cross section	0.25 mm ² ... 1.5 mm ²
Connection cross section AWG	24 ... 16
Stripping length of the individual wire	8 mm ± 1 mm

Dimensions


HC-M-05L-TPT-M - Contact insert module



1423961

<https://www.phoenixcontact.com/nz/products/1423961>

Dimensional drawing



Width	34 mm
Height	36 mm
Length	14.6 mm

Mechanical characteristics

Contact diameter	2.5 mm
------------------	--------

Electrical properties

Rated voltage (III/3)	230 V (Conductor-PE)
	400 V (Conductor-Conductor)
Rated voltage for power contacts	230/400 V
Rated surge voltage	4 kV
Rated current	16 A

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 500
-----------------------------	-------

Material specifications

Flammability rating according to UL 94	V0
Contact material	Copper alloy
Contact surface material	Ag
Contact carrier material	PA
Standards/regulations	PA: Fire protection in rail vehicles - requirement sets R22, R23, and R24 acc. to DIN EN 45545-2 (Risk level HL1 - HL3)

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-40 °C ... 125 °C
---------------------------------	-------------------

Standards and regulations

Constructional and testing regulations	DIN EN 61984
	DIN EN 60664
Tests	DIN EN 61984
	DIN EN 60664

Testing

Standards/regulations	PA: Fire protection in rail vehicles - requirement sets R22, R23, and R24 acc. to DIN EN 45545-2 (Risk level HL1 - HL3)
-----------------------	---

HC-M-05L-TPT-M - Contact insert module




1423961


<https://www.phoenixcontact.com/nz/products/1423961>

Drawings

Dimensional drawing



Dimensional drawing




HC-M-05L-TPT-M - Contact insert module

1423961


<https://www.phoenixcontact.com/nz/products/1423961>



Schematic diagram



Connector pin assignment, connection side



Derating diagram

HC-M-05L-TPT-M - Contact insert module



1423961

<https://www.phoenixcontact.com/nz/products/1423961>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/nz/products/1423961>

 UL Recognized Approval ID: E468743				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	600 V	16 A	-	-

 CSA Approval ID: 13631				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	600 V	12 A	- 16	-

 UL Recognized Approval ID: E118976				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	600 V	16 A	-	-

 EAC Approval ID: RU C-DE.BL08.B.00511				
---	--	--	--	--

 VDE Zeichengenehmigung Approval ID: 40050148				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	400 V	10 A	-	0.25 - 2.5

HC-M-05L-TPT-M - Contact insert module



1423961

<https://www.phoenixcontact.com/nz/products/1423961>

Classifications

ECLASS

ECLASS-11.0	27440217
ECLASS-12.0	27440217
ECLASS-13.0	27440217

ETIM

ETIM 9.0	EC000438
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

HC-M-05L-TPT-M - Contact insert module



1423961
<https://www.phoenixcontact.com/nz/products/1423961>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd
Unit 15C, 906-930 Great South Road, Penrose
Auckland 1061
0508 474 636
sales@phoenixcontact.co.nz